

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

TYPE I - RENEWABLE ENERGY PROJECTS

Note: Categories I.A, I.B and I.C involve renewable energy technologies that supply electricity, mechanical and thermal energy, respectively, to the user directly. Renewable energy technologies that supply electricity to a grid fall into category I.D.

Follow the link to find [General guidance](#) / [Abbreviations](#)

II.G. Energy Efficiency Measures in Thermal Applications of Non-Renewable Biomass

Technology/ Measure

1. This category comprises of small appliances involving the efficiency improvements in the thermal applications of non-renewable biomass. These technologies and measures include high efficiency cook stoves and ovens using non-renewable biomass. Project activities, which also involve the switch to renewable biomass, shall apply using category I-E.

Boundary

2. The project boundary is the physical, geographical area of the use of non-renewable biomass.

Baseline

3. It is assumed that in the absence of the project activity, the baseline scenario would be the use of fossil fuels commonly observed with local consumers, for meeting similar thermal energy needs.

4. Emission reductions would be calculated as:

$$ER_y = B_{y,savings} \cdot NCV_{biomass} \cdot EF_{non-renewable\ biomass,CO2}$$

where:

ER_y	Emission reductions during the year y in t CO ₂
$B_{y,savings}$	Quantity of non-renewable biomass that is saved in tonnes
$NCV_{biomass}$	Net calorific value of the non-renewable biomass that is substituted (IPCC default for wood fuel, 15 MJ/Kg)
$EF_{non-renewable\ biomass,CO2}$	Emission factor for the substitution of non-renewable biomass by similar consumers locally in t CO ₂ / TJ biomass.

$$B_{y,savings} = B_y \cdot \left(1 - \frac{h_{old}}{h_{new}}\right)$$

where:

B_y	Quantity of non-renewable biomass used in the absence of the project activity
η_{old}	Efficiency of the system being replaced, use 20% as default value or local data if available
η_{new}	Efficiency of the system being deployed as part of the project activity.

**Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories**

II.G. Energy Efficiency Measures in Thermal Applications of Non-Renewable Biomass (cont)

$$EF_{\text{non-renewable biomass,CO}_2} = \frac{e_{\text{stoves,biomass}}}{e_{\text{stoves,fossil}}} \cdot EF_{\text{CO}_2,\text{fossil}}$$

where:

estoves,biomass	Average efficiency of stoves fired with biomass, use 20% as default value or local data if available
estoves,fossil	Average efficiency of stoves fired with fossil fuel, use 50% as default value or local data if available
EFCO ₂ , fossil	CO ₂ emission factor for the fossil fuel; 71.5 tCO ₂ /TJ for Kerosene, 63.0 tCO ₂ /TJ for LPG or the IPCC default value of the fossil fuel commonly observed with local consumers

Leakage

5. No leakage calculation is required.

Monitoring

6. Monitoring shall consist of an annual check of all appliances or a representative sample thereof to ensure that they are still operating or replaced by an equivalent in service appliance. Monitoring shall include the efficiency of the appliances.
7. Monitoring shall ensure that the replaced low efficiency appliances are not used within the boundary.