



Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

TYPE II - ENERGY EFFICIENCY IMPROVEMENT PROJECTS

Project participants shall take into account the general guidance to the methodologies, information on additionality, abbreviations and general guidance on leakage provided at <http://cdm.unfccc.int/methodologies/SSCmethodologies/approved.html>.

II.E. Energy efficiency and fuel switching measures for buildings

Technology/measure

1. This category comprises any energy efficiency and fuel switching measure implemented at a single building, such as a commercial, institutional or residential building, or group of similar buildings, such as a school, district or university. This category covers project activities aimed primarily at energy efficiency; a project activity that involves primarily fuel switching falls into category III.B.¹ Examples include technical energy efficiency measures (such as efficient appliances, better insulation and optimal arrangement of equipment) and fuel switching measures (such as switching from oil to gas). The technologies may replace existing equipment or be installed in new facilities. The aggregate energy savings of a single project may not exceed the equivalent of 60 GWh per year.

2. This category is applicable to project activities where it is possible to directly measure and record the energy use within the project boundary (e.g. electricity and/or fossil fuel consumption).

3. This category is applicable to project activities where the impact of the measures implemented (improvements in energy efficiency) by the project activity can be clearly distinguished from changes in energy use due to other variables not influenced by the project activity (signal to noise ratio).

Boundary

4. The project boundary is the physical, geographical site of the building(s).

Baseline

5. The energy baseline consists of the energy use of the existing equipment that is replaced in the case of retrofit measures and of the facility that would otherwise be built in the case of a new facility.

6. Each energy form in the emission baseline is multiplied by an emission coefficient. For the electricity displaced, the emission coefficient is calculated in accordance with provisions under category I.D. For fossil fuels, the IPCC default values for emission coefficients may be used.

¹ Thus, fuel-switching measures that are part of a package of energy efficiency measures at a single location may be part of a project activity included in this project category.



Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

II.E. Energy efficiency and fuel switching measures for buildings (cont)

Leakage

7. If the energy efficiency technology is equipment transferred from another activity or if the existing equipment is transferred to another activity, leakage is to be considered.

Monitoring

8. In the case of retrofit measures, monitoring shall consist of:
- (a) Documenting the specifications of the equipment replaced;
 - (b) Calculating the energy savings due to the measures installed.
9. In the case of a new facility, monitoring shall consist of:
- (a) Metering the energy use of the building(s);
 - (b) Calculating the energy savings of the new building(s).

Project activity under a programme of activities

The following conditions apply for use of this methodology in a project activity under a programme of activities:

8. In case the project activity involves fossil fuel switching measures leakage resulting from fuel extraction, processing, liquefaction, transportation, re-gasification and distribution of fossil fuels outside of the project boundary shall be considered. The guidance provided in the leakage section of ACM009 as in annex 1 of this document shall be followed in this regard.

In case the project activity involves the replacement of equipment, and the leakage effect of the use of the replaced equipment in another activity is neglected because the replaced equipment is scrapped, an independent monitoring of scrapping of replaced equipment needs to be implemented. The monitoring should include a check if the number of project activity equipment distributed by the project and the number of scrapped equipment correspond with each other. For this purpose scrapped equipment should be stored until such correspondence has been checked. The scrapping of replaced equipment should be documented and independently verified.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

II.E. Energy efficiency and fuel switching measures for buildings (cont)

Annex 1

(GUIDANCE ON LEAKAGE BELOW CONCERNS PROJECT ACTIVITY UNDER A
PROGRAMME OF ACTIVITIES)

Leakage

1. Leakage may result from fuel extraction, processing, liquefaction, transportation, re-gasification and distribution of fossil fuels outside of the project boundary. This includes mainly fugitive CH₄ emissions and CO₂ emissions from associated fuel combustion and flaring. In this methodology, the following leakage emission sources shall be considered:²

- Fugitive CH₄ emissions associated with fuel extraction, processing, liquefaction, transportation, re-gasification and distribution of natural gas used in the project plant and fossil fuels used in the grid in the absence of the project activity.
- In the case LNG is used in the project plant: CO₂ emissions from fuel combustion / electricity consumption associated with the liquefaction, transportation, re-gasification and compression into a natural gas transmission or distribution system.

Thus, leakage emissions are calculated as follows:

$$LE_y = LE_{CH_4,y} + LE_{LNG,CO_2,y} \quad (1)$$

Where:

LE_y Leakage emissions during the year y in t CO₂e

$LE_{CH_4,y}$ Leakage emissions due to fugitive upstream CH₄ emissions in the year y in t CO₂e

$LE_{LNG,CO_2,y}$ Leakage emissions due to fossil fuel combustion / electricity consumption associated with the liquefaction, transportation, re-gasification and compression of LNG into a natural gas transmission or distribution system during the year y in t CO₂e

Note that to the extent that upstream emissions occur in Annex I countries that have ratified the Kyoto Protocol, from 1 January 2008 onwards, these emissions should be excluded, if technically possible, in the leakage calculations.

Fugitive methane emissions

For the purpose of determining fugitive methane emissions associated with the production – and in case of natural gas, the transportation and distribution of the fuels – project participants should multiply the quantity of natural gas consumed in all element processes *i* with a methane emission factor for these upstream emissions ($EF_{NG,upstream,CH_4}$), and subtract for all fuel types *k* which would be used in the absence of the project activity the fuel quantities multiplied with respective methane emission factors ($EF_{k,upstream,CH_4}$), as follows:

² The Meth Panel is undertaking further work on the estimation of leakage emission sources in case of fuel switch project activities. This approach may be revised based on outcome of this work.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

II.E. Energy efficiency and fuel switching measures for buildings (cont)

$$LE_{CH_4,y} = \left[FF_{project,y} \cdot NCV_{NG,y} \cdot EF_{NG,upstream,CH_4} - \sum_k FF_{baseline,k,y} \cdot NCV_k \cdot EF_{k,upstream,CH_4} \right] \cdot GWP_{CH_4} \quad (2)$$

with

$$FF_{project,y} = \sum_i FF_{project,i,y} \quad \text{and} \quad (3)$$

$$FF_{baseline,k,y} = \sum_i FF_{baseline,i,k,y} \quad (4)$$

Where:

| | |
|-------------------------|--|
| $L_{CH_4,y}$ | Leakage emissions due to upstream fugitive CH ₄ emissions in the year y in t CO ₂ e |
| $FF_{project,y}$ | Quantity of natural gas combusted in all element processes during the year y in m ³ |
| $FF_{project,i,y}$ | Quantity of natural gas combusted in the element process i during the year y in m ³ |
| $NCV_{NG,y}$ | Average net calorific value of the natural gas combusted during the year y in MWh/m ³ |
| $EF_{NG,upstream,CH_4}$ | Emission factor for upstream fugitive methane emissions from production, transportation and distribution of natural gas in t CH ₄ per MWh fuel supplied to final consumers |
| $FF_{baseline,k,y}$ | Quantity of fuel type k (a coal or petroleum fuel type) that would be combusted in the absence of the project activity in all element processes during the year y in a volume or mass unit |
| $FF_{baseline,i,k,y}$ | Quantity of fuel type k (a coal or petroleum fuel type) that would be combusted in the absence of the project activity in the element process i during the year y in a volume or mass unit |
| NCV_k | Average net calorific value of the fuel type k (a coal or petroleum fuel type) that would be combusted in the absence of the project activity during the year y in MWh per volume or mass unit |
| $EF_{k,upstream,CH_4}$ | Emission factor for upstream fugitive methane emissions from production of the fuel type k (a coal or petroleum fuel type) in t CH ₄ per MWh fuel produced |
| GWP_{CH_4} | Global warming potential of methane valid for the relevant commitment period |

Where reliable and accurate national data on fugitive CH₄ emissions associated with the production, and in case of natural gas, the transportation and distribution of the fuels is available, project participants should use this data to determine average emission factors by dividing the total quantity of CH₄ emissions by the quantity of fuel produced or supplied respectively.³ Where such data is not available, project participants may use the default values provided in Table 2 below. In this case, the

³ GHG inventory data reported to the UNFCCC as part of national communications can be used where country-specific approaches (and not IPCC Tier 1 default values) have been used to estimate emissions.

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

II.E. Energy efficiency and fuel switching measures for buildings (cont)

natural gas emission factor for the location of the project should be used, except in cases where it can be shown that the relevant system element (gas production and/or processing/transmission/distribution) is predominantly of recent vintage and built and operated to international standards, in which case the US/Canada values may be used.

Note that the emission factor for fugitive upstream emissions for natural gas ($EF_{NG,upstream,CH_4}$) should include fugitive emissions from production, processing, transport and distribution of natural gas, as indicated in the Table 2 below. Note further that in case of coal the emission factor is provided based on a mass unit and needs to be converted in an energy unit, taking into account the net calorific value of the coal.

Table 2: Default emission factors for fugitive CH₄ upstream emissions

| Activity | Unit | Default emission factor | Reference for the underlying emission factor range in Volume 3 of the 1996 Revised IPCC Guidelines |
|--|-----------------------------|-------------------------|--|
| Coal | | | |
| Underground mining | t CH ₄ / kt coal | 13.4 | Equations 1 and 4, p. 1.105 and 1.110 |
| Surface mining | t CH ₄ / kt coal | 0.8 | Equations 2 and 4, p.1.108 and 1.110 |
| Oil | | | |
| Production | t CH ₄ / PJ | 2.5 | Tables 1-60 to 1-64, p. 1.129 - 1.131 |
| Transport, refining and storage | t CH ₄ / PJ | 1.6 | Tables 1-60 to 1-64, p. 1.129 - 1.131 |
| Total | t CH ₄ / PJ | 4.1 | |
| Natural gas | | | |
| USA and Canada | | | |
| Production | t CH ₄ / PJ | 72 | Table 1-60, p. 1.129 |
| Processing, transport and distribution | t CH ₄ / PJ | 88 | Table 1-60, p. 1.129 |
| Total | t CH ₄ / PJ | 160 | |
| Eastern Europe and former USSR | | | |
| Production | t CH ₄ / PJ | 393 | Table 1-61, p. 1.129 |
| Processing, transport and distribution | t CH ₄ / PJ | 528 | Table 1-61, p. 1.129 |
| Total | t CH ₄ / PJ | 921 | |
| Western Europe | | | |
| Production | t CH ₄ / PJ | 21 | Table 1-62, p. 1.130 |
| Processing, transport and distribution | t CH ₄ / PJ | 85 | Table 1-62, p. 1.130 |
| Total | t CH ₄ / PJ | 105 | |
| Other oil exporting countries / Rest of world | | | |
| Production | t CH ₄ / PJ | 68 | Table 1-63 and 1-64, p. 1.130 and 1.131 |
| Processing, transport and distribution | t CH ₄ / PJ | 228 | Table 1-63 and 1-64, p. 1.130 and 1.131 |
| Total | t CH ₄ / PJ | 296 | |
| Note: The emission factors in this table have been derived from IPCC default Tier 1 emission factors provided in Volume 3 of the 1996 Revised IPCC Guidelines, by calculating the average of the provided default emission factor range. | | | |

CO₂ emissions from LNG

Where applicable, CO₂ emissions from fuel combustion / electricity consumption associated with the liquefaction, transportation, re-gasification and compression of LNG into a natural gas transmission or distribution system ($LE_{LNG,CO_2,y}$) should be estimated by multiplying the quantity of natural gas combusted in the project with an appropriate emission factor, as follows:



Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

II.E. Energy efficiency and fuel switching measures for buildings (cont)

$$LE_{LNG,CO_2,y} = FF_{project,y} \cdot EF_{CO_2,upstream,LNG} \quad (5)$$

Where:

- $LE_{LNG,CO_2,y}$ Leakage emissions due to fossil fuel combustion / electricity consumption associated with the liquefaction, transportation, re-gasification and compression of LNG into a natural gas transmission or distribution system during the year y in t CO₂e
- $FF_{project,y}$ Quantity of natural gas combusted in all element processes during the year y in m³
- $EF_{CO_2,upstream,LNG}$ Emission factor for upstream CO₂ emissions due to fossil fuel combustion / electricity consumption associated with the liquefaction, transportation, re-gasification and compression of LNG into a natural gas transmission or distribution system

Where reliable and accurate data on upstream CO₂ emissions due to fossil fuel combustion / electricity consumption associated with the liquefaction, transportation, re-gasification and compression of LNG into a natural gas transmission or distribution system is available, project participants should use this data to determine an average emission factor. Where such data is not available, project participants may assume a default value of 6 t CO₂/TJ as a rough approximation.⁴

⁴ This value has been derived on data published for North American LNG systems. “Barclay, M. and N. Denton, 2005. Selecting offshore LNG process. http://www.fwc.com/publications/tech_papers/files/LNJ091105p34-36.pdf (10th April 2006)”.