



1 **Draft revision** to the approved consolidated baseline and monitoring methodology ACM0013
2 **Consolidated baseline and monitoring methodology for “Construction and operation of new grid**
3 **connected fossil fuel fired power plants using a less GHG intensive technology”**

4 **I. SOURCE AND APPLICABILITY**

5 **Sources**

6 This consolidated baseline and monitoring methodology is based on elements from the following
7 proposed new methodologies:

- 8 • NM0215 “Baseline and Monitoring Methodology for Grid Connected High-efficiency Coal-
9 fired Electricity Generation in Countries Where Different Power Expansion Plans are
10 Formulated for Broadly Different Power Technologies and Where These Plans are Restrictive”
11 prepared by Huaneng Power International, Inc., Global Climate Change Institute of the
12 Tsinghua University and CDM Office of CWEME, China;
- 13 • NM0217 “Grid-connected supercritical coal-fired power generation” submitted by NTPC Ltd,
14 India, whose baseline study and project design document were prepared by Perspectives
15 Climate Change GmbH, Hamburg, Germany.

16 This methodology also refers to the latest approved versions of the following tools:

- 17 • “Tool to calculate the emission factor for an electricity system”;
- 18 • “Tool for the demonstration and assessment of additionality”;
- 19 • “Assessment of the validity of the current/original baseline and update of the baseline at the
20 renewal of the crediting period”.

21 For more information regarding the proposed new methodologies and the tools and their consideration
22 by the CDM Executive Board (the Board) please refer to <<http://cdm.unfccc.int/goto/MPappmeth>>.

23 **Selected approach from paragraph 48 of the CDM modalities and procedures**

24 “Emissions from a technology that represents an economically attractive course of action, taking into
25 account barriers to investment”.

26 and

27 “The average emissions of similar project activities undertaken in the previous five years, in similar
28 social, economic, environmental and technological circumstances, and whose performance is among the
29 top 20 per cent of their category”.

30 **Definitions**

31 For the purpose of this methodology the following definitions apply:

32 **Power plant.** A *power plant* is a facility for the generation of electric power **from thermal energy**
33 **produced by the combustion of a fuel.** In case where several power units have been installed at one
34 site, each unit should be considered as a power plant. **For example, two 600 MW coal-fired power units**
35 **installed at one site should be considered as two power plants.**

36 **Cogeneration plant.** A *cogeneration plant* is a plant that (i) **simultaneously generates heat and power**
37 **through combustion of fuels, and (ii) provides useful thermal energy to end-users which use the heat for**
38 **other purposes than power generation (e.g. industrial users, district heating, etc).**



39 **Fossil fuel category.** The *fossil fuel category* refers to the following three categories of fossil fuels in
40 Table 1.1 in Volume 2 Energy, Chapter 1, of the 2006 IPCC Guidelines: (i) **LIQUID** liquid fuels
41 (Crude oil and petroleum products), (ii) **SOLID** solid fuels (Coal and coal products) and (iii) **GAS** gas
42 (Natural Gas).

43 **Fossil fuel type.** The *fossil fuel type* refers to the fuel types as defined in Table 1.1 in Volume 2:
44 Energy, Chapter 1, of the 2006 IPCC Guidelines.

45 **Reference year v .** The *reference year v* is the most recent year prior to the date of submission of the
46 PDD for validation of the project activity, for which the required data from the power plants to be
47 included in the sample group for the emissions benchmark (as per guidance in the baseline emissions
48 section hereunder) is available. In any case, the *reference year v* cannot begin more than 2 years prior
49 to the date of submission of the PDD for validation of the project activity.

50 **Power generation technology** refers to one of the following technologies, ranked by their efficiency,
51 from the lowest to the highest efficiency, for each fossil fuel category:

- 52 • Solid fuels: subcritical technology, supercritical technology, and ultra-supercritical technology;
- 53 • Gaseous fuels: single cycle technology and combined cycle technology;
- 54 • Liquid fuels: single cycle technology and combined cycle technology.

55 The specifications of each technology are given in Appendix I. Additions and revisions to the definition
56 of the power plant technology may be proposed through the “Procedure for the submission and
57 consideration of requests for revision of AMs and tools for large scale CDM project activities”.

58 **Applicability**

59 The methodology is applicable under the following conditions:

- 60 • The project activity is the construction and operation of a new fossil fuel fired grid-connected
61 **electricity generation power** plant that uses a more efficient power generation technology¹ than
62 what would otherwise be used with the given fossil fuel category;
- 63 • **One A single** fossil fuel category should be used as main fuel in the project power plant. In
64 addition to this main fossil fuel category, small amounts of other fossil fuel categories can be
65 used for start-up or auxiliary purposes,² but they shall not comprise more than 3% of the total
66 fuels used annually on an energy basis;
- 67 • The project activity does not include the construction **and or** operation of a co-generation power
68 plant;
- 69 • The information, as required under this methodology, on power plants that are planned or under
70 construction, and the data, as required under this methodology, on fuel consumption and
71 electricity generation of recently constructed power plants are available;
- 72 • The identified baseline fuel category is used in more than 50% of total generation by utilities in
73 the geographical area within the host country, as defined later in the methodology, or in the
74 entire host country.³ To demonstrate this applicability condition data from the latest three years

¹ – A possible project activity could be, e.g. the construction and operation of a supercritical coal fired power plant.

² The DOE should verify that start-up or auxiliary fuels are only used during: the start-up periods of the power plant, or short periods of interruption in the supply of the main fuel due to technical or operational problems. This is to ensure that it is not a common practice, during the normal operation of the power plant, to fire or co-fire these categories of fuel as a multi-fuel power plant.

³ For the purpose of demonstrating compliance with the applicability condition the geographical area has to be limited by the physical borders of the host country and cannot be extended to neighboring non-Annex I



- 75 shall be used. Maximum value of same fossil fuel generation estimated for three years should
 76 be greater than 50%.; The identified baseline fuel category is used in more than 50% of the
 77 total rated capacity of power plants which were commissioned for commercial operation in the
 78 most recent five calendar/fiscal years prior to the publication of the CDM-PDD for global
 79 stakeholder consultation, within the electric grid⁴ to which the project plant will be connected;
- 80 • At least 5 new power plants can be identified as similar to the project plant in Step 1 of the
 81 baseline identification procedure;
 - 82 • The most likely technology, as determined in the section “Identification of the baseline
 83 scenario” below, fulfills the conditions presented in Step 3 of that section.

84 This methodology is only applicable to new electricity generation power plants. For project activities
 85 involving a retrofit of existing power plants facilities with the installation of highly efficient
 86 technologies, project participants are encouraged to submit new methodologies or submit a request for
 87 revision to existing methodologies, as appropriate. For project activities involving a switch to a less
 88 GHG intensive fossil fuel in existing power plants, project participants may use consider using
 89 approved methodology ACM0011 “Consolidated baseline methodology for fuel switching from coal
 90 and/or petroleum fuels to natural gas in existing power plants for electricity generation”. For project
 91 activities involving the construction and operation of a new power plant with less GHG intensive fossil
 92 fuel, project participants may use other approved methodologies (e.g. AM0029).

93 II. BASELINE METHODOLOGY PROCEDURE

94 Identification of the baseline scenario

95 The baseline scenario is identified based on an assessment of which new power generation technologies
 96 that use the same fossil fuel category as the project activity are currently being implemented in the
 97 geographical area (as defined in Step 1 below) of the project activity.

98 Project participants shall use the following steps to identify the most likely technology that would be
 99 applied in the baseline scenario (i.e. the baseline technology):

100 ***Step 1: Identify all new power plants similar to the project activity***

101 Identify all power plants (excluding power plants registered as CDM project activities but including
 102 power plants requesting registration as CDM project activities or under validation) which fulfill all of
 103 the following conditions when the CDM-PDD is published for global stakeholder consultation:

- 104 • The plant uses the same fossil fuel category as the project activity. The plant may use small
 105 amounts of fuels within another fossil fuel category than the main fuel category for start-up or
 106 auxiliary purposes, but these other fuels shall not comprise more than 3% of the total fuels used
 107 annually by the power plant on an energy basis;
- 108 • The plant is not a cogeneration plant;
- 109 • The plant has been issued with a government permit and has:
 - 110 ○ Either made the request for tender available to suppliers for acquiring major equipment;
 - 111 or
 - 112 ○ Signed contracts for equipment or construction/operation services;

countries, even if such an extended geographical area is used for the calculation of a benchmark emission factor.

⁴ The grid boundary is defined as per the latest version of the “Tool to calculate the emission factor for an electricity system” approved by the Board.



- 113 • The government permit has not been issued for more than 5 years;
- 114 • The plant has not yet started commercial operation;
- 115 • The plant has a comparable size to the project activity, defined as the range from 50% to 150%
- 116 of the rated capacity of the project plant; and
- 117 • The plant is planned to be operated in the same load category, i.e. at peak load (defined as a
- 118 load factor of less than 3,000 hours per year) or base load (defined as a load factor of more than
- 119 3,000 hours per year), as the project activity.

120 If the number of identified plants is less than 5 within the boundary of the grid to which the project
121 plant will be connected, the geographical area should be extended to the country. If the number of the
122 identified plants is still less than 5, the geographical area should be extended by including all
123 neighboring non-Annex I countries. If the number remains to be less than 5, all non-Annex I countries
124 in the continent should be considered.

125 For each identified power plant, document in the CDM-PDD in a table the following information: name
126 of the unit, operator of the unit, exact location of the unit, the power generation technology used, the
127 planned installed capacity of the unit, the year when the government permit was issued, and whether the
128 request for tender was made available to suppliers for acquiring major equipment or whether the
129 contracts for equipment or construction/operation services were signed. If this information is not
130 available or if less than 5 power plants could be identified in all non-Annex I countries in the continent,
131 then the methodology is not applicable.

132 ***Step 2: Determine the market share of each technology***

133 Based on the power generation technology and the installed capacity of each plant identified in Step 1
134 above, calculate the market share of each technology, by dividing the total rated capacity of each
135 technology by the total rated capacity of all identified plants.

136 ***Step 3: Identify the baseline technology***

137 Sort the market share of the technologies by their efficiency, from the lowest to the highest efficiency,
138 as ranked in the definition section of this methodology.

139 Add up the market shares of each technology one by one from the end of the least efficient technology
140 until the subtotal of market shares reaches 80% in terms of installed generation capacity. The most
141 efficient technology within this subset shall be selected as the baseline technology.

142 The methodology is applicable only if all of the following conditions are fulfilled:

- 143 (a) The baseline technology, as identified as per the procedure outlined above, is different from
144 and less efficient than the project technology; and
- 145 (b) The use of the baseline technology at the project activity site would be in compliance with all
146 mandatory applicable legal and regulatory requirements; and
- 147 (c) For both the baseline technology and the project technology, the project participants have
148 conducted one combined or two separate feasibility study(ies)⁵, which shall have the same level
149 of detail in the analysis for both technologies and shall contain at least the following
150 information:
 - 151 ○ A power plant design study which specifies the type of equipment and key design
152 parameters of the plant, including, inter alia, the type of the pre-heating system, the

⁵ Preliminary feasibility studies, or studies conducted for the FEL-2 stage or other equivalent project planning stage, are permitted if they contain the information as required by the methodology for the feasibility studies.

153 boiler, the turbine, the generator, the condenser, the air pollution control equipment, etc,
154 as well as all information on the key operating parameters, such as steam temperatures,
155 pressures, re-heating temperatures and pressures, condensing temperatures and
156 pressures, excess air ratio, etc;

- 157 ○ The design and operation efficiency of the technology;
- 158 ○ An estimate of all costs, including investment costs, fuel costs, and operating and
159 maintenance costs; and
- 160 ○ A specification of the fuel type(s) used.

161 The feasibility study(ies) shall be the one(s) that are used by the project proponent to make the
162 investment decision and shall be conducted based on the specific characteristics of the site
163 where the project activity is implemented, taking into account ambient conditions (e.g. air
164 temperature and humidity in the case of air cooling), fuel availability, and any other site-
165 specific characteristics.

166 The site characteristics and the fossil fuel type and its origin shall be the same for the baseline
167 technology and the project technology in the feasibility studies or an appropriate justification
168 for the differences shall be provided in the CDM-PDD.

169 ***Step 1: Identify plausible baseline scenarios***

170 The identification of alternative baseline scenarios should include all possible realistic and credible
171 alternatives that provide outputs or services comparable with the proposed CDM project activity
172 (including the proposed project activity without CDM benefits), i.e. all type of power plants that could
173 be constructed as alternative to the project activity within the project boundary, as defined in the section
174 “Project boundary” and in Step 2 of the section “Baseline emissions” below.

175 Alternatives to be analysed should include, *inter alia*:

- 176 ● The project activity not implemented as a CDM project;
- 177 ● The construction of one or several other power plants instead of the proposed project activity,
178 including:
 - 179 ○ Power generation using the same fossil fuel category as in the project activity, but
180 technologies other than that used in the project activity;
 - 181 ○ Power generation using fossil fuel categories other than that used in the project activity;
 - 182 ○ Other power generation technologies, such as renewable power generation.
- 183 ● Import of electricity from connected grids, including the possibility of new interconnections.

184 In establishing these scenarios, project participants should clearly identify and document which
185 category and type of fuel would be used in each alternative, taking into account the requirements of the
186 technology.

187 These alternatives need not consist solely of power plants of the same capacity, load factor and
188 operational characteristics (i.e. several smaller plants, or the share of a larger plant may be a reasonable
189 alternative to the project activity), however they should deliver similar services (e.g. peak vs. baseload
190 power). Note further that the baseline scenario candidates identified may not be available to project
191 participants, but could be available to other stakeholders within the grid boundary (e.g. other companies
192 investing in power capacity expansions). Ensure that all relevant power plant technologies that have
193 recently been constructed or are under construction or are being planned (e.g. documented in official
194 power expansion plans) are included as plausible alternatives. A clear description of each baseline



195 scenario alternative, including information on the technology, such as the efficiency and technical
196 lifetime, shall be provided in the CDM PDD.

197 The project participant shall exclude baseline scenarios that are not in compliance with all applicable
198 legal and regulatory requirements. If one or more scenarios are excluded, appropriate explanations and
199 documentation to support the exclusion of these scenarios shall be provided.

200 ***Step 2: Identify the economically most attractive baseline scenario alternative***

201 The economically most attractive baseline scenario alternative is identified using investment analysis.
202 The levelized cost of electricity production in \$/kWh should be used as financial indicator for
203 investment analysis. Calculate the suitable financial indicator for all alternatives remaining after Step
204 1. Include all relevant costs (including, for example, the investment cost, fuel costs and operation and
205 maintenance costs), and revenues (including subsidies/fiscal incentives,⁶ ODA, etc. where applicable),
206 and, as appropriate, non-market cost and benefits in the case of public investors.

207 The investment analysis should be presented in a transparent manner and all the relevant assumptions
208 should be provided in the CDM PDD, so that a reader can reproduce the analysis and obtain the same
209 results. Critical techno-economic parameters and assumptions (such as capital costs, fuel price
210 projections, lifetimes, the load factor of the power plant and discount rate or cost of capital) should be
211 clearly presented. Justify and/or cite assumptions in a manner that can be validated by the DOE. In
212 calculating the financial indicator, the risks of the alternatives can be included through the cash flow
213 pattern, subject to project-specific expectations and assumptions (e.g. insurance premiums can be used
214 in the calculation to reflect specific risk equivalents). Where assumptions, input data, and data sources
215 for the investment analysis differ across the project activity and its alternatives, differences should be
216 well substantiated.

217 The CDM PDD submitted for validation shall present a clear comparison of the financial indicator for
218 all scenario alternatives. The baseline scenario alternative that has the best indicator (i.e. the lowest
219 levelized cost of electricity production) can be pre-selected as the most plausible baseline scenario.

220 A sensitivity analysis shall be performed for all alternatives, to confirm that the conclusion regarding
221 the financial attractiveness is robust to reasonable variations in the critical assumptions (e.g. fuel prices
222 and the load factor). The investment analysis provides a valid argument in selecting the baseline
223 scenario only if it consistently supports (for a realistic range of assumptions) the conclusion that the
224 pre-selected baseline scenario is likely to remain the most economically and/or financially attractive.

225 If sensitivity analysis confirms the result, then select the most economically attractive alternative as the
226 most plausible baseline scenario. In case the sensitivity analysis is not fully conclusive, select the
227 baseline scenario alternative with the lowest emission rate among the alternatives that are the most
228 financially and/or economically attractive.

229 If the type of power plant identified as the baseline scenario is different from the power plant
230 technologies that have recently been constructed or are under construction or are being planned (e.g.
231 documented in official power expansion plans), the project participants shall provide explanations to
232 this apparent discrepancy between observations and what should be considered as rational economic
233 behavior.

234 If the emission rate of the selected baseline scenario is clearly below that of the project activity (e.g. the
235 baseline scenario is hydro, nuclear or biomass power), then the project activity should not be
236 considered to yield emission reductions, and this methodology cannot be applied.

⁶ Note the guidance by EB 22 on national and/or sectoral policies and regulations.



237 The methodology is only applicable if the most plausible baseline scenario is the construction of (a)
238 new power plant(s) using the same fossil fuel category as used in the project activity. This means that
239 if the most likely baseline scenario identified through the baseline identification procedure is the import
240 of electricity or the construction of a new power plant(s) that (partly) use renewable energy sources,
241 nuclear sources or other categories of fossil fuels than the fossil fuel category fired in the project
242 activity plant, then this methodology is not applicable.

243 **Additionality**

244 The latest version of the “Tool for the demonstration and assessment of additionality”, agreed by the
245 Board, should be applied to assess the additionality of the proposed project activity. Ensure
246 consistency with the procedure to determine the most likely baseline scenario as provided above. In the
247 case Option II (Investment comparison analysis) is applied in Sub-step 2b, it should be demonstrated
248 that the baseline alternative is available to the project participant(s).

249 Project participants shall use the following steps to demonstrate the additionality of the proposed
250 project activity:

251 ***Step 1: Identification of alternatives to the project activity***

252 The alternative scenarios shall be limited to two scenarios:

- 253 • The proposed project activity undertaken without being registered as a CDM project activity;
254 and
- 255 • Electricity is supplied by a new power plant applying the baseline technology, determined as
256 per the procedures for baseline identification.

257 ***Step 2: Investment Analysis***

258 This step should be implemented following Step 2 of the latest version of the “Tool for the
259 demonstration and assessment of additionality”, except where methodology-specific requirements are
260 set out further below. In validating the application of this step, Designated Operation Entities (DOEs)
261 shall carefully assess and verify the reliability and creditability of all data, rationales, assumptions,
262 justifications and documentation provided by the project participants to support the demonstration of
263 additionality. The elements checked during this assessment and the conclusions shall be documented
264 transparently in the validation report.

265 In applying this step, the investment comparison analysis (Option II) shall be used and the levelized
266 cost of electricity production shall be used as the financial indicator. The levelized cost of electricity
267 production in \$/kWh shall, where applicable:

- 268 • Include all relevant costs (including the investment cost, fuel costs and operation and
269 maintenance costs);
- 270 • Include subsidies/fiscal incentives/tax benefits,⁷ ODA, etc., and, as appropriate, non-market
271 cost and benefits in the case of public investors, if this is standard practice for the selection of
272 public investments in the host country. If the feed-in tariff of the project plant is higher than the
273 feed-in tariff which would apply to the baseline technology implemented at the project site,
274 then the difference between the feed-in tariffs shall be considered as a subsidy;
- 275 • Exclude income taxes, revenues from sales of electricity generation, and other revenues not
276 related to electricity sales (e.g. payments for capacity or reserve).

⁷ Note the guidance by EB 22 on national and/or sectoral policies and regulations.

277 The fuel type used for the investment analysis shall be the same in the two scenarios identified in Step
 278 1. The load factor used in the calculation for the proposed project activity shall be equal to or higher
 279 than the load factor used for the baseline scenario. Other assumptions and input data for the investment
 280 analysis shall not differ between the scenario of the project activity and the baseline scenario, unless
 281 differences can be well substantiated.

282 In applying the sensitivity analysis, critical assumptions, such as, inter alia, fuel prices and the load
 283 factor shall be varied. In particular, the sensitivity analysis regarding the fuel prices shall take into
 284 account the price development of the fossil fuel category in the host country in the past ten
 285 calendar/fiscal years prior to the publication of the CDM-PDD for global stakeholder consultation.

286 The proposed project activity is deemed additional if the investment analysis concludes that the
 287 levelized costs of electricity production are lower for the alternative scenario with the baseline
 288 technology than for the proposed project activity and if the sensitivity analysis consistently supports
 289 (for a realistic range of assumptions) the conclusion that the baseline scenario is likely to remain
 290 economically and/or financially more attractive than the proposed project activity.

291 **Project boundary**

292 The spatial extent of the project boundary includes the power plant at the project site and all power
 293 plants considered for the calculation of the baseline CO₂ emission factor ($EF_{BL,CO_2,y}$).

294 In the calculation of project emissions, only CO₂ emissions from fossil fuel combustion in the project
 295 plant are considered. In the calculation of baseline emissions, only CO₂ emissions from fossil fuel
 296 combustion in power plant(s) in the baseline are considered.

297 The greenhouse gases included in or excluded from the project boundary are shown in Table 1.

298 **Table 1: Overview of emissions sources included in or excluded from the project boundary**

	Source	Gas	Included?	Justification / Explanation
Baseline	Power generation in baseline	CO ₂	Yes	Main emission source
		CH ₄	No	Excluded for simplification. This is conservative
		N ₂ O	No	Excluded for simplification. This is conservative
Project Activity	On-site fuel combustion in the project plant	CO ₂	Yes	Main emission source
		CH ₄	No	Excluded for simplification
		N ₂ O	No	Excluded for simplification

299 **Project emissions**

300 The project activity is the on-site combustion of fossil fuels in the project plant to generate electricity.
 301 The CO₂ emissions from electricity generation in the project plant (PE_y) should be calculated as
 302 follows:

303
$$PE_y = \left[\sum_i FF_{i,y} \times NCV_{i,y} \right] \times EF_{FF,CO_2} \tag{1}$$

304 Where:

- PE_y = Project emissions in year y (tCO₂/yr)
 $FF_{i,y}$ = Quantity of fuel type i combusted in the project plant in year y (Mass or volume unit per year)
 $NCV_{i,y}$ = Weighted average net calorific value of fuel type i in year y (GJ per mass or volume unit)
 i = Fossil fuel types used in the project plant in year y
 EF_{FF,CO_2} = CO₂ emission factor of the fossil fuel type used in the project and the baseline (t CO₂/GJ)

305 Baseline emissions

306 Baseline emissions are calculated by multiplying the electricity generated in the project plant from
307 using fossil fuel types within the main fossil fuel category ($EG_{PJ,main_FF,y}$)⁸ with a baseline CO₂ emission
308 factor (EF_{BL,CO_2}), as follows:

$$309 \quad BE_y = EG_{PJ,main_FF,y} \times EF_{BL,CO_2} \quad (2)$$

310 and:

$$311 \quad EG_{PJ,main_FF,y} = EG_{PJ,y} \times \left[\frac{\sum_p (FC_{p,y} \cdot NCV_{p,y})}{\sum_p (FC_{p,y} \cdot NCV_{p,y}) + \sum_q (FC_{q,y} \cdot NCV_{q,y})} \right] \quad (3)$$

312 Where:

- BE_y = Baseline emissions in year y (tCO₂ / yr)
 $EG_{PJ,main_FF,y}$ = Net quantity of electricity generated in the project plant from using fossil fuel types within the main fossil fuel category in year y (MWh / yr)
 $EG_{PJ,y}$ = Total net quantity of electricity generated in the project plant in year y (MWh / yr)
 EF_{BL,CO_2} = Baseline emission factor (tCO₂/MWh)
 $FC_{p,y}$ = Quantity of fossil fuel type p consumed by the project plant in year y (Mass or volume unit / yr)
 $NCV_{p,y}$ = Average net calorific value of the fossil fuel type p consumed by the project plant in year y (GJ / Mass or volume unit)
 $FC_{q,y}$ = Quantity of fossil fuel type q consumed by the project plant in year y (Mass or volume unit / yr)
 $NCV_{q,y}$ = Average net calorific value of the fossil fuel type q consumed by the project plant in year y (GJ / Mass or volume unit)
 p = Fossil fuel types that are used in the project plant and that belong to the main fossil fuel category
 Eq = Fossil fuel types that are used in the project plant for auxiliary and start-up purposes

313

314

⁸ This methodology allows to claim emission reductions from using fossil fuels more efficiently for power generation, but does not account for any emission reductions from using less carbon intensive fuels. Given that the CO₂ emission factor and amount of any start-up/auxiliary fuels may differ between the project and the baseline, the crediting of emission reductions is limited to the electricity generated from the main fossil fuel only.

315 EF_{BL,CO_2} will be determined using the lowest value between (i) the emission factor of the
316 technology and fuel type that has been identified as the most likely baseline scenario, and (ii) a
317 benchmark emission factor determined based on the performance of the top 15% power plants that use
318 the same fuel category as the project plant and any technology available in the geographical area as
319 defined in Step 1.32 below.

320 Consequently, project participants shall use for EF_{BL,CO_2} the lowest value among the
321 following two options:

322 **Option Approach 1:** The emission factor of the technology and fuel type identified as the most
323 likely baseline scenario under “Identification of the baseline scenario” section above,
324 and calculated as follows:

$$325 \quad EF_{BL,CO_2} = 3.6 \cdot \frac{EF_{FF,CO_2}}{\eta_{BL}} \quad (4)$$

$$326 \quad EF_{BL,CO_2} = 3.6 \cdot \frac{\text{MIN}(EF_{FF,BL,CO_2}; EF_{FF,CO_2})}{\eta_{BL}}$$

327 Where:

EF_{BL,CO_2} = Baseline emission factor (t CO₂ / MWh)

EF_{FF,BL,CO_2} = CO₂ emission factor of the fossil fuel type that has been identified as the most likely baseline scenario (tCO₂/GJ)

EF_{FF,CO_2} = CO₂ emission factor of the fossil fuel type used in the project and the baseline (t CO₂ / GJ)

η_{BL} = Energy efficiency of the power generation technology that has been identified as the most likely baseline scenario

3.6 = Unit conversion factor from GJ to MWh

328 **Option Approach 2:** The average emissions intensity of all power plants j , corresponding to the
329 power plants whose performance is among the top 15 % of their category, using data
330 from the reference year v , and taking into account the technical development that would
331 likely have occurred in the time between the investment decision on the power plants j
332 and the investment decision on the project activity, as follows:

$$333 \quad EF_{BL,CO_2} = \frac{\sum_j FC_j \cdot NCV_j \cdot EF_{FF,CO_2}}{\sum_j EG_j}$$

$$334 \quad EF_{BL,CO_2} = \frac{EF_{FF,CO_2}}{\eta_{avg,j} + \Delta\eta \cdot d} \times 3.6 \quad (5)$$

335 with

$$336 \quad \eta_{avg,j} = 3.6 \times \frac{\sum_j EG_{j,v}}{\sum_j (FC_{j,v} \cdot NCV_{j,v})} \quad (6)$$

337

Where:

EF_{BL,CO_2}	=	Baseline emission factor (tCO ₂ /MWh)
$\eta_{avg,j}$	=	Weighted average efficiency of power plants j
$\Delta\eta$	=	Average annual efficiency improvement for newly constructed power plants that would likely have occurred due to technical development in the time between the investment decisions made for the power plants j and the investment decision made for the proposed project activity (1/yr)
d	=	Data vintage, expressing the time difference between the envisaged start of commercial operation of the proposed project activity and the average start time of commercial operation of power plants j (yr) ⁹
$FC_{j,v}$	=	Amount of fuel consumed by power plant j in the reference year v (Mass or volume unit per year)
$NCV_{j,v}$	=	Average net calorific value of the fossil fuel type consumed by power plant j in the reference year v (GJ/Mass or volume unit)
EF_{FF,CO_2}	=	CO ₂ emission factor of the fossil fuel type used in the project and the baseline (tCO ₂ /GJ)
$EG_{j,v}$	=	Net electricity generated and delivered to the grid by power plant j in the reference year v (MWh/yr)
J_j	=	The top 15% performing power plants (excluding cogeneration plants and including power plants registered as CDM project activities), as identified below, among all power plants in a defined geographical area that have a similar size, are operated at similar load and use a fuel type within the same fuel category as the project activity in the geographical area as identified in Step 1.3

338 In the following steps, the parameters $\eta_{avg,i}$ and $\Delta\eta$ are determined. In applying these steps, all
339 underlying data, the data sources and all calculations shall be transparently documented in the CDM-
340 PDD, in a manner that the reader can re-produce the calculations.

341 **Step 1: (1) For determination of the top 15% performer power plants j , the following step-wise**
342 **approach is used: Determination of $\eta_{avg,j}$**

343 Steps 1.1 to 1.3 may need to be applied in an iterative manner until the set of the similar plants is finally
344 identified.

345 **Step 1.1: Definition of similar plants to the project activity**

346 The sample group cohort of similar power plants used to calculate $\eta_{avg,i}$ should consist of all power
347 plants (except for cogeneration power plants) (including all power plants registered as CDM project
348 activities, requesting registration as CDM project activities, or under validation) that fulfill all of the
349 following conditions:¹⁰

- 350 • That use the same fossil fuel category (as the main fuel) as the project activity. This should
351 include power plants which use small amounts of fuels within another fossil fuel category than

⁹ An example for the determination of this parameters is provided in the section on “data and parameters not monitored”.

¹⁰ Cogeneration plants excluded from the sample group shall simultaneously generates heat and power in a specific installation through the combustion of fuels, and the heat generated shall be provided to end users which use the heat for other purposes than power generation (e.g. industrial users, district heating, etc). Hence, power plants that use the heat to produce extra electricity, as it is the case in natural gas combined cycle power plants, are not considered as cogeneration plants and shall be included in the sample group.

352 the main fuel for start-up or auxiliary purposes, but these other fuels shall not comprise more
353 than 3% of the total fuels used annually by the sample power plant on an energy basis;

- 354 • That started commercial operation within the four year period preceding the reference year v ,
355 which is initially set as the calendar/fiscal year prior to the date of publication of the CDM-
356 PDD for global stakeholder consultation have been constructed in the previous five years,
357 where the last year of this 5 years period should be the reference year v ;
- 358 • That are not co-generation plants;
- 359 • That have a comparable size to the project activity, defined as the range from 50% to 150% of
360 the rated capacity of the project plant;
- 361 • That are operated in the same load category, i.e. at peak load (defined as a load factor of less
362 than 3,000 hours per year) or base load (defined as a load factor of more than 3,000 hours per
363 year), as the project activity; and
- 364 • That have operated (supplied electricity to the grid) in the reference year v .

365 **Step 2: Definition of the geographical area**

366 The geographical area to identify similar power plants should be chosen in a manner that the total
367 number of power plants N in the sample group comprises at least 10 plants. As a default, the grid¹¹ to
368 which the project plant will be connected should be used. If the number of similar plants, as defined in
369 Step 1, within the grid boundary is less than 10, the geographical area should be extended to the
370 country. If the number of similar plants is still less than 10, the geographical area should be extended
371 by including all neighboring non-Annex I countries. If the number remains to be less than 10, all non-
372 Annex I countries in the continent should be considered.

373 If the necessary data on power plants of the sample group in the relevant geographical area are not
374 available, or if there are less than 10 similar power plants in all non-Annex I countries in the continent,
375 then data from power plants Annex I or OECD countries can be used instead for the remaining plants
376 required to complete the sample group.

377 **Step 1.2: Determination of the reference year v**

378 If the necessary data for all similar power plants within the electric grid¹² to which the project plant will
379 be connected are not available for the calendar/fiscal year prior to the date of publication of the CDM-
380 PDD for global stakeholder consultation, then the previous calendar/fiscal year should be selected as
381 the reference year v and Step 1.1 shall be applied for this year. If the necessary data for that year is also
382 not available, an earlier calendar/fiscal year(s) may be used as the reference year v and Step 1.1 shall be
383 applied for this year, until the reference year v is the calendar/fiscal year that starts between 3 and 4
384 years prior to the date of publication of the CDM-PDD for global stakeholder consultation. If the
385 necessary data is also not available for this calendar/fiscal year, then the methodology is not applicable.

386 **Step 1.3: Identification of the sample group cohort of power plants and the geographical area**

387 Identify all power plants n that are to be included in the sample group cohort of plants used to
388 determine $\eta_{avg,j}$ by applying the criteria in Step 1.1 and using the reference year v as determined in Step
389 1.2. Determine the total number N of all identified similar power plants that use the same fuel as the
390 project plant and any technology available within the geographical area, as defined in Step 2 above that
391 are connected to the grid¹² to which the project plant will be connected. The sample group should also

¹¹ The grid boundary is defined as per the latest version of the “Tool to calculate the emission factor for an electricity system” approved by the Board.

¹² The grid boundary is defined as per the latest version of the “Tool to calculate the emission factor for an electricity system” approved by the Board.



392 include all power plants within the geographical area registered as CDM project activities, which meet
393 the criteria defined in Step 1 above.

394 If the number of similar plants within the electric grid to which the project plant will be connected is
395 less than 10, then the geographical area should be extended to the country and Steps 1.1 and 1.2 should
396 be iterated for the country. If the number of similar plants is still less than 10, the geographical area
397 should be extended by including all neighboring non-Annex I countries and Steps 1.1 and 1.2 should be
398 iterated accordingly. If the number remains to be less than 10, all non-Annex I countries in the
399 continent should be considered and Steps 1.1 and 1.2 should be reiterated accordingly.

400 If the necessary data on the similar power plants in the relevant geographical area are not available, or
401 if there are less than 10 similar power plants in all non-Annex I countries in the continent, then the
402 methodology is not applicable.

403 **Step 1.4: Determination of the plant efficiencies**

404 Calculate the operational efficiency of each power plant n identified in the previous step. For each
405 plant, the most recent one-year data from the reference year v available shall be used, excluding the
406 period when testing of the plant was conducted. The operational efficiency of each power plant n in the
407 sample group cohort is calculated as follows:

$$408 \quad \eta_{n,v} = 3.6 \cdot \frac{EG_{n,v}}{FC_{n,v} \cdot NCV_{n,v}} \quad (7)$$

409 Where:

- $\eta_{n,v}$ = Operational efficiency of the power plant n in the reference year v
- $EG_{n,v}$ = Net electricity generated and delivered to the grid by the power plant n in the reference year v (MWh / yr)
- $FC_{n,v}$ = Quantity of fuel consumed in the power plant n in the reference year v (Mass or volume unit / yr)
- $NCV_{n,v}$ = Average net calorific value of the fuel type fired in power plant n in the reference year v (GJ / mass or volume unit)
- 3.6 = Unit conversion factor from GJ to MWh
- v = Reference year v
- n = All power plants identified in Step 1.3 in the defined geographical area that have a similar size, are operated at similar load and use a fuel type within the same fuel category as the project activity

410 **Step 1.5: Identification of the top 15% performer plants j**

411 Sort the sample group cohort of N plants from the power plants in a decreasing order of the operational
412 efficiency. Identify the top performer plants j as the plants with the 1st to J^{th} highest operational
413 efficiency, where the J (the total number of plants j) is calculated as the product of N (the total number
414 of plants n identified in Step 3)1.3) and 15%, rounded down if it is decimal.¹³ If the generation of all
415 identified plants j (the top performers) is less than 15% of the total generation of all plants n (the whole
416 sample group cohort), then the number of plants j included in the top performer group should be
417 enlarged until the group represents at least 15% of total generation of all plants n .

¹³ This is conservative as this limits the number of the top 15% performer plants, which will always lead to exclusion of the least efficient plant among them.

418 **Step 2: Determination of d**

419 The data vintage d , expressed in years, is determined as the time difference between the envisaged start
420 of commercial operation of the proposed project activity and the average start time of commercial
421 operation of power plants j .

422 **Step 3: Determination of $\Delta\eta$**

423 If d is determined to be less than 1 year, $\Delta\eta$ is set at zero; otherwise, the project participants may choose
424 between the following two options to determine $\Delta\eta$:

425 **Option A:** Determine $\Delta\eta$ based on historical data

426 Calculate $\Delta\eta$ based on the historical technical development observed in the applicable geographical
427 area as defined in Step 1.3. Determine $\Delta\eta$ based on the average annual improvement in the efficiency of
428 newly constructed power plants observed over a period of ten years in the applicable geographical area
429 by applying a regression analysis. The last year of the regression analysis shall be the calendar/fiscal
430 year prior to the reference year v . This option can be used only if a student test can demonstrate that the
431 relationship between plant efficiency and plant age is statically significant with 95% confidence;
432 otherwise Option B shall be applied. If the regression analysis determines $\Delta\eta$ to be less than zero, $\Delta\eta$ is
433 conservatively assumed to be zero.

434 Apply and document in the CDM-PDD the following steps:

- 435 • Step 3.A.1: Identify all power plants m within the applicable geographical area, as determined
436 in Step 1.3 above,
- 437 ○ That use the same fossil fuel category (as the main fuel) as the project activity. This
438 should include power plants which use small amounts of fuels within another fossil fuel
439 category than the main fuel for start-up or auxiliary purposes, but these other fuels shall
440 not comprise more than 3% of the total fuels used annually by the power plant on an
441 energy basis;
 - 442 ○ That are not co-generation plants;
 - 443 ○ That started commercial operation within the ten year period preceding the reference year
444 v (i.e. that started commercial operation within the years $v-10$ to $v-1$);
 - 445 ○ That have a comparable size to the project activity, defined as the range from 50% to
446 150% of the rated capacity of the project plant;
 - 447 ○ That are operated in the same load category, i.e. at peak load (defined as a load factor of
448 less than 3,000 hours per year) or base load (defined as a load factor of more than 3,000
449 hours per year), as the project activity;
 - 450 ○ That have supplied electricity to the grid in the reference year v .
- 451 • Step 3.A.2: Determine for each plant m the operational efficiency $\eta_{m,v}$ in the year v , by applying
452 the equation in Step 1.4 above for all power plants m and for the year in which the plant started
453 commercial operation;
- 454 • Step 3.A.3: Plot the efficiency of all power plants m over the date in which the power plants
455 started commercial operation and apply a linear regression analysis and determine the average
456 annual efficiency improvement $\Delta\eta$ as a function of the date of construction using the method of
457 least squares;

458 **Option B:** Use for $\Delta\eta$ a conservative default value of 0.3%.¹⁴

459 All the underlying data, data sources, calculations and steps to estimate $\eta_{avg,i}$, $\Delta\eta$ and d shall be
460 documented transparently in the CDM-PDD, including, inter alia, a list of the plants identified in Steps
461 1.3 and 1.5 for $\eta_{avg,i}$ and a list of the plants identified in Step 3.A.1 for $\Delta\eta$, as well as relevant data on
462 the fuel consumption and electricity generation of all identified power plants. The DOE shall check the
463 fuel consumption and electricity generation against records on purchased fuel and sold electricity for all
464 identified power plants; if such information is not available, the DOE may check against government
465 publications provided that the data are collected and verified by a governmental organization and they
466 are based on the actual fuel consumption and electricity generation of the plants and not derived from
467 other data (e.g. regulations).

468 ~~All steps should be documented transparently, including a list of the plants identified in Steps 3 and 5,~~
469 ~~as well as relevant data on the fuel consumption and electricity generation of all identified power~~
470 ~~plants.~~

471 **Leakage**

472 No leakage emissions are to be considered.

473 **Emission reductions**

474 To calculate the emission reductions the project participant shall apply the following equation:

$$475 \quad ER_y = BE_y - PE_y \quad (8)$$

476 Where:

ER_y = Emission reductions in year y (t CO₂ / yr)
 BE_y = Baseline emissions in year y (t CO₂ / yr)
 PE_y = Project emissions in year y (t CO₂ / yr)

477 **Changes required for methodology implementation in 2nd and 3rd crediting periods**

478 The required changes should be assessed using the tool for “Assessment of the validity of the
479 current/original baseline and update of the baseline at the renewal of the crediting period”. ~~At the~~
480 ~~renewal of a crediting period, project participants should assess whether the baseline scenario is still~~
481 ~~valid by applying the procedure to select the most plausible baseline scenario, as described above.~~

482 ~~Moreover, t~~ The baseline emission factor (EF_{BL,CO_2}) shall ~~should~~ be updated, applying both **Options**
483 **Approaches 1 and 2** and choosing for the subsequent crediting period again the lower value among the
484 two ~~options~~ approaches. For **Approach Option 1**, the most likely power plant technology identified in
485 the application of the procedure to select the baseline scenario should be used. ~~For Option 2, the~~
486 ~~baseline emission factor should be updated based on the most recent available data at the time of~~
487 ~~renewal of the crediting period.~~ For **Approach 2**, at the first renewal of the renewal crediting period, the
488 baseline emission factor should be recalculated using a new reference year v . The new reference year v
489 shall be the calendar/fiscal year which is two years after the actual start of commercial operation of the
490 project activity. This provision aims to reduce the data vintage (between the start of commercial
491 operation of the proposed project activity and the average start time of commercial operation of power
492 plants j) to less than one year for second and third crediting periods.

¹⁴ This is the upper end of the values assumed for the average annual efficiency improvement in the information note prepared by the Methodologies Panel at its 53rd meeting.



493 Data and parameters not monitored

Data / Parameter:	EF_{FF,BL,CO_2}
Data unit:	tCO ₂ /GJ
Description:	CO ₂ emission factor of the fossil fuel type that has been identified as the most likely baseline scenario
Source of data:	IPCC default values for the respective fuel type at the lower limit of the uncertainty at a 95% confidence interval as provided in table 1.4 of Chapter 1 of Vol. 2 (Energy) of the 2006 IPCC Guidelines on National GHG Inventories
Measurement procedures (if any):	-
Any comment:	-

494

Data / Parameter:	η_{BL}
Data unit:	-
Description:	Energy efficiency of the power generation technology that has been identified as the most likely baseline scenario
Source of data:	This parameter is determined as part of the baseline scenario selection procedure
Measurement procedures (if any):	-
Any comment:	As a conservative approach, the efficiency should be determined as the efficiency at optimum load, e.g., as provided by in the feasibility study(ies) conducted for the identified baseline power generation technology and for the project site. The efficiency shall be derived on a net basis, taking into account auxiliary equipment. The efficiency shall not be derived from any historical operational data from existing power plants. In addition, the adopted value shall not be lower than the minimum efficiency (if available) specified for the respective baseline technology in Appendix I

495

Data / Parameter:	$FC_{j,m,v}$, $FC_{m,v}$, and $FC_{n,v}$
Data unit:	Mass or volume unit / yr
Description:	Amount of fuel consumed by power plant j , m or n in the reference year v , where: <ul style="list-style-type: none"> j are the top 15% performer plants among all power plants in a defined geographical area that have a similar size, are operated at similar load and use a fuel type within the same fuel category as the project activity and any technology available within the geographical area, as defined in Step 1.32 under “Baseline emissions” section; m are all power plants in the defined geographical area as defined in Step 3.A.1 to determine $\Delta\eta$ under “Baseline emissions” section; n are all power plants (including power plants registered as CDM project activities) in the defined geographical area that have a similar size, are operated at similar load and use a fuel type within the same fuel category as the project activity and any technology available within the geographical area, as defined in Step 1.32 under “Baseline emissions” section
Source of data:	Measurements of the fuel consumption in each power plant j or n , e.g. provided in statistics from central/regional regulatory authorities
Measurement procedures (if any):	-
Any comment:	The DOE should verify that the data on fuel consumption is based on first-hand measurements of the actual quantity of fuel consumed by each power plant, and is not based on second-hand calculations or estimations

496



497

Data / Parameter:	$NCV_{i,v}$, $NCV_{m,v}$ and $NCV_{n,v}$
Data unit:	GJ/Mass or volume unit
Description:	<p>Average net calorific value of the fossil fuel type consumed by power plant j, m or n in the reference year v, where:</p> <ul style="list-style-type: none"> j are the top 15% performer plants among all power plants in a defined geographical area that have a similar size, are operated at similar load and use a fuel type within the same fuel category as the project activity and any technology available within the geographical area, as defined in Step 1.32 under the “Baseline emissions” section; m are all power plants in the defined geographical area as defined in Step 3 in Option A to determine $\Delta\eta$ under the “Baseline emissions” section; n are all power plants (including power plants registered as CDM project activities) in the defined geographical area that have a similar size, are operated at similar load and use a fuel type within the same fuel category as the project activity and any technology available within the geographical area, as defined in Step 1.32 under the “Baseline emissions” section
Source of data:	Use plant-specific data if available (e.g. from national energy balances if the fuel consumption of the plant is provided on an energy basis). Otherwise use well-documented and reliable regional or national average values. If such data are not available, IPCC default values may be used
Measurement procedures (if any):	-
Any comment:	-

498

Data / Parameter:	EF_{FF,CO_2}
Data unit:	tCO ₂ /GJ
Description:	CO ₂ emission factor of the fossil fuel type used in the project and the baseline (tCO ₂ /GJ)
Source of data:	IPCC default values of the fuel type used in the project plant at the lower limit of the uncertainty at a 95% confidence interval as provided in table 1.4 of Chapter 1 of Vol. 2 (Energy) of the 2006 IPCC Guidelines on National GHG Inventories. In the case that several fuel types may be used in the project plant according to the technology provider’s designs, use the fuel type with the lowest IPCC default value at the lower limit of the uncertainty
Measurement procedures (if any):	-
Any comment:	-

499



500

Data / Parameter:	$EG_{j,v}$, $EG_{m,v}$, and $EG_{n,v}$
Data unit:	MWh/yr
Description:	<p>Net electricity generated and delivered to the grid by power plant j, m or n in the reference year v, where:</p> <ul style="list-style-type: none"> j are the top 15% performer plants among all power plants in a defined geographical area that have a similar size, are operated at similar load and use a fuel type within the same fuel category as the project activity and any technology available within the geographical area, as defined in Step 1.32 under the “Baseline emissions” section; m are all power plants in the defined geographical area as defined in Step 3 in Option A to determine $\Delta\eta$ under the “Baseline emissions” section; n are all power plants (including power plants registered as CDM project activities) in the defined geographical area that have a similar size, are operated at similar load and use a fuel type within the same fuel category as the project activity and any technology available within the geographical area, as defined in Step 1.32 under the “Baseline emissions” section
Source of data:	Electricity generation statistics, e.g. from central-/regional regulatory authorities
Measurement procedures (if any):	-
Any comment:	-

501

Data / Parameter:	$\Delta\eta$
Data unit:	1/yr
Description:	Average annual efficiency improvement for newly constructed power plants that would likely have occurred due to technical development in the time between the investment decisions made for the power plants j and the investment decision made for the proposed project activity
Source of data:	Determined as per Option A or Option B in Step 3 of the “Baseline emissions” section above
Measurement procedures (if any):	-
Any comment:	-

502

Data / Parameter:	d
Data unit:	Years
Description:	Data vintage, expressing the time difference between the envisaged start of commercial operation of the proposed project activity and the average start time of commercial operation of power plant j
Source of data:	Determined as per Step 2 of the “Baseline emissions” section above. Documented evidence on the envisaged start of commercial operation of the proposed project activity shall be provided
Measurement procedures (if any):	-
Any comment:	For example: Assume that the proposed CDM project plant is scheduled to start commercial operation on 1 July 2012. Assume further that the average start time of commercial operation of power plants j is 1 January 2006. Therefore, the data vintage is calculated to be 6.5 years (the time difference between 1 July 2012 and 1 January 2006)



503 III. MONITORING METHODOLOGY

504 All data collected as part of monitoring plan should be archived electronically and be kept at least for 2
 505 years after the end of the last crediting period. One hundred per cent of the data should be monitored if
 506 not indicated otherwise in the comments in the tables below. All measurements should use calibrated
 507 measurement equipment according to relevant industry standards.

508 Data and parameters monitored

Data / Parameter:	$EG_{PJ,y}$
Data unit:	MWh / yr
Description:	Total net quantity of electricity generated in the project plant and fed into the grid in year y
Source of data:	Measurements by project participants
Measurement procedures (if any):	Electricity meters
Monitoring frequency:	Continuously
QA/QC procedures:	The metered net electricity generation should be cross-checked with receipts from sales
Any comment:	Ensure that $EG_{PJ,y}$ is the net electricity generation (the gross generation by the project plant minus all auxiliary electricity consumption of the plant). If the actual average load factor during a monitoring period increases above the value of the load factor assumed for the proposed project activity in the CDM-PDD by more than 5% (or the upper end of the load factor values tested in the sensitivity analysis, if it is higher than 5%), then a request for approval of post-registration changes shall be submitted following the Clean Development Mechanism Project Cycle Procedure

509

Data / Parameter:	$FC_{p,y}$
Data unit:	Mass or volume unit per year (e.g. ton/yr or m ³ /yr)
Description:	Quantity of fossil fuel type p consumed by the project plant in year y
Source of data:	Onsite measurements
Measurement procedures (if any):	<ul style="list-style-type: none"> • Use either mass or volume meters. In cases where fuel is supplied from small daily tanks, rulers can be used to determine mass or volume of the fuel consumed, with the following conditions: The ruler gauge must be part of the daily tank and calibrated at least once a year and have a book of control for recording the measurements (on a daily basis or per shift); • Accessories such as transducers, sonar and piezoelectronic devices are accepted if they are properly calibrated with the ruler gauge and receiving a reasonable maintenance; • In case of daily tanks with pre-heaters for heavy oil, the calibration will be made with the system at typical operational conditions
Monitoring frequency:	Continuously
QA/QC procedures:	The consistency of metered fuel consumption quantities should be cross-checked by an annual energy balance that is based on purchased quantities and stock changes Where the purchased fuel invoices can be identified specifically for the CDM project, the metered fuel consumption quantities should also be cross-checked with available purchase invoices from the financial records
Any comment:	Fossil fuel types p are those used in the project plant and that belong to the main fossil fuel category



510

Data / Parameter:	$FC_{q,y}$
Data unit:	Mass or volume unit per year (e.g. ton/yr or m ³ /yr)
Description:	Quantity of fossil fuel type q consumed by the project plant in year y
Source of data:	Onsite measurements
Measurement procedures (if any):	<ul style="list-style-type: none"> Use either mass or volume meters. In cases where fuel is supplied from small daily tanks, rulers can be used to determine mass or volume of the fuel consumed, with the following conditions: The ruler gauge must be part of the daily tank and calibrated at least once a year and have a book of control for recording the measurements (on a daily basis or per shift); Accessories such as transducers, sonar and piezoelectronic devices are accepted if they are properly calibrated with the ruler gauge and receiving a reasonable maintenance; In case of daily tanks with pre-heaters for heavy oil, the calibration will be made with the system at typical operational conditions
Monitoring frequency:	Continuously
QA/QC procedures:	<p>The consistency of metered fuel consumption quantities should be cross-checked by an annual energy balance that is based on purchased quantities and stock changes.</p> <p>Where the purchased fuel invoices can be identified specifically for the CDM project, the metered fuel consumption quantities should also be cross-checked with available purchase invoices from the financial records</p>
Any comment:	Fossil fuel types q are those used in the project plant and that belong to another fossil fuel category than the main fossil fuel category (i.e. auxiliary and start-up fuels)

511

Data / Parameter:	$FF_{i,y}$
Data unit:	Mass or volume unit per year (e.g. ton/yr or m ³ /yr)
Description:	Quantity of fuel type i combusted in the project plant in year y
Source of data:	Onsite measurements
Measurement procedures (if any):	<ul style="list-style-type: none"> Use either mass or volume meters. In cases where fuel is supplied from small daily tanks, rulers can be used to determine mass or volume of the fuel consumed, with the following conditions: The ruler gauge must be part of the daily tank and calibrated at least once a year and have a book of control for recording the measurements (on a daily basis or per shift); Accessories such as transducers, sonar and piezoelectronic devices are accepted if they are properly calibrated with the ruler gauge and receiving a reasonable maintenance; In case of daily tanks with pre-heaters for heavy oil, the calibration will be made with the system at typical operational conditions
Monitoring frequency:	Continuously
QA/QC procedures:	<p>The consistency of metered fuel consumption quantities should be cross-checked by an annual energy balance that is based on purchased quantities and stock changes.</p> <p>Where the purchased fuel invoices can be identified specifically for the CDM project, the metered fuel consumption quantities should also be cross-checked with available purchase invoices from the financial records</p>
Any comment:	-

512



Data / Parameter:	NCV _{i,y}											
Data unit:	GJ per mass or volume unit (e.g. GJ/ton or GJ/m ³)											
Description:	Weighted average net calorific value of fuel type <i>i</i> in year <i>y</i>											
Source of data:	The following data sources may be used if the relevant conditions apply:											
	<table border="1"> <thead> <tr> <th>Data source</th> <th>Conditions for using the data source</th> </tr> </thead> <tbody> <tr> <td>(a) Values provided by the fuel supplier in invoices</td> <td>This is the preferred source if the carbon fraction of the fuel is not provided (Option A)</td> </tr> <tr> <td>(b) Measurements by the project participants</td> <td>If (a) is not available</td> </tr> <tr> <td>(c) Regional or national default values</td> <td>If (a) is not available These sources can only be used for liquid fuels and should be based on well documented, reliable sources (such as national energy balances).</td> </tr> <tr> <td>(d) IPCC default values at the upper limit of the uncertainty at a 95% confidence interval as provided in Table 1.2 of Chapter 1 of Vol. 2 (Energy) of the 2006 IPCC Guidelines on National GHG Inventories</td> <td>If (a) is not available</td> </tr> </tbody> </table>	Data source	Conditions for using the data source	(a) Values provided by the fuel supplier in invoices	This is the preferred source if the carbon fraction of the fuel is not provided (Option A)	(b) Measurements by the project participants	If (a) is not available	(c) Regional or national default values	If (a) is not available These sources can only be used for liquid fuels and should be based on well documented, reliable sources (such as national energy balances).	(d) IPCC default values at the upper limit of the uncertainty at a 95% confidence interval as provided in Table 1.2 of Chapter 1 of Vol. 2 (Energy) of the 2006 IPCC Guidelines on National GHG Inventories	If (a) is not available	
Data source	Conditions for using the data source											
(a) Values provided by the fuel supplier in invoices	This is the preferred source if the carbon fraction of the fuel is not provided (Option A)											
(b) Measurements by the project participants	If (a) is not available											
(c) Regional or national default values	If (a) is not available These sources can only be used for liquid fuels and should be based on well documented, reliable sources (such as national energy balances).											
(d) IPCC default values at the upper limit of the uncertainty at a 95% confidence interval as provided in Table 1.2 of Chapter 1 of Vol. 2 (Energy) of the 2006 IPCC Guidelines on National GHG Inventories	If (a) is not available											
Measurement procedures (if any):	For (a) and (b): Measurements should be undertaken in line with national or international fuel standards											
Monitoring frequency:	For (a) and (b): The NCV should be obtained for each fuel delivery, from which weighted average annual values should be calculated For (c): Review appropriateness of the values annually For (d): Any future revision of the IPCC Guidelines should be taken into account											
QA/QC procedures:	Verify if the values under (a), (b) and (c) are within the uncertainty range of the IPCC default values as provided in Table 1.2, Vol. 2 of the 2006 IPCC Guidelines. If the values fall below this range collect additional information from the testing laboratory to justify the outcome or conduct additional measurements. The laboratories in (a), (b) or (c) should have ISO17025 accreditation or justify that they can comply with similar quality standards											
Any comment:	-											



514

Data / Parameter:	NCV _{p,v}											
Data unit:	GJ per mass or volume unit (e.g. GJ/ton or GJ/m ³)											
Description:	Average net calorific value of the fossil fuel type <i>p</i> consumed by the project plant in year <i>y</i>											
Source of data:	The following data sources may be used if the relevant conditions apply:											
	<table border="1"> <thead> <tr> <th>Data source</th> <th>Conditions for using the data source</th> </tr> </thead> <tbody> <tr> <td>(e) Values provided by the fuel supplier in invoices</td> <td>This is the preferred source if the carbon fraction of the fuel is not provided (Option A)</td> </tr> <tr> <td>(f) Measurements by the project participants</td> <td>If (a) is not available</td> </tr> <tr> <td>(g) Regional or national default values</td> <td>If (a) is not available These sources can only be used for liquid fuels and should be based on well documented, reliable sources (such as national energy balances).</td> </tr> <tr> <td>(h) IPCC default values at the upper limit of the uncertainty at a 95% confidence interval as provided in Table 1.2 of Chapter 1 of Vol. 2 (Energy) of the 2006 IPCC Guidelines on National GHG Inventories</td> <td>If (a) is not available</td> </tr> </tbody> </table>	Data source	Conditions for using the data source	(e) Values provided by the fuel supplier in invoices	This is the preferred source if the carbon fraction of the fuel is not provided (Option A)	(f) Measurements by the project participants	If (a) is not available	(g) Regional or national default values	If (a) is not available These sources can only be used for liquid fuels and should be based on well documented, reliable sources (such as national energy balances).	(h) IPCC default values at the upper limit of the uncertainty at a 95% confidence interval as provided in Table 1.2 of Chapter 1 of Vol. 2 (Energy) of the 2006 IPCC Guidelines on National GHG Inventories	If (a) is not available	
Data source	Conditions for using the data source											
(e) Values provided by the fuel supplier in invoices	This is the preferred source if the carbon fraction of the fuel is not provided (Option A)											
(f) Measurements by the project participants	If (a) is not available											
(g) Regional or national default values	If (a) is not available These sources can only be used for liquid fuels and should be based on well documented, reliable sources (such as national energy balances).											
(h) IPCC default values at the upper limit of the uncertainty at a 95% confidence interval as provided in Table 1.2 of Chapter 1 of Vol. 2 (Energy) of the 2006 IPCC Guidelines on National GHG Inventories	If (a) is not available											
Measurement procedures (if any):	For (a) and (b): Measurements should be undertaken in line with national or international fuel standards											
Monitoring frequency:	For (a) and (b): The NCV should be obtained for each fuel delivery, from which weighted average annual values should be calculated For (c): Review appropriateness of the values annually For (d): Any future revision of the IPCC Guidelines should be taken into account											
QA/QC procedures:	Verify if the values under (a), (b) and (c) are within the uncertainty range of the IPCC default values as provided in Table 1.2, Vol. 2 of the 2006 IPCC Guidelines. If the values fall below this range collect additional information from the testing laboratory to justify the outcome or conduct additional measurements. The laboratories in (a), (b) or (c) should have ISO17025 accreditation or justify that they can comply with similar quality standards											
Any comment:	Fossil fuel types <i>p</i> are those used in the project plant and that belong to the main fossil fuel category											

515



516

Data / Parameter:	NCV _{q,v}	
Data unit:	GJ per mass or volume unit (e.g. GJ/ton or GJ/m ³)	
Description:	Average net calorific value of the fossil fuel type <i>q</i> consumed by the project plant in year <i>y</i>	
Source of data:	The following data sources may be used if the relevant conditions apply:	
	Data source	Conditions for using the data source
	(i) Values provided by the fuel supplier in invoices	This is the preferred source if the carbon fraction of the fuel is not provided (Option A)
	(j) Measurements by the project participants	If (a) is not available
	(k) Regional or national default values	If (a) is not available These sources can only be used for liquid fuels and should be based on well documented, reliable sources (such as national energy balances).
	(l) IPCC default values at the upper limit of the uncertainty at a 95% confidence interval as provided in Table 1.2 of Chapter 1 of Vol. 2 (Energy) of the 2006 IPCC Guidelines on National GHG Inventories	If (a) is not available
Measurement procedures (if any):	For (a) and (b): Measurements should be undertaken in line with national or international fuel standards	
Monitoring frequency:	For (a) and (b): The NCV should be obtained for each fuel delivery, from which weighted average annual values should be calculated For (c): Review appropriateness of the values annually For (d): Any future revision of the IPCC Guidelines should be taken into account	
QA/QC procedures:	Verify if the values under (a), (b) and (c) are within the uncertainty range of the IPCC default values as provided in Table 1.2, Vol. 2 of the 2006 IPCC Guidelines. If the values fall below this range collect additional information from the testing laboratory to justify the outcome or conduct additional measurements. The laboratories in (a), (b) or (c) should have ISO17025 accreditation or justify that they can comply with similar quality standards	
Any comment:	Fossil fuel types <i>q</i> are those used in the project plant and that belong to another fossil fuel category than the main fossil fuel category (i.e. auxiliary and start-up fuels)	

517



518

Appendix I

519

Specifications of Power Generation Technologies

Power Generation Technology	Specifications	Minimum Value of Efficiency
Solid fuels		
Subcritical technology	The operating pressure of the main steam boiler is equal to or lower than 22 MPa	38.7% with water cooling and 36.6% with air cooling ¹⁵
Supercritical technology	The operating pressure of the main steam boiler is above 22 MPa The operating temperature of the main steam boiler is below 593°C ¹⁶	40.0% ¹⁷
Ultra-supercritical technology	The operating pressure of the main steam boiler is above 22 Mpa The operating temperature of the main steam boiler is above 593°C	Not available
Gaseous fuels		
Single cycle technology	Includes a gas turbine(s) but no steam turbine	Not available
Combined cycle technology	Includes a gas turbine(s) and its exhaust heat is recovered to generate power by a steam turbine(s)	Not available

520

521

History of the document

Version	Date	Nature of revision
05.0.0	EB 67, Annex # 11 May 2012	The revision: <ul style="list-style-type: none"> • Incorporates a more objective procedure to identify the baseline scenario; • Provides additional guidance for the investment comparison analysis for the demonstration of additionality; • Improves the procedure to determine the efficiency of the baseline technology; • Clarifies the data requirements and accounts for the potential impact of the data vintage of the plants used to determine the baseline efficiency through Approach/Option 2; • Changes title from “Consolidated baseline and monitoring methodology for new grid connected fossil fuel fired power plants using a less GHG intensive technology” to “Construction and operation of new grid connected fossil fuel fired power plants using a less GHG intensive technology”.
04.0.0	EB 56, Annex 7 17 September 2010	The revision: <ul style="list-style-type: none"> • Includes a definition for cogeneration plants; • Clarifies that the referential point in time for historical data, required in the calculation of baseline emissions, is the date of submission of the

¹⁵ Calculated as the average of measured efficiencies of the above-average plants of the Chinese subcritical coal plants, as reported by the China Electricity Council in 2010.

¹⁶ Internal Energy Agency. 2010. Power Generation from Coal.

¹⁷ Calculated as the average of measured efficiencies of the above-average plants of the Chinese supercritical coal plants, as reported by the China Electricity Council in 2010.



		<p>PDD for validation of the project activity;</p> <ul style="list-style-type: none"> • Expands the applicability of the methodology to power plants that fire other fuel categories, than the main one, for start-up or auxiliary purposes; • Includes minor editorial improvements.
03	EB 53, Annex 7 26 March 2010	The revision concerns mainly the determination of the emission factor under the baseline and under the project scenario to ensure that emission reductions are limited to those resulting from the higher efficiency of the power generation technology used in the project activity as compared to the baseline.
02.1	EB 46, Annex 8 25 March 2009	<p>The methodology was editorially revised:</p> <ul style="list-style-type: none"> • To correct error in the unit in equation 2 and 3; • To correct unit conversion factor from GJ to MWh in equation 4; • To include $EF_{FF,PJ,CO_2,y}$ in the monitoring table under 'data and parameters monitored'; and • To correct other unit inconsistencies and editorial errors.
02	EB 39, Annex 6 16 May 2008	The methodology was revised to clarify that in the fourth applicability condition the geographical area has to be limited by the physical borders of the host country and as such cannot be extended to neighboring non-Annex I countries.
01	EB 34, Annex 2 12 September 2007	Initial adoption.
<p>Decision Class: Regulatory Document Type: Standard Business Function: Methodology</p>		