

Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories

TYPE III - OTHER PROJECT ACTIVITIES

Follow the link to find [General guidance](#) / [Abbreviations](#)

III.E. Landfill Methane Recovery

Technology/measure

1. This project category comprises measures to capture and combust methane from landfills used for disposal of residues from human activities including municipal solid wastes and industrial wastes containing biodegradable organic matter.
2. If the recovered methane is used for heat and electricity generation the project can use a corresponding methodology under type I project activities.

Boundary

3. The project boundary is the physical, geographical site of the landfill where the gas is captured and destroyed/used.

Project Activity Direct Emissions

4. Total annual project activity related emissions shall be less than or equal to 15 kilo tonnes of CO₂ equivalent. Project activity emissions consists of:
 - (a) Methane not captured by the project and released to the atmosphere, which is estimated as the difference between the yearly methane generation potential and the sum of the methane recovered and combusted by the project activity.
 - (b) CO₂ emissions related to the power used by the project activity facilities. Emission factors for grid electricity or diesel fuel use as the case may be shall be calculated as described in category I.D

$$PE_y = (MB_y - MD_{y,project}) * GWP_{CH4} + PE_{y,power}$$

where:

PE_y :	project activity emissions in the year “y” (tonnes of CO ₂ equivalent)
MB_y	methane generation potential in the year y (tonnes of CH ₄)
$MD_{y,project}$	Methane estimated ex-ante in the project design document to be destroyed by flaring or fuelling in the project activity during the year “y” (tonnes of CH ₄).
GWP_{CH4}	Global Warming Potential for methane (value of 21)
$PE_{y,power}$	emissions through electricity or diesel consumption in the year “y”

Yearly Methane Generation Potential

5. The method below is used to evaluate the yearly methane generation potential in the landfill. The quantity of methane projected to be formed during a given year is estimated using a first order decay model based on the discrete time estimate method proposed in the IPCC Guidelines¹

¹ *Good Practice Guidance and Uncertainty Management in National Greenhouse Gas Inventories (IPCC, 2000)*

**Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories**

III.E. Landfill Methane Recovery (cont)

$$MB_y = \frac{16}{12} \cdot F \cdot DOC_f \cdot MCF \cdot \sum_{x=1}^y \sum_{j=A}^D A_{j,x} \cdot DOC_j \cdot (1 - e^{-k_j}) \cdot e^{-k_j \cdot (y-x)}$$

where:

- F is fraction of methane in the landfill gas (default 0.5)
- DOC_j is per cent of degradable organic carbon (by weight) in the waste type j
- DOC_f is fraction of DOC dissimilated to landfill gas (IPCC default 0.77)
- MCF is Methane Correction Factor (fraction, IPCC default 1.0)
- $A_{j,x}$ is amount of organic waste type j landfilled in the year x (tonnes/year)
- k_j is decay rate for the waste stream type j
- j is waste type distinguished into the waste categories (from A to D), as illustrated in the table below
- x is year since the landfill started receiving wastes: x runs from the first year of landfill operation (x=1) to the year for which emissions are calculated (x=y)
- y is year for which LFG emissions are calculated

Table III.E.1. Waste stream decay rates (k_j) and associated IPCC default values for DOC_j

Waste stream A to E	Per cent DOC_j (by weight)	Decay-rate (k_j)
A. Paper and textiles	40	0.023
B. Garden and park waste and other (non-food) putrescibles	17	0.023
C. Food waste	15	0.231
D. Wood and straw waste ¹⁾	30	0.023
E. Inert material	0	0

¹⁾ Excluding lignin-C

6. The amount of organic waste type “j” landfilled in each year “x” ($A_{j,x}$) should be known. Alternatively, it can be considered as constant through the years. If the pre-existing amount and composition of the waste in the landfill are unknown, they can be estimated by comparison with other landfills with similar conditions in regional or national levels, using parameters related to the attended population. For projects in which the landfill will be operated during the crediting period, the waste amount and composition shall be monitored.

Baseline

7. The baseline scenario is the situation where, in the absence of the project activity, biomass and other organic matter are left to decay within the project boundary and methane is emitted to the atmosphere. Baseline emissions shall exclude methane emissions that would have to be removed to comply with national or local safety requirement or legal regulations:

$$BE_y = (MD_{project,y} - MD_{reg,y}) \cdot GWP_{CH4}$$

Leakage

**Indicative simplified baseline and monitoring methodologies
for selected small-scale CDM project activity categories**

III.E. Landfill Methane Recovery (cont)

8. If the methane recovery technology is equipment transferred from another activity or if the existing equipment is transferred to another activity, leakage effects are to be considered.

Monitoring

9. Emission reductions achieved by the project activity in each year will be assessed ex-post through direct measurement of the amount of methane fuelled or flared. The maximal emission reduction in any year is limited to the yearly methane generation potential calculated in the project design document for that year.

10. The amount of methane recovered and fuelled or flared shall be monitored ex-post, using continuous flow meters. The fraction of methane in the landfill gas should be measured with a continuous analyser or, alternatively, with periodical measurements at a 95% confidence level. Temperature and pressure of the landfill gas are required to determine the density of methane combusted.

11. Regular maintenance should ensure optimal operation of flares. The flare efficiency, defined as the fraction of time in which the gas is combusted in the flare, multiplied by the efficiency of the flaring process, shall be monitored.

12. The emission reduction achieved by the project activity will be measured as the amount of methane recovered and destroyed by the project activity, calculated as:

$$ER_{project,y} = LFG_{burnt,y} * w_{CH4,y} * D_{CH4,y} * FE * GWP_{CH4}$$

where:

$ER_{project,y}$	emission reduction of the project activity in the year “y” (tonnes of CO2 eq.)
$LFG_{burnt,y}$	landfill gas flared or fuelled in the year “y” (m ³).
$w_{CH4,y}$	methane content in landfill gas in the year “y” (fraction).
$D_{CH4,y}$	methane Density in the Landfill gas flared or fuelled in the year “y” (tonnes/m ³).
FE	flare efficiency in the year “y” (fraction).

13. The method for integration of the terms in equation above to obtain the results for one year of measurements within the confidence level, as well as the methods and instruments used for metering, recording and processing the data obtained, shall be described in the project design document and monitored during the crediting period.

14. Flow meters, sampling devices and gas analysers shall be subject to regular maintenance, testing and calibration to ensure accuracy.