



Methodological tool

“Tool to determine the mass flow of a greenhouse gas in a gaseous stream”

(Version 02.0.0)

I. DEFINITIONS, SCOPE, APPLICABILITY AND PARAMETERS

Definitions

For the purpose of this tool, the following definitions apply:

Absolute humidity. Is the ratio between the mass of H₂O (vapor phase) in the gas and the mass of the dry gas.

Dry basis. A parameter that does not account for the H₂O present in the gas.

Gaseous stream. A mixture of gaseous components which may contain different fractions of N₂, CO₂, O₂, CO, H₂, CH₄, N₂O, NO, NO₂, SO₂, SF₆, PFCs and H₂O in the vapor phase and its absolute pressure must be below 10 atm or 1.013 MPa.¹ Other gases may be present (e.g. hydrocarbons) provided their total concentration represents less than 1% (v/v) of the total.² A dry gas or dry gaseous stream excludes the H₂O fraction and a wet gas or wet gaseous stream includes the H₂O fraction.

Moisture content. The H₂O concentration in mass of H₂O (vapor phase) per volume of dry gas at normal conditions, also referred to as NPT conditions, expressed in mg H₂O/m³ dry gas.

Normal conditions. As 0°C (273.15 K, 32°F) and 1 atm (101.325 kN/m², 101.325 kPa, 14.69 psia, 29.92 in Hg, 760 torr).

Relative humidity. The ratio between the partial pressure of H₂O in the gas and the saturation pressure at a given temperature.

Saturation (absolute) humidity. The maximum amount of H₂O (vapor phase) that the gas can contain at a given temperature and pressure, expressed as mass of H₂O per mass of the dry gas.

Wet basis. A parameter that accounts for the H₂O present in the gas.

¹ This condition is required because it is assumed in the calculations that the gas stream behaves as an ideal binary mixture of water vapor and an ideal gas. If the gaseous stream contains larger fractions of other gases, such as hydrocarbons other than methane or HFCs, the gas cannot be considered to be an ideal gas mixture. Moderate pressures will assure that gases behave as ideal gases.

² For the cases of landfill gas and exhaust gases from thermal oxidation using natural gas, it will be assumed that the total concentration of other gases represents less than 1% (v/v).



Scope and applicability

This tool provides procedures to determine the following parameter:

Parameter	SI Unit	Description
$F_{i,t}$	kg/h	Mass flow of greenhouse gas i (CO ₂ , CH ₄ , N ₂ O, SF ₆ or a PFC) in the gaseous stream in time interval t

The mass flow of a particular greenhouse gas is calculated based on measurements of: (a) the total volume flow or mass flow of the gas stream, (b) the volumetric fraction of the gas in the gas stream and (c) the gas composition and water content. The flow and volumetric fraction may be measured on a **dry basis or wet basis**. The tool covers the possible measurement combinations, providing six different calculation options to determine the mass flow of a particular greenhouse gas (Options A to F shown in Table 1).

Typical applications of this tool are methodologies where the flow and composition of residual or flared gases or exhaust gases are measured for the determination of baseline or project emissions.

Methodologies where CO₂ is the particular and only gas of interest should continue to adopt material balances as the means of flow determination and may not adopt this tool as material balances are the cost effective way of monitoring flow of CO₂.

The underlying methodology should specify:

- (a) The gaseous stream the tool should be applied to,
- (b) For which greenhouse gases the mass flow should be determined,
- (c) In which time intervals the flow of the gaseous stream should be measured, and
- (d) Situations where the simplification offered for calculating the molecular mass of the gaseous stream (equations (3) or (17)) is not valid (such as the gaseous stream is predominantly composed of a gas other than N₂).

II. PROCEDURE

The mass flow of a greenhouse gas i in a gaseous stream ($F_{i,t}$) is determined through measurement of the flow and volumetric fraction of the gaseous stream. Table 1 shows the different ways to make these measurements and the corresponding calculation option for $F_{i,t}$.

Project participants should document in the CDM-PDD which option is applied. $F_{i,t}$ should be calculated following the steps/guidance described for each option below.

**Table 1: Measurement options**

Option	Flow of gaseous stream	Volumetric fraction
A	Volume flow – dry basis	dry or wet basis ³
B	Volume flow – wet basis	dry basis
C	Volume flow – wet basis	wet basis
D	Mass flow – dry basis	dry or wet basis
E	Mass flow – wet basis	dry basis
F	Mass flow – wet basis	wet basis

Determination of the absolute humidity of the gaseous stream

The absolute humidity is a parameter required for Options B and E. It can be determined from measurement of the moisture content (Option 1), or by assuming the gaseous stream is dry or saturated in a simplified conservative approach (Option 2). Project participants should document in the CDM-PDD which option they apply.

Option 1: Calculation using measurement of the moisture content

This option provides a procedure to determine the absolute humidity of the gaseous stream ($m_{H_2O,t,db}$) from measurements of the moisture content of the gas, according to equation (1).

$$m_{H_2O,t,db} = \frac{C_{H_2O,t,db,n}}{10^6 * \rho_{t,db,n}} \quad (1)$$

Where:

- $m_{H_2O,t,db}$ = Absolute humidity of the gaseous stream in time interval t on a dry basis
= (kg H₂O/kg dry gas)
- $C_{H_2O,t,db,n}$ = Moisture content of the gaseous stream in time interval t on a dry basis at normal conditions (mg H₂O/m³ dry gas)
- $\rho_{t,db,n}$ = Density of the gaseous stream in time interval t on a dry basis at normal conditions
(kg dry gas/m³ dry gas)

The density of the gaseous stream on a dry basis at normal conditions ($\rho_{t,db,n}$) is determined as follows:

$$\rho_{t,db,n} = \frac{P_n * MM_{t,db}}{R_u * T_n} \quad (2)$$

³ Flow measurement on a dry basis is not feasible at reasonable costs for a wet gaseous stream, so there will be no difference in the readings for volumetric fraction in wet basis analyzers and dry basis analyzers and both types can be used indistinctly for calculation Options A and D.



Where:

- $\rho_{t,db,n}$ = Density of the gaseous stream in time interval t on a dry basis at normal conditions (kg dry gas/m³ dry gas)
- P_n = Absolute pressure at normal conditions (Pa)
- T_n = Temperature at normal conditions (K)
- $MM_{t,db}$ = Molecular mass of the gaseous stream in a time interval t on a dry basis (kg dry gas/kmol dry gas)
- R_u = Universal ideal gases constant (Pa.m³/kmol.K)

The molecular mass of the gaseous stream ($MM_{t,db}$) is estimated as follows:

$$MM_{t,db} = \sum_k (v_{k,t,db} * MM_k) \quad (3)$$

Where:

- $MM_{t,db}$ = Molecular mass of the gaseous stream in time interval t on a dry basis (kg dry gas/kmol dry gas)
- $v_{k,t,db}$ = Volumetric fraction of gas k in the gaseous stream in time interval t on a dry basis (m³ gas k/m³ dry gas)
- MM_k = Molecular mass of gas k (kg/kmol)
- k = All gases, except H₂O, contained in the gaseous stream (e.g. N₂, CO₂, O₂, CO, H₂, CH₄, N₂O, NO, NO₂, SO₂, SF₆ and PFCs). See available simplification below

The determination of the molecular mass of the gaseous stream ($MM_{t,db}$) requires measuring the volumetric fraction of all gases (k) in the gaseous stream. However as a simplification, the volumetric fraction of only the gases k that are greenhouse gases and are considered in the emission reduction calculation in the underlying methodology must be monitored and the difference to 100% may be considered as pure nitrogen. The simplification is not acceptable if it is differently specified in the underlying methodology.

Option 2: Simplified calculation without measurement of the moisture content

This option provides a simple and conservative approach to determine the absolute humidity by assuming the gaseous stream is dry or saturated depending on which is the conservative situation.⁴

If it is conservative to assume that the gaseous stream is dry, then $m_{H_2O,t,db}$ is assumed to equal 0. If it is conservative to assume that the gaseous stream is saturated, then $m_{H_2O,t,db}$ is assumed to equal the saturation absolute humidity ($m_{H_2O,t,db,sat}$) and calculated using equation (4).

$$m_{H_2O,t,db,Sat} = \frac{p_{H_2O,t,Sat} * MM_{H_2O}}{(P_t - p_{H_2O,t,Sat}) * MM_{t,db}} \quad (4)$$

⁴ An assumption that the gaseous stream is saturated is conservative for the situation that the mass flow of greenhouse gas i is underestimated (applicable for calculating baseline emissions). Conversely, an assumption that the gas stream is dry is conservative for the situation that the greenhouse gas i is overestimated (applicable for calculating project emissions).



Where:

$m_{\text{H}_2\text{O},t,\text{db},\text{sat}}$	= Saturation absolute humidity in time interval t on a dry basis (kg H ₂ O/kg dry gas)
$p_{\text{H}_2\text{O},t,\text{Sat}}$	= Saturation pressure of H ₂ O at temperature T_t in time interval t (Pa)
T_t	= Temperature of the gaseous stream in time interval t (K)
P_t	= Absolute pressure of the gaseous stream in time interval t (Pa)
$MM_{\text{H}_2\text{O}}$	= Molecular mass of H ₂ O (kg H ₂ O/kmol H ₂ O)
$MM_{t,\text{db}}$	= Molecular mass of the gaseous stream in a time interval t on a dry basis (kg dry gas/kmol dry gas)

Parameter $MM_{t,\text{db}}$ is estimated using equation (3).

Option A

Flow measurement on a dry basis is not doable for a wet gaseous stream. Therefore, it is necessary to demonstrate that the gaseous stream is dry to use this option. There are two ways to do this:

- Measure the moisture content of the gaseous stream ($C_{\text{H}_2\text{O},t,\text{db},n}$) and demonstrate that this is less or equal to 0.05 kg H₂O/m³ dry gas; or
- Demonstrate that the temperature of the gaseous stream (T_t) is less than 60°C (333.15 K) at the flow measurement point.

If it cannot be demonstrated that the gaseous stream is dry, then the flow measurement should be assumed to be on a wet basis and the corresponding option from Table 1 should be applied instead.

The mass flow of greenhouse gas i ($F_{i,t}$) is determined as follows:

$$F_{i,t} = V_{t,\text{db}} * v_{i,t,\text{db}} * \rho_{i,t} \quad (5)$$

With

$$\rho_{i,t} = \frac{P_t * MM_i}{R_u * T_t} \quad (6)$$

Where:

$F_{i,t}$	= Mass flow of greenhouse gas i in the gaseous stream in time interval t (kg gas/h)
$V_{t,\text{db}}$	= Volumetric flow of the gaseous stream in time interval t on a dry basis (m ³ dry gas/h)
$v_{i,t,\text{db}}$	= Volumetric fraction of greenhouse gas i in the gaseous stream in a time interval t on a dry basis (m ³ gas i /m ³ dry gas)
$\rho_{i,t}$	= Density of greenhouse gas i in the gaseous stream in time interval t (kg gas i /m ³ gas i)
P_t	= Absolute pressure of the gaseous stream in time interval t (Pa)
MM_i	= Molecular mass of greenhouse gas i (kg/kmol)
R_u	= Universal ideal gases constant (Pa.m ³ /kmol.K)
T_t	= Temperature of the gaseous stream in time interval t (K)

**Option B**

The mass flow of greenhouse gas i ($F_{i,t}$) is determined using equations (5) and (6). The volumetric flow of the gaseous stream in time interval t on a dry basis ($V_{t,db}$) is determined by converting the measured volumetric flow from wet basis to dry basis as follows:

$$V_{t,db} = V_{t,wb} / (1 + v_{H_2O,t,db}) \quad (7)$$

Where:

- $V_{t,db}$ = Volumetric flow of the gaseous stream in time interval t on a dry basis (m³ dry gas/h)
 $V_{t,wb}$ = Volumetric flow of the gaseous stream in time interval t on a wet basis (m³ wet gas/h)
 $v_{H_2O,t,db}$ = Volumetric fraction of H₂O in the gaseous stream in time interval t on a dry basis (m³ H₂O/m³ dry gas)

The volumetric fraction of H₂O in time interval t on a dry basis ($v_{H_2O,t,db}$) is estimated according to equation (8).

$$v_{H_2O,t,db} = \frac{m_{H_2O,t,db} * MM_{t,db}}{MM_{H_2O}} \quad (8)$$

Where:

- $v_{H_2O,t,db}$ = Volumetric fraction of H₂O in the gaseous stream in time interval t on a dry basis (m³ H₂O/m³ dry gas)
 $m_{H_2O,t,db}$ = Absolute humidity in the gaseous stream in time interval t on a dry basis (kg H₂O/kg dry gas)
 $MM_{t,db}$ = Molecular mass of the gaseous stream in time interval t on a dry basis (kg dry gas/kmol dry gas)
 MM_{H_2O} = Molecular mass of H₂O (kg H₂O/kmol H₂O)

The absolute humidity of the gaseous stream ($m_{H_2O,t,db}$) is determined using either Option 1 or 2 specified in the Determination of the absolute humidity of the gaseous stream section of the tool and the molecular mass of the gaseous stream ($MM_{t,db}$) is determined using equation (3).

Option C

The mass flow of greenhouse gas i ($F_{i,t}$) is determined as follows:

$$F_{i,t} = V_{t,wb,n} * v_{i,t,wb} * \rho_{i,n} \quad (9)$$

with

$$\rho_{i,n} = \frac{P_n * MM_i}{R_u * T_n} \quad (10)$$



Where:

$F_{i,t}$	= Mass flow of greenhouse gas i in the gaseous stream in time interval t (kg gas/h)
$V_{t,wb,n}$	= Volumetric flow of the gaseous stream in time interval t on a wet basis at normal conditions (m^3 wet gas/h)
$V_{i,t,wb}$	= Volumetric fraction of greenhouse gas i in the gaseous stream in time interval t on a wet basis (m^3 gas i/m^3 wet gas)
$\rho_{i,n}$	= Density of greenhouse gas i in the gaseous stream at normal conditions (kg gas i/m^3 wet gas i)
P_n	= Absolute pressure at normal conditions (Pa)
T_n	= Temperature at normal conditions (K)
MM_i	= Molecular mass of greenhouse gas i (kg/kmol)
R_u	= Universal ideal gases constant ($Pa \cdot m^3/kmol \cdot K$)

The following equation should be used to convert the volumetric flow of the gaseous stream from actual conditions to normal conditions of temperature and pressure:

$$V_{t,wb,n} = V_{t,wb} \cdot [(T_n/T_t) \cdot (P_t/P_n)] \quad (11)$$

Where:

$V_{t,wb,n}$	= Volumetric flow of the gaseous stream in a time interval t on a wet basis at normal conditions (m^3 wet gas/h)
$V_{t,wb}$	= Volumetric flow of the gaseous stream in time interval t on a wet basis (m^3 wet gas/h)
P_t	= Pressure of the gaseous stream in time interval t (Pa)
T_t	= Temperature of the gaseous stream in time interval t (K)
P_n	= Absolute pressure at normal conditions (Pa)
T_n	= Temperature at normal conditions (K)

Option D

Flow measurement on a dry basis is not doable for a wet gaseous stream. Therefore, it is necessary to demonstrate that the gaseous stream is dry to use this option. There are two ways to do this:

- Measure the moisture content of the gaseous stream ($C_{H_2O,t,db,n}$) and demonstrate that this is less or equal to $0.05 \text{ kg H}_2\text{O}/m^3$ dry gas; or
- Demonstrate that the temperature of the gaseous stream (T_t) is less than 60°C (333.15 K)d at the flow measurement point.

If it cannot be demonstrated that the gaseous stream is dry, then the flow measurement should be assumed to be on a wet basis and the corresponding option from Table 1 should be applied instead.

The mass flow of greenhouse gas i ($F_{i,t}$) is determined using equations (5) and (6). The volumetric flow of the gaseous stream in time interval t on a dry basis ($V_{t,db}$) is determined by converting the mass flow of the gaseous stream to a volumetric flow as follows:



$$V_{t,db} = M_{t,db} / \rho_{t,db} \quad (12)$$

Where:

- $V_{t,db}$ = Volumetric flow of the gaseous stream in time interval t on a dry basis (m^3 dry gas/h)
 $M_{t,db}$ = Mass flow of the gaseous stream in time interval t on a dry basis (kg/h)
 $\rho_{t,db}$ = Density of the gaseous stream in time interval t on a dry basis (kg dry gas/ m^3 dry gas)

The density of the gaseous stream ($\rho_{t,db}$) should be determined as follows:

$$\rho_{t,db} = \frac{P_t * MM_{t,db}}{R_u * T_t} \quad (13)$$

Where:

- $\rho_{t,db}$ = Density of the gaseous stream in a time interval t on a dry basis (kg dry gas/ m^3 dry gas)
 $MM_{t,db}$ = Molecular mass of the gaseous stream in a time interval t on a dry basis (kg dry gas/kmol dry gas)
 P_t = Pressure of the gaseous stream in time interval t (Pa)
 T_t = Temperature of the gaseous stream in time interval t (K)

The molecular mass of the gaseous stream ($MM_{t,db}$) is estimated using equation (3).

Option E

The mass flow of greenhouse gas i ($F_{i,t}$) is determined using equations (5) and (6). The volumetric flow of the gaseous stream in time interval t on a dry basis ($V_{t,db}$) is determined in two steps. First the mass flow of the gaseous stream in time interval t on a wet basis ($M_{t,wb}$) is converted from wet basis to dry basis as follows:

$$M_{t,db} = M_{t,wb} / (1 + m_{H_2O,t,db}) \quad (14)$$

Where:

- $M_{t,db}$ = Mass flow of the gaseous stream in time interval t on a dry basis (kg/h)
 $M_{t,wb}$ = Mass flow of the gaseous stream in time interval t on a wet basis (kg/h)
 $m_{H_2O,t,db}$ = Absolute humidity of H_2O in the gaseous stream in a time interval t on a dry basis (kg H_2O /kg dry gas)

Then, the mass flow of the gaseous stream in time interval t on a dry basis ($M_{t,db}$) is converted to the volumetric flow of the gaseous stream in time interval t on a dry basis ($V_{t,db}$) using equation (12).

The absolute humidity of the gaseous stream ($m_{H_2O,t,db}$) is determined using either Option 1 or 2 specified in the “Determination of the absolute humidity of the gaseous stream” section of the tool.

**Option F**

The mass flow of greenhouse gas i ($F_{i,t}$) is determined using equations (9), (10), and the following equations:

$$V_{t,wb,n} = M_{t,wb} / \rho_{t,wb,n} \quad (15)$$

and

$$\rho_{t,wb,n} = \frac{P_n * MM_{t,wb}}{R_u * T_n} \quad (16)$$

Where:

- $V_{t,wb,n}$ = Volumetric flow of the gaseous stream in time interval t at normal conditions on a wet basis (m^3 wet gas/h)
- $V_{i,t,wb}$ = Volumetric fraction of greenhouse gas i in the gaseous stream in time interval t on a wet basis (m^3 gas i/m^3 wet gas)
- $M_{t,wb}$ = Mass flow of the gaseous stream in time interval t on a wet basis (kg/h)
- $\rho_{t,wb,n}$ = Density of the gaseous stream in time interval t on a wet basis at normal conditions (kg wet gas/ m^3 wet gas)
- P_n = Absolute pressure at normal conditions (Pa)
- T_n = Temperature at normal conditions (K)
- $MM_{t,wb}$ = Molecular mass of the gaseous stream in time interval t on a wet basis (kg wet gas/kmol wet gas)
- R_u = Universal ideal gases constant (Pa. m^3 /kmol.K)

The molecular mass of the gaseous stream ($MM_{t,wb}$) is determined as follows:

$$MM_{t,wb} = \sum_k (v_{k,t,wb} * MM_k) \quad (17)$$

Where:

- $MM_{t,wb}$ = Molecular mass of the gaseous stream in time interval t on a wet basis (kg wet gas/kmol wet gas)
- $v_{k,t,wb}$ = Volumetric fraction of gas k in the gaseous stream in time interval t on a wet basis (m^3 gas k/m^3 wet gas)
- MM_k = Molecular mass of gas k (kg/kmol)
- k = All gases contained in the gaseous stream (e.g. N_2 , CO_2 , O_2 , CO , H_2 , CH_4 , N_2O , NO , NO_2 , SO_2 , SF_6 and PFCs and H_2O in vapor phase). See available simplification below

The determination of the molecular mass of the gaseous stream ($MM_{t,wb}$) requires measuring the volumetric fraction of all gases (k) in the gaseous stream. However as a simplification, the volumetric fraction of only the gases k that are greenhouse gases and are considered in the emission reduction calculation in the underlying methodology must be monitored and the difference to 100% may be



considered as pure nitrogen. The simplification is not acceptable if it is differently specified in the underlying methodology.

Data and parameters not monitored

Data / Parameter:	R_u
Data unit:	$\text{Pa}\cdot\text{m}^3/\text{kmol}\cdot\text{K}$
Description:	Universal ideal gases constant
Value to be applied:	8,314
Any comment:	

Data / Parameter:	MM_i		
Data unit:	kg/kmol		
Description:	Molecular mass of greenhouse gas <i>i</i>		
Value to be applied:	Compound	Structure	Molecular mass (kg / kmol)
	Carbon dioxide	CO_2	44.01
	Methane	CH_4	16.04
	Nitrous oxide	N_2O	44.02
	Sulfur hexafluoride	SF_6	146.06
	Perfluoromethane	CF_4	88.00
	Perfluoroethane	C_2F_6	138.01
	Perfluoropropane	C_3F_8	188.02
	Perfluorobutane	C_4F_{10}	238.03
	Perfluorocyclobutane	$\text{c-C}_4\text{F}_8$	200.03
	Perfluoropentane	C_5F_{12}	288.03
	Perfluorohexane	C_6F_{14}	338.04
Any comment:			



Data / Parameter:	MM _k		
Data unit:	kg/kmol		
Description:	Molecular mass of gas <i>k</i>		
Value to be applied:	For gases <i>k</i> that are greenhouse gases apply values for MM _i .		
	Compound	Structure	Molecular mass (kg / kmol)
	Nitrogen	N ₂	28.01
	Oxygen	O ₂	32.00
	Carbon monoxide	CO	28.01
	Hydrogen	H ₂	2.02
	Nitric oxide	NO	30.01
	Nitrogen dioxide	NO ₂	46.01
	Sulfur dioxide	SO ₂	64.06
Any comment:			

Data / Parameter:	MM _{H₂O}
Data unit:	kg/kmol
Description:	Molecular mass of water
Value to be applied:	18.0152 kg/kmol
Any comment:	

Data / Parameter:	P _n
Data unit:	Pa
Description:	Total pressure at normal conditions
Value to be applied:	101,325 Pa
Any comment:	

Data / Parameter:	T _n
Data unit:	K
Description:	Temperature at normal conditions
Value to be applied:	273.15 K
Any comment:	



III. MONITORING METHODOLOGY PROCEDURE

Data and parameters to be monitored

All monitored data must be linked in time, i.e. calculations shall be performed considering only a set of data acquired in the same time interval. As noted above, project participants may use an hour or a smaller discrete time interval.

Data / Parameter:	$V_{t,wb}$
Data unit:	m ³ wet gas/h
Description:	Volumetric flow of the gaseous stream in time interval t on a wet basis
Source of data:	
Measurement procedures (if any):	Volumetric flow measurement should always refer to the actual pressure and temperature. Instruments with recordable electronic signal (analogical or digital) are required
Monitoring frequency:	Continuous if not specified in the underlying methodology
QA/QC procedures:	Periodic calibration against a primary device provided by an independent accredited laboratory is mandatory. Calibration and frequency of calibration is according to manufacturer's specifications
Any comment:	This parameter will be monitored in Options B and C

Data / Parameter:	$V_{t,db}$
Data unit:	m ³ dry gas/h
Description:	Volumetric flow of the gaseous stream in time interval t on a dry basis
Source of data:	
Measurement procedures (if any):	Volumetric flow measurement should always refer to the actual pressure and temperature. Calculated based on the wet basis flow measurement plus water concentration measurement
Monitoring frequency:	Continuous if not specified in the underlying methodology
QA/QC procedures:	Periodic calibration against a primary device provided by an independent accredited laboratory is mandatory. Calibration and frequency of calibration is according to manufacturer's specifications
Any comment:	This parameter will be monitored in Options A

Data / Parameter:	$V_{i,t,db}$
Data unit:	m ³ gas i /m ³ dry gas
Description:	Volumetric fraction of greenhouse gas i in a time interval t on a dry basis
Source of data:	
Measurement procedures (if any):	Continuous gas analyser operating in dry-basis. Volumetric flow measurement should always refer to the actual pressure and temperature



Monitoring frequency:	Continuous if not specified in the underlying methodology
QA/QC procedures:	Calibration should include zero verification with an inert gas (e.g. N ₂) and at least one reading verification with a standard gas (single calibration gas or mixture calibration gas). All calibration gases must have a certificate provided by the manufacturer and must be under their validity period
Any comment:	This parameter will be monitored in Options B and E and may be monitored in Options A and D

Data / Parameter:	$V_{i,t,wb}$
Data unit:	m ³ gas /m ³ wet gas
Description:	Volumetric fraction of greenhouse gas <i>i</i> in a time interval <i>t</i> on a wet basis
Source of data:	
Measurement procedures (if any):	Calculated based on the dry basis analysis plus water concentration measurement or continuous in-situ analyzers if not specified in the underlying methodology
Monitoring frequency:	Continuous if not specified in the underlying methodology
QA/QC procedures:	Calibration should include zero verification with an inert gas (e.g. N ₂) and at least one reading verification with a standard gas (single calibration gas or mixture calibration gas). All calibration gases must have a certificate provided by the manufacturer and must be under their validity period
Any comment:	This parameter will be monitored in Options C and F and may be monitored in Options A and D

Data / Parameter:	$M_{t,wb}$
Data unit:	kg/h
Description:	Mass flow of the gaseous stream in time interval <i>t</i> on a wet basis
Source of data:	
Measurement procedures (if any):	Instruments with recordable electronic signal (analogical or digital) are required
Monitoring frequency:	Continuous if not specified in the underlying methodology
QA/QC procedures:	Periodic calibration against a primary device provided by an independent accredited laboratory is mandatory. Calibration and frequency of calibration is according to manufacturer's specifications
Any comment:	This parameter will be monitored in Options E and F

Data / Parameter:	$M_{t,db}$
Data unit:	kg/h
Description:	Mass flow of the gaseous stream in time interval <i>t</i> on a dry basis
Source of data:	
Measurement procedures (if any):	Calculated based on the wet basis flow measurement plus water concentration measurement



Monitoring frequency:	Continuous if not specified in the underlying methodology
QA/QC procedures:	Calibration and frequency of calibration is according to manufacturer's specifications
Any comment:	This parameter will be monitored in Option D

Data / Parameter:	$C_{H_2O,t,db,n}$
Data unit:	mg H ₂ O/m ³ dry gas
Description:	Moisture content of the gaseous stream at normal conditions, in time interval <i>t</i>
Source of data:	Measurements according to the USEPA CF42 method 4 – Gravimetric determination of water content
Measurement procedures (if any):	Discrete measurement procedure
Monitoring frequency:	The mean value among three consecutive measurements performed in the same day (at least 2 hours each) shall be considered. Measurements should coincide with the Annual Surveillance Test (associated with requirements of the EN 14181 standard) or the calibration of the flow meter for the gaseous stream
QA/QC procedures:	According to the USEPA CF42 method 4
Any comment:	Monitoring is required if Option 1 described in the “Determination of the absolute humidity of the gaseous stream” section of the tool is applied, or as one of the ways of proving that the gaseous stream is dry (necessary for Options A or D)

Data / Parameter:	T_t
Data unit:	K
Description:	Temperature of the gaseous stream in time interval <i>t</i>
Source of data:	
Measurement procedures (if any):	Instruments with recordable electronic signal (analogical or digital) are required. Examples include thermocouples, thermo resistance, etc
Monitoring frequency:	Continuous unless differently specified in the underlying methodology
QA/QC procedures:	Periodic calibration against a primary device provided by an independent accredited laboratory is mandatory. Calibration and frequency of calibration is according to manufacturer's specifications
Any comment:	Provided all parameters are converted to normal conditions during the monitoring process, this parameter may not be needed except for moisture content determination and therefore it should be metered only when performing such measurements (with same frequency). However, if the applicability condition related to the gaseous stream flow temperature being below 60°C is adopted, this parameter must be monitored continuously to assure the applicability condition is met



Data / Parameter:	P_t
Data unit:	Pa
Description:	Pressure of the gaseous stream in time interval t
Source of data:	
Measurement procedures (if any):	Instruments with recordable electronic signal (analogical or digital) are required. Examples include pressure transducers, etc
Monitoring frequency:	Continuous unless differently specified in the underlying methodology
QA/QC procedures:	Periodic calibration against a primary device must be performed periodically and records of calibration procedures must be kept available as well as the primary device and its calibration certificate. Pressure transducers (either capacitive or resistive) must be calibrated monthly
Any comment:	Provided all parameters are converted to normal conditions during the monitoring process, this parameter may not be needed except for moisture content determination and therefore it should be metered only when performing such measurements (with same frequency)

Data / Parameter:	$P_{H_2O,t,Sat}$
Data unit:	Pa
Description:	Saturation pressure of H_2O at temperature T_t in time interval t
Source of data:	
Measurement procedures (if any):	This parameter is solely a function of the gaseous stream temperature T_t and can be found at reference [1] for a total pressure equal to 101,325 Pa
Monitoring frequency:	
QA/QC procedures:	
Any comment:	[1] Fundamentals of Classical Thermodynamics; Gordon J. Van Wylen, Richard E. Sonntag and Borgnakke; 4 ^o Edition 1994, John Wiley & Sons, Inc.

Data / Parameter:	$V_{k,t,db}$
Data unit:	$m^3 \text{ gas } k/m^3 \text{ dry gas}$
Description:	Volumetric fraction of gas k in the gaseous stream in time interval t on a dry basis
Source of data:	
Measurement procedures (if any):	Continuous gas analyser operating in dry-basis
Monitoring frequency:	Continuous if not specified in the underlying methodology
QA/QC procedures:	Calibration should include zero verification with an inert gas (e.g. N_2) and at least one reading verification with a standard gas (single calibration gas or mixture calibration gas). All calibration gases must have a certificate provided by the manufacturer and must be under their validity period
Any comment:	



Data / Parameter:	$V_{k,t,wb}$
Data unit:	$m^3 \text{ gas } k/m^3 \text{ wet gas}$
Description:	Volumetric fraction of gas k in the gaseous stream in time interval t on a wet basis
Source of data:	
Measurement procedures (if any):	Calculated based on the dry basis analysis plus water concentration measurement or continuous in-situ analyzers if not specified in the underlying methodology
Monitoring frequency:	Continuous if not specified in the underlying methodology
QA/QC procedures:	Calibration should include zero verification with an inert gas (e.g. N_2) and at least one reading verification with a standard gas (single calibration gas or mixture calibration gas). All calibration gases must have a certificate provided by the manufacturer and must be under their validity period
Any comment:	

IV. REFERENCES

[1] Fundamentals of Classical Thermodynamics; Gordon J. Van Wylen, Richard E. Sonntag and Borgnakke; 4th Edition 1994, John Wiley & Sons, Inc.

[2] Drying: Principles, Applications and Design; Czeslaw Strumillo and Tadeusz Kudra; 1986; Gordon & Breach Science Publisher; Montreaux, Switzerland.

History of the document

Version	Date	Nature of revision(s)
02.0.0	EB 61, Annex 11 3 June 2011	Revision to: <ul style="list-style-type: none"> • Corrects inconsistencies in the expression of some parameters; • Provides a more simple option to demonstrate that the gaseous stream is dry based on showing that the temperature of the gaseous stream does not exceed 60°C, and changing the threshold for moisture content for a dry gaseous stream to be equal to or less than 0.05 kg H_2O/m^3 dry gas; • States that only the volumetric fraction of greenhouse gases being considered in the emission calculation of the underlying methodology must be monitored for determining the molecular mass of the gaseous stream; • Changes the frequency that the moisture content must be monitored to coincide with calibration of the flow meter, or the time of the Annual Surveillance Test associated with the EN 14181; • Editorial changes to improve the tool's structure, incorporate additional cross-referencing and remove repeated text.
01	EB 47, Annex 10 28 May 2009	Initial adoption.
Decision Class: Regulatory Document Type: Tool Business Function: Methodology		