

CDM-MP94-A03

Large-scale Consolidated Methodology

Mass rapid transit projects

Version 06.0

Sectoral scope(s): 07

DRAFT



COVER NOTE

1. Procedural background

1. A stakeholder submitted AM_REV_0266: Inclusion of autonomous-rail rapid transit as one of the rail-based mass rapid transit systems (hereinafter referred to as AM_REV_0266). The proposal requests to revise "ACM0016: Large-scale Consolidated Methodology Mass rapid transit projects" (hereinafter referred to as ACM0016) to expand its applicability to include autonomous-rail rapid transit (ART) as one of the rail-based mass rapid transit systems (MRTS) in urban or suburban regions for passenger transport by replacing a traditional urban public transport system. The revision also proposed the inclusion of green hydrogen as a fuel for the mass transport system.

2. Purpose

2. The purpose of this revision is to expand the scope of the methodology to include ART as one of the rail-based MRTS and the application of green hydrogen as a fuel for the mass transport system urban public transport system.

3. Key issues and proposed solutions

3. The proposed revision includes;
 - (a) Changes in the applicability conditions of the methodology to include ART and green hydrogen;
 - (b) A definition of ART;
 - (c) A definition of green hydrogen and vehicles powered by hydrogen;
 - (d) A condition for the additionality demonstration;
 - (e) An approach to calculate project emissions due to physical leaks of hydrogen and leakage emissions for upstream emissions related to the production, handling and use of green hydrogen.

4. Impacts

4. The revised draft version of the methodology provides a framework to calculate emission reductions for the project activities that implement ART projects as one of the rail-based MRTS and the the utilization of green hydrogen as a fuel for MRTS.

5. Subsequent work and timelines

5. The draft revised methodology is recommended by the MP for consideration by the Board at its 122nd meeting, no further work is envisaged.

6. Recommendations to the Board

6. The MP recommends that the Board adopt this draft revision to ACM0016, to be made effective at the time of the Board's approval.

DRAFT

TABLE OF CONTENTS	Page
1. INTRODUCTION	6
2. SCOPE, APPLICABILITY, AND ENTRY INTO FORCE	6
2.1. Scope	6
2.2. Applicability	6
2.3. Entry into force	8
2.4. Applicability of sectoral scopes	8
3. NORMATIVE REFERENCES	8
3.1. Selected approach from paragraph 48 of the CDM modalities and procedures	9
4. DEFINITIONS	9
5. BASELINE METHODOLOGY	11
5.1. Project boundary	11
5.2. Additionality demonstration	12
5.2.1. Step 1: Country level assessment	13
5.2.2. Step 2: City level assessment	14
5.2.3. Step 3: System level assessment	15
5.3. Baseline emissions	16
5.4. Project emissions	18
5.4.1. Determination of direct project emissions (DPE_y)	18
5.4.2. Direct project emissions from fuel consumption	18
5.4.3. Direct project emissions from electricity consumption	21
5.4.4. Determination of indirect project emissions (IPE_y)	22
5.4.5. Project emissions due to physical leaks of hydrogen	23
5.5. Leakage	23
5.5.1. Leakage due to the change in load factor of buses ($LE_{LF,Z,y}$)	24
5.5.2. Determination of emissions due to a change in load factor of taxis ($LE_{LFT,y}$)	25
5.5.3. Leakage due to reduced congestion ($LE_{CONg,y}$)	27
5.5.4. Upstream emissions from gaseous fuels ($LE_{UP,y}$)	31

5.5.5.	Upstream emissions related to the handling and use of green hydrogen ($LE_{hyd,y}$)	32
5.6.	Emission reductions	33
5.7.	Changes required for methodology implementation in 2 nd and 3 rd crediting periods	33
5.8.	Data and parameters not monitored	33
6.	MONITORING METHODOLOGY	37
6.1.	Data and parameters monitored	37
APPENDIX 1.	GUIDELINE FOR THE ESTABLISHMENT OF LOAD FACTOR STUDIES FOR BUSES BASED ON VISUAL OCCUPANCY	46
APPENDIX 2.	GUIDELINE FOR THE ESTABLISHMENT OF LOAD FACTOR STUDIES FOR BUSES BASED ON BOARDING-ALIGHTING SURVEYS	47
APPENDIX 3.	GUIDELINE FOR THE ESTABLISHMENT OF LOAD FACTOR STUDIES FOR TAXIS/MOTORCYCLES OR PASSENGER CARS	48
APPENDIX 4.	METHODOLOGICAL DESIGN OF SURVEY MRTS	49
APPENDIX 5.	DEFAULT QUESTIONNAIRE	56

DRAFT

1. Introduction

1. The following table describes the key elements of the methodology.

Table 1. Methodology key elements

Typical project(s)	Establishment and operation of new rail-based or bus-based mass rapid transit systems (MRTS) in urban or suburban regions for passenger transport by replacing a traditional urban public transport system. For buses, typical projects involve the replacement, extension of bus lanes or expansion of existing BRT systems (adding new routes and lines). For trains, typical projects involve the extension of existing rail line or expansion of existing rail infra-structure (e.g. new rail lines, or new Autonomous-rail Rapid Transit (ART) lines).
Type of GHG emissions mitigation action	Energy efficiency: Displacement of more-GHG intensive transport modes (e.g. an existing fleet of buses operating under mixed traffic conditions) by less-GHG-intensive ones (e.g. newly developed rail-based systems or segregated bus lanes)

2. Scope, applicability, and entry into force

2.1. Scope

2. The scope of this methodology includes the establishment and/or expansion and operation of rail-based or bus-based mass rapid transit systems (MRTS) in urban or suburban districts of a host city.

2.2. Applicability

3. The methodology is applicable for the implementation of Mass Rapid Transit Systems (MRTS), such as segregated Bus Rapid Transits (BRT) bus lanes or rail-based lines, that replaces existing bus routes operating under mixed traffic conditions.
4. The project may involve one or more of the measures listed below:
 - (a) The construction of a new rail-based infrastructure (e.g. new rail lines, or new Autonomous-rail Rapid Transit (ART lines));
 - (b) The expansion of an existing rail infrastructure (e.g. extension of an existing rail line or ART line);
 - (c) The construction of new segregated BRT bus lanes;
 - (d) The extension of bus lanes of existing BRT systems or expansions of existing BRT systems (i.e. adding new routes and lines).

5. For projects involving BRTs, the following specific provisions apply:
 - (a) Only BRT systems without feeder route are eligible under this methodology¹;
 - (b) The buses used in the routes that were replaced by the project MRTS can be retired or relocated to another part of the network;
 - (c) The project activity may be based on existing road infrastructure, but the bus lanes shall be separated physically from mixed traffic.
6. Fuels including (liquified) gaseous fuels or biofuel blends, as well as electricity can be used in the baseline or project case. The following conditions² apply in case of biofuels:
 - (a) The project buses shall use the same biofuel blend (same percentage of biofuel) as commonly used by conventional comparable³ urban buses in the country i.e. the methodology is not applicable if project buses use higher or lower blends of biofuels than those used by conventional buses;
 - (b) The project buses shall not use a significantly higher biofuel blend than cars and taxis.⁴
7. Vehicles powered by hydrogen used in the project activity may be eligible on the prerequisite that hydrogen consumed by project vehicles is exclusively green hydrogen produced by electrolysis of water using electricity from a dedicated greenfield renewable energy generation plant. This shall be demonstrated by acquiring green hydrogen certificates for each consignment of green hydrogen used in the project activity vehicles.
8. The methodology is applicable for urban or suburban trips. It is not applicable for inter-urban transport.
9. In addition, the applicability conditions included in the tools referred to below shall apply.
10. The methodology is applicable if the most plausible baseline scenario is the continuation of the use of current modes of transport.
11. The methodology is not applicable for:
 - (a) Operational improvements (e.g. new or larger buses) of an already existing and operating bus lane or rail-based MRTS;

¹ BRTs with feeder lines plus trunk routes, where passengers can realize their entire trip in the project system, shall use methodology "AM0031: Bus rapid transit systems".

² No provisions to calculate upstream emissions from the production of the fuels are provided in order to keep the methodology simple. Therefore, in order to ensure that the calculated emission reductions are conservative, this applicability condition aims to limit the use of the methodology to cases where the upstream emissions under the project activity are likely to be equal or lower than in the baseline scenario. Note that other methodologies involving fuel switch situations usually require the consideration of upstream emissions.

³ Comparable means of the same fuel type e.g. project buses using diesel are compared with conventional buses using diesel etc. The comparison is made for each year of monitoring based on official fuels sold. The term commonly used refers to the majority of units.

⁴ Project proponents wishing to consider project buses with a higher biofuel blend may propose a revision to this methodology.

- (b) Bus lanes replacing an existing rail-based system i.e. the existing urban or suburban rail infrastructure shall remain fully (in its full length) operational;
- (c) The implementation of air- or water-based transport systems.

12. In the case of vehicles powered by hydrogen included in the project activity, the project participants shall demonstrate that double-counting of emission reductions will not occur, e.g. via a contractual agreement with each relevant counterparty such as hydrogen powered vehicle manufacturer(s), hydrogen fueling station(s), hydrogen producer(s), renewable energy power plant(s). The project participants shall maintain a comprehensive inventory of project vehicles, including the unique identification of the vehicles. The steps undertaken to avoid double-counting shall be documented in the project design document.

2.3. Entry into force

13. The date of entry into force is the date of the publication of the **EB 122** meeting report on **31 May 2024**.

2.4. Applicability of sectoral scopes

14. For or validation and verification of CDM projects and programme of activities by a designated operational entity (DOE) using this methodology, application of sectoral scope 7 is mandatory.

3. Normative references

15. This consolidated baseline and monitoring methodology is based on the following proposed new methodologies:

- (a) "NM0258: Methodology for Bus Lanes" developed by Grütter Consulting AG, Switzerland;
- (b) "NM0266: Methodology for Rail Based Urban Mass Rapid Transit Systems (MRTS)" developed by Grütter Consulting AG, Switzerland.

16. This methodology also refers to the latest approved version of the following tools:

- (a) "TOOL01: Tool for the demonstration and assessment of additionality" (hereinafter referred as "TOOL01");
- (b) "TOOL03: Tool to calculate project or leakage CO₂ emissions from fossil fuel combustion" (hereinafter referred as "TOOL03");
- (c) "TOOL05: Tool to calculate baseline, project and/or leakage emissions from electricity consumption and monitoring of electricity generation" (hereinafter referred as "TOOL05");
- (d) "TOOL11: Assessment of the validity of the original/current baseline and update of the baseline at the renewal of the crediting period" (hereinafter referred as "TOOL11");
- (e) "TOOL15: Upstream leakage emissions associated with fossil fuel use" (hereinafter referred as "TOOL15").

- (f) “TOOL18: Baseline emissions for modal shift measures in urban passenger transport” (hereinafter referred as “TOOL18”);
 - (g) “TOOL23: Additionality of first-of-its-kind project activities” (hereinafter referred as “TOOL23”);
17. For more information regarding the proposed new methodologies and the tools as well as their consideration by the Executive Board of the clean development mechanism (CDM) (hereinafter referred to as the Board) please refer to <<http://cdm.unfccc.int/goto/MPappmeth>>.

3.1. Selected approach from paragraph 48 of the CDM modalities and procedures

18. Existing actual or historical emissions, as applicable.

4. Definitions

19. The definitions contained in the Glossary of CDM terms shall apply.
20. For the purpose of this methodology, the following definitions apply:
- (a) **Affected roads** - the roads influenced by the establishment of the MRTS. Affected roads are those inside a radius of minimum 1 kilometer running parallel to the MRTS line (roads on both sides of the MRTS line are included). Only roads with large traffic volumes are included;
 - (b) **Autonomous-rail Rapid Transit (ART)** - is a passenger transit service system using electronically-guided rubber-wheeled trams. The system relies on precise markings or pre-installed cartographic information embedded on the road, and deploys various sensors and trajectory-following control technologies to allow the ART trams to move along virtual tracks on the roadway instead of steel wheels.
 - (c) **Bus lane** (or trunk route) - refers to a segregated lane, where only buses are allowed to operate. Private vehicles are not allowed to use the bus lane. Exceptions such as emergency vehicles can apply. Bus lanes need not necessarily be physically separated from other traffic lanes. If no physical separation is realized then it shall be ensured that enforcement takes place to prevent the usage of the bus lane by other vehicles. The bus-lane might share part of the lanes with other modes of transport e.g. at traffic crossings, bridges, tunnels, in narrow parts or on roads with limited traffic e.g. in suburban parts of the city. However, for the purpose of this methodology more than half of the included bus lane shall be a bus-only lane;
 - (d) **Bus rapid transit (BRT) system** - is a bus-based collective urban or sub-urban passenger transit service system that uses bus lanes for trunk routes, and operates at high levels of performance, especially with regard to travel times and passenger carrying capacity;
 - (e) **City** - is a continuous area on which urban settlement has occurred including the historical core area and the adjacent suburbs defined by its administrative boundaries;

- (f) **Extensions of bus lanes** - are those where the same bus operates on the entire route i.e. passengers need not change from one bus to another bus when using the bus lane. The entire bus lane is thus composed of an existing or “old lane” and a “lane extension” (latter is the project activity);

Figure 1. Extension of bus lanes



- (g) **Extension of rail infrastructure** - is defined as adding additional kilometers along an existing rail-route;
- (h) **Feeder routes** - refer to bus routes which have intersections with trunk routes and which “feed” passengers on the trunk routes. Feeder routes are those with less passenger demand and operate under mixed traffic conditions;
- (i) **Green hydrogen** - an energy carrier that is produced from dedicated greenfield renewable energy-powered electrolysis of water;
- (j) **Vehicles powered by hydrogen** - a category of vehicles that uses a propulsion system powered by hydrogen, it can include similar engines to that of electric vehicles, where energy stored as hydrogen is converted into electricity by fuel cells;
- (k) **Larger urban zone (LUZ)** - of a city covers the whole functional zone around the city (including the core city) i.e. it corresponds to the commuting area around the city;
- (l) **Mass Rapid Transit Systems (MRTS)** - are collective urban or suburban passenger services operating at high levels of performance, especially with regard to travel times and passenger carrying capacity and can be based on elevated, surface level or underground roads or rail systems. MRTS can be rail-based systems such as subways/metros, Light Rail Transit (LRTs) systems, including trams, or suburban heavy duty rail systems, or ART or road-based bus systems. For the purpose of this methodology road-based MRTS are bus systems using bus-lanes, which can also be called BRT systems;
- (m) **New bus lanes** - are new routes operated by buses. Additional bus routes might share certain stations with an existing lane but passengers will have to switch buses if their trip involves stations on the “old” and the “new” lane;

Figure 2. New bus lanes



- (n) **Rebound effect** (or take-back effect) - the effect that the MRTS has on 'consumer behaviour' leading to additional trips. The rebound effect is an extension of the "Law of Demand", a basic principle of economics, which states that if prices decline, consumption usually increases. If the MRTS project reduces traffic congestion or improves the quality of transportation and reduces travel time, therefore reducing opportunity costs, it tends to increase the number and/or length of trips undertaken. Generated Traffic is the additional vehicle travel that occurs when reduced congestion increases traffic speeds and reduces travel time;
- (o) **Vehicle speed** - refers to the average speed of a vehicle, which is the total distance travelled by the vehicle divided by the total time taken by the vehicle to cover this distance, on the affected road. For the purpose of this methodology taxis and passenger cars are treated identically.

5. Baseline methodology

5.1. Project boundary

- 21. The spatial extent of the project boundary encompasses the passenger trips completed on the MRTS system within the urban zone of the city in which the project takes place. It is based on the origins and destinations of passengers using the project system. As the project cannot control the trip origins or destinations of passengers the spatial area of the project is the entire larger urban zone of the city in which the project operates.
- 22. The project only includes emission reductions from the MRTS routes. The location of the MRTS lanes should be transparently outlined in the project design document (CDM-PDD). If any MRTS lane would in a later stage be extended (prolonged) beyond the originally planned route detailed in the CDM-PDD, then the project proponents shall follow the latest requirements in "CDM Project cycle procedures" in order to claim emission reductions from these additional lanes.
- 23. If the project activity involves electricity-based transport systems (e.g. electrical railway systems), the project boundary also includes the power plants connected physically to the electricity system that supply power to the project, and/or the captive power plant.
- 24. The greenhouse gases included in or excluded from the project boundary are shown in Table 2.


Table 2. Emission sources included in or excluded from the project boundary

Source		Gas	Included	Justification/Explanation
Baseline	Mobile source emissions of different modes of transport (buses, passenger cars, motorcycles, taxis), which the passengers of the MRTS system would have taken in the absence of the project MRTS	CO ₂	Yes	Major emission source
		CH ₄	Yes	Included only if gaseous fuels are used and excluded for liquid fuels. CH ₄ emissions are a minor emission source of the total CO ₂ e emissions in diesel/gasoline vehicles Neglecting these emissions in baseline as well as project emissions is conservative as fuel consumption and thus also CH ₄ emissions are reduced through the project
		N ₂ O	No	N ₂ O emissions are a minor source of the total CO ₂ e emissions. Neglecting these emissions in baseline as well as project emissions is conservative as fuel consumption and thus also N ₂ O emissions are reduced through the project
Project activity	Direct emissions from the operation of the project MRTS	CO ₂	Yes	Major emission source
		CH ₄	Yes	Included only if gaseous fuels are used. See argument above
		N ₂ O	No	See explanation above
	Indirect emissions from the different modes of transport used by the passengers of the MRTS, from their point of origin to the MRTS entry station, and from the MRTS exit station to their final destination	CO ₂	Yes	Major emission source
		CH ₄	Yes	Included only if gaseous fuels are used. See argument above
		N ₂ O	No	See explanation above

5.2. Additionality demonstration

25. MRTS projects implemented in least developed countries (LDC) are deemed to be automatically additional.
26. If MRTS projects are implemented in countries other than LDCs and face the first-if-its-kind barrier, the latest approved version of the “Additionality of first-of-its-kind project activities” shall be followed to demonstrate the additionality of these project activities.
27. For MRTS projects, which are implemented in countries other than LDCs and which are not first-of-its-kind, the procedure illustrated in Figure 3 and described below shall be applied.

Figure 3. Additionality demonstration



5.2.1. Step 1: Country level assessment

- 28. This step aims to determine whether the proposed CDM project activity is common practice in the host country where the project is proposed to be implemented. For this purpose, project participants shall assess whether there are less than three cities with MRTS that started commercial operation in the host country of the proposed CDM project activity prior to the start of the CDM project activity.
- 29. The project participants shall:

- (a) Identify all cities with MRTS that have started commercial operation in the host country prior to the start of the CDM project activity. Project participants shall include a brief description of each system in the CDM-PDD;
 - (b) Identify which MRTS were developed as CDM project activities in the host country (registered project activities and project activities which have been published on the UNFCCC website for global stakeholder consultation as part of the validation process) and exclude all⁵ MRTS developed as CDM project activities from the assessment of common practice in this step.
30. If the number of cities with MRTS (excluding systems developed as CDM project activities) is equal to or exceeds three cities, then projects participants should proceed to Step 2, otherwise project participants should proceed to Step 3.

5.2.2. Step 2: City level assessment

31. This step aims to determine whether the proposed project activity is common practice in the host city where the proposed CDM project activity is intended to be implemented. For this purpose, project participants shall assess whether the share of trips realized on the existing public transport system(s) in the host city, which belong to the same public transport category as the proposed CDM project activity, is less than or equal to 20 per cent of total public transport trips in the host city.
32. The project participants shall:
- (a) Provide a breakdown of the total public transport trips realized in the host city by the shares of trips realized on different public transport categories, distinguishing between the following public transport categories:
 - (i) Metro;
 - (ii) Sub-urban rail;
 - (iii) Light rail transit including trams;
 - (iv) **ART;**
 - (v) Conventional bus system;
 - (vi) BRTs;
 - (b) Describe in the CDM-PDD the existing public transport systems and identify to which of the public transport categories they belong. Identify also to which public transport category the proposed project activity belongs. Determine and document in the CDM-PDD the shares of trips realized on each relevant public transport system and on each public transport category, expressed in percentages of the total public transport trips realized on all public transport systems in the host city.
33. If the share of motorized trips realized on the existing systems which belong to the same public transport category as the proposed project activity exceeds 20 per cent of total motorized public transport trips in the host city, then the proposed CDM project activity is

⁵ This is subject to further decisions by the Board.

not additional. If the share of trips is less than or equal to 20 per cent, then project participants should proceed to Step 3.

5.2.3. Step 3: System level assessment

34. Two options are provided for the system level assessment of the proposed project activity.
- (a) Conduct an investment analysis following the procedure under section 5.2.3.1 below; or
 - (b) Conduct a performance analysis, following the procedure under section 5.2.3.2 below.

5.2.3.1. Procedure for Investment analysis

35. The aim of this analysis is to determine whether the proposed project activity is not economically or financially feasible using “Option III. Benchmark analysis”, including the sensitivity analysis, provided in the TOOL01.
36. The investment analysis should be undertaken from the perspective of the operator/investor of the public transportation system of the city or urban area, reflecting the costs and revenues from the perspective of the operator/investor. If the project is subsidized through public authorities and institutions (e.g. local or central government, international donor organizations), e.g. through grants which do not need to be repaid, soft loans or contributions to operating and maintenance costs, or deficit guarantees, the financial assessment is made, taking into account these subsidies, including as investment the total system costs minus any such public subsidies. Any capital that needs to be repaid should be included in the calculations, e.g. loans by the municipality or city authority should be considered as a capital investment by the project operator and not be subtracted from the total system costs.
37. In applying the investment analysis, cost overruns of former investments in MRTS or reduced revenues of former MRTS investments compared to original projections, which make new investments less viable and riskier, can be considered. In this case, project participants should evaluate the cost overruns or reduced revenues of former MRTS that were implemented in the same host country in the last 20 years. Information on originally projected and actually observed costs/revenues should be based on official and public data. As a conservative approach, the lower end of the range of cost-overruns or reduced revenues observed over this period should be assumed for the project MRTS.
38. If the results of the sensitivity analysis are not conclusive, then the project activity is not additional. If the sensitivity analysis confirms the proposed project activity is not economically attractive, then the proposed project activity is additional.
39. Project participants utilizing green hydrogen shall not take into account any costs associated with hydrogen production for the investment analysis.

5.2.3.2. Procedure for a performance analysis

40. The MRTS project shall demonstrate that for road-based systems, forecasted emissions from the project MRTS is less than or equal to 50 gCO₂/pkm⁶ and, forecasted electricity consumption of the rail-based systems is less than or equal to 0.1 kWh/pkm, to demonstrate that the project is additional.
41. For this purpose the annual amount of emissions from project MRTS for road-based systems and/or annual amount of electricity consumption by the project MRTS for rail-based systems shall be based on expected efficiency and energy source of the project vehicles, annual number of passengers expected to travel in the project system and an average distance that these passengers are expected to travel in the project MRTS when the project MRTS will reach its planned capacity. A four-step model, or equivalent, of the transportation system of the project city as mentioned under section 5.7 below shall be used as the basis for forecasting the number of passengers and distance of travel on the system. This analysis shall be conducted ex ante for the purpose of additionality demonstration. All assumptions used in calculations need to be documented and substantiated in the CDM-PDD.
42. If the project activity is deemed to be additional, then the baseline scenario is assumed to be the continuation of the use of current modes of transport provided that the project participants can provide an explanation showing that the existing transport system (possibly expanded using additional vehicles) would be able to meet the transportation demand that will be met by the project system.

5.3. Baseline emissions

43. Baseline emissions include the emissions that would have happened due to the transportation of the passengers who use the project activity to travel between the point of origin (O) to the final destination (D), had the project activity not been implemented. This is differentiated according to the modes of transport (relevant vehicle categories) that the passengers would have used in the absence of the project.
44. Baseline emissions are calculated based on the latest version of the TOOL18, and taking into account the following provisions:
 - (a) The core baseline parameters used for calculating baseline emission are updated through surveys conducted in year 1 and year 4 of the crediting period, and changes only apply if the baseline emissions factors would be lower than the original factors;

⁶ Refer section 3 of “Performance benchmarks in draft revision of AM0031, AM0101 and ACM0016” available as annex 3 to 67th meeting report of Meth Panel.

- (b) The survey shall capture O and D of the passenger and which modes the passenger would have used and the distance it would have travelled between O and D⁷;
- (c) When applying equation 4 of the TOOL18, the parameter “Share of passengers who shifted from electricity-based or road based vehicle category i (S_i)” should be calculated taking into account all passengers travelling in the project transport mode, including induced traffic (i.e. those passengers who responded in the survey that they would not have travelled in the absence of the project transport mode). In case the baseline considers the expansion of the existing system with additional vehicles, then the determination of parameter $SFC_{i,n,x}$ under TOOL18 should take into account the share of new vehicles in the respective vehicle category;
- (d) If the project participants choose not to claim emission reductions for switching from passenger cars, taxis or motorcycles to the project transport, the modal survey will also not include these categories or questions related directly to these categories (change of trip distance of passenger cars or fuel type of passenger cars). The survey will, however, include the categories of public transport, non-motorised transport (NMT), and induced traffic (i.e. categories with emission factors lower than the project, to ensure that emission reductions are not overstated);
- (e) Criteria for identifying the vehicle categories are as follows:
 - (i) At a minimum, public transport, non-motorised transport and induced traffic have to be included;
 - (ii) Conditions to include categories with reliable data on fuel consumption and load factors;
 - (iii) Only include categories that are relevant for the MRTS project. If the project will only generate credits from public transport without modal shift, then passenger cars, taxis and motorcycles need not be included;
 - (iv) Differentiate relevant fuel types for each category. Diesel, gasoline and gas (CNG or LPG) are listed separately if a minimum of 10 per cent of vehicles of the respective category use such a fuel, while the threshold for zero-GHG-emission⁸ fuels is minimum 1 per cent. The 10 per cent threshold is justified, as greenhouse gas (GHG) emission differentials between diesel, gasoline and gaseous fuels are less than 20 per cent;

⁷ As a rule of thumb, O and D are assumed to be equal for both baseline and project scenarios (except for induced traffic, which is included only as project but not as baseline trip). However, the trip distance and the modes used between O and D in the baseline and project scenarios are different since (i) the passenger shifts its transportation mode, e.g. from cars to the project MRTS, and (ii) some passengers using the project MRTS may be willing to make detours due to the higher speed of the MRTS versus conventional baseline mode of transport.


⁸ Zero-emission in the context of operating emissions and not well-to-wheel or life-cycle emissions; this includes hydrogen.

- (v) If the baseline includes the expansion of the existing public transportation system with additional vehicles, then the determination of parameter $SFC_{i,n,x}$ under the TOOL18 should take into account the share of new vehicles in the respective vehicle category.

5.4. Project emissions

- 45. Project emissions are based on the fuel and/or electricity consumed by the MRTS (direct project emissions) plus emissions caused by project passengers from their trip origin to the entry station of the project and from the exit station of the project to their final destination (indirect project emissions), as illustrated in Figure 4.

Figure 4 Direct and indirect project emissions



- 46. Project emissions are calculated as follows:

$$PE_y = DPE_y + IPE_y \quad \text{Equation (1)}$$

Where:

- PE_y = Project emissions in year y (tCO₂)
- DPE_y = Direct project emissions in year y (tCO₂)
- IPE_y = Indirect project emissions in year y (tCO₂)

5.4.1. Determination of direct project emissions (DPE_y)

- 47. Direct project emissions are determined based on the fuel and electricity consumed by the project system.

$$DPE_y = DPE_{FC,y} + DPE_{EC,y} + PE_{H2-leaks,y} \quad \text{Equation (2)}$$

Where:

- $DPE_{FC,y}$ = Direct project emissions from fuel consumption in year y (tCO₂)
- $DPE_{EC,y}$ = Direct project emissions from electricity consumption in year y (tCO₂)
- $PE_{H2-leaks,y}$ = Direct project emissions due to physical leaks of hydrogen (tCO₂e)

5.4.2. Direct project emissions from fuel consumption

- 48. The methodology provides two alternatives to determine project emissions from fuel consumption, depending on data availability. If records exist, the data quality of both

alternatives is equal. Reliable data are, for example, based on electronic measurement of fuel consumption or data monitored by the company managing the vehicles. For both alternatives, specific fuel consumption data (i.e. consumption per distance driven) needs to be crosschecked in the QA system. Cross-checks include a comparison over time within the same company, as well as a comparison with, for example other companies operating MRTS systems using the same type of vehicles.

5.4.2.1. Alternative A: Use of fuel consumption data

49. This alternative is based on the total fuel consumed by project buses. For buses using liquid fossil fuels, the project emissions from fossil fuel consumption shall be estimated using the latest approved version of the TOOL03. The following guidance is provided for applying the tool:

- (a) The parameter $PE_{FC,j,y}$ in the tool corresponds to the project emissions from the project transport system that uses fossil fuels in year y ; and
- (b) Element process j corresponds to the combustion of fuel type n in the project vehicles.

50. For buses using gaseous fossil fuels, the project emissions from fossil fuel consumption shall be estimated based in one of the following approaches:

- (a) If fuel is being measured on a mass basis, the following equation shall be applied:

$$PE_{FC,y} = \sum_n [FC_{PJ,n,y} \times NCV_n \times (EF_{CO_2,n} + GWP_{CH_4} \times EF_{CH_4,n})] \times 10^{-6} \quad \text{Equation (3)}$$

Where:

- PE_y = Project emissions in year y (tCO₂e)
- $FC_{PJ,n,y}$ = Total consumption of fuel type n in year y by the project (t) by both trunk buses and feeder buses (tonne)
- NCV_n = Net calorific value of the fuel type n (TJ/Gg)
- $EF_{CO_2,n}$ = CO₂ emission factor for fuel type n (tCO₂/TJ)
- $EF_{CH_4,n}$ = CH₄ emission factor for gaseous fuel type n (tCH₄/TJ)
- GWP_{CH_4} = Global warming potential of the CH₄ (tCO₂e/tCH₄)
- n = Fuel type used by the project

- (b) If fuel is being measured on a volumetric basis, the following equation shall be applied:

$$PE_{FC,y} = \sum_n [FC_{PJ,n,y} \times NCV_n \times \rho_n \times (EF_{CO_2,n} + GWP_{CH_4} \times EF_{CH_4,n})] \times 10^{-6} \quad \text{Equation (4)}$$

Where:

- PE_y = Project emissions in year y (tCO₂e)
- $FC_{PJ,n,y}$ = Total consumption of fuel type n in year y by the project by both trunk buses and feeder buses (L)

NCV_n	=	Net calorific value of the fuel type n (TJ/Gg)
ρ_n	=	Density of the fuel type n (t/L)
$EF_{CO_2,n}$	=	CO ₂ emission factor for fuel type n (tCO ₂ /TJ)
$EF_{CH_4,n}$	=	CH ₄ emission factor for gaseous fuel type n (tCH ₄ /TJ)
GWP_{CH_4}	=	Global warming potential of the CH ₄ (tCO ₂ e/tCH ₄)
n	=	Fuel type used by the project

5.4.2.2. Alternative B: Use of specific fuel consumption and distance data

51. Total project emissions under alternative B are calculated from the following equation.

$$PE_{FC,y} = EF_{km,Z,y} \times DD_{Z,y} \times 10^{-6} \quad \text{Equation (5)}$$

Where:

PE_y	=	Project emissions in year y (t CO ₂ e)
$EF_{km,Z,y}$	=	Emissions factor per kilometer for project buses in year y (gCO ₂ e/km). Calculated through equation (9) below
$DD_{Z,y}$	=	Total distance driven by project buses in year y (km)

52. $EF_{km,Z,y}$ is determined based on the fuel efficiency data (i.e. consumption per kilometer driven).

(a) If the specific fuel consumption is determined on a mass basis (i.e. in mass units/km), the following equation shall be applied

$$EF_{km,Z,y} = \sum_n [SFC_{Z,n,y} \times NCV_n \times (EF_{CO_2,n} + GWP_{CH_4} \times EF_{CH_4,n})] \times 10^{-3} \quad \text{Equation (6)}$$

Where:

$EF_{km,Z,y}$	=	Emissions factor per kilometer for project bus in year y (gCO ₂ e/km)
$SFC_{j,n,y}$	=	Specific consumption of fuel type n by project bus in year y (g/km)
NCV_n	=	Net calorific value of the fuel type n (TJ/Gg)
$EF_{CO_2,n}$	=	CO ₂ emission factor for fuel type n (tCO ₂ /TJ)
$EF_{CH_4,n}$	=	CH ₄ emission factor for gaseous fuel type n (tCH ₄ /TJ)
GWP_{CH_4}	=	Global warming potential of the CH ₄ (tCO ₂ e/tCH ₄)
n	=	Fuel type used by project bus category j

(b) If the specific fuel consumption is determined on a volumetric basis (i.e. in volume units/km), the following equation shall be applied

$$EF_{km,Z,y} = \sum_n [SFC_{Z,n,y} \times NCV_n \times \rho_n \times (EF_{CO_2,n} + GWP_{CH_4} \times EF_{CH_4,n})] \times 10^3 \quad \text{Equation (7)}$$

Where:

$EF_{km,Z,y}$	=	Emissions factor per kilometer for project bus in year y (gCO ₂ e/km)
$SFC_{Z,n,y}$	=	Specific consumption of fuel type n by project bus in year y (L/km)
NCV_n	=	Net calorific value of the fuel type n (TJ/Gg)
ρ_n	=	Density of the fuel type n (t/L)
$EF_{CO_2,n}$	=	CO ₂ emission factor for fuel type n (tCO ₂ /TJ)
$EF_{CH_4,n}$	=	CH ₄ emission factor for gaseous fuel type n (tCH ₄ /TJ)
GWP_{CH_4}	=	Global warming potential of the CH ₄ (tCO ₂ e/tCH ₄)
n	=	Fuel type used by project bus category j

5.4.3. Direct project emissions from electricity consumption

53. The methodology also provides two alternatives to determine project emissions from electricity consumption by electric vehicles (buses or trains), depending on data availability. If records exist, the data quality of both alternatives is equal. Reliable data are, for example, based on electronic measurement of electricity consumption or data monitored by the company managing the project vehicles. For both alternatives, specific electricity consumption data (i.e. consumption per distance driven) needs to be crosschecked in the QA system. Cross-checks include a comparison over time within the same company, as well as a comparison with, for example other companies operating MRTS systems using the same types of vehicles.

5.4.3.1. Alternative A: Use of electricity consumption data

54. This alternative is based on the total electricity consumed by electric vehicles (buses or trains). Project emissions shall be estimated using the latest approved version of the TOOL05, where the parameter $PE_{EC,j,y}$ in Equation 1 of the tool corresponds to the project emissions from the project transport system that uses electricity in year y .

5.4.3.2. Alternative B: Use of specific electricity consumption and distance data

55. Total project emissions under alternative B are calculated applying Equation 1 from the TOOL05, where the parameter $EC_{PJ,j,y}$ is determined as the product between the specific electricity consumed by the project vehicles and the distance driven by the project vehicles:

$$EC_{PJ,j,y} = \sum_n SEC_{j,n,y} \times DD_{j,n,y} \times 10^{-3} \quad \text{Equation (8)}$$

Where:

$EC_{PJ,j,n,y}$	=	Electricity consumed by the project vehicle n from the electricity consumption source j in year y (MWh)
$SEC_{j,n,y}$	=	Specific electricity consumed by the project vehicle n from the electricity consumption source j in year y (kWh/km)
$DD_{j,n,y}$	=	Total distance driven by vehicle n year y (km)

56. For both electric and fossil fuel vehicles, the fuel-efficiency data is derived from annual data reported by the transport companies operating the project vehicles either for all units or for a representative sample of comparable units (comparable technology, vintage and size). To ensure a conservative approach, the specific fuel and electricity consumption of comparable vehicles, if based on sample measurement, should be taken as the upper 95 per cent confidence level of the sample measurement conducted.
57. If the CDM project includes only parts of a larger activity (e.g. a certain line of a comprehensive MRTS development), the fuel used by the project vehicles shall be separated from the total fuel used. The separation is done (in order of preference) by the following means:
- (a) By operators: this method is used if certain operators are assigned to certain parts of the project;
 - (b) By distance driven: the fuel share for each part of the project is based on the share of kilometers per project part;
 - (c) By passengers: the fuel share for each part of the project is based on the share of passengers per part of the project (based on the entry points of passengers).

5.4.4. Determination of indirect project emissions (IPE_y)

58. Indirect project emissions are those caused by passengers from their point of origin (O) up to the project activity entry station, and from the project activity exit station up to the final destination (D):
- (a) The survey realized identifies O, the project entry station, the project exit station and D of the passenger, plus the modes used between the different points (e.g. bike from origin to project entry station and taxi from project exit station to final destination);
 - (b) The distances between O and the entry, and between the exit and D are calculated based, e.g. on public transit routes, electronic maps and GPS (identical to baseline trip determination);
 - (c) The emission factors per passenger-kilometer used for indirect project emissions are determined based on equation 1 of the TOOL18.
59. Indirect project emissions are determined based on the equation below:

$$IPE_y = P_y \times \sum_i (D_{ind,i,1-4} \times EF_{pkm,i,1-4} \times 10^{-6}) \quad \text{Equation (9)}$$

Where:

- IPE_y = Indirect project emissions in year y (tCO₂)
- P_y = Total number of passengers transported in year y
- $EF_{pkm,i,1-4}$ = Emission factor per passenger-kilometer of mode i in years 1 and 4 of the crediting period (gCO₂/pkm)

$D_{ind,i,1-4}$ = Average indirect project trip distance of surveyed passengers using mode i in years 1 and 4 of the crediting period (km)

5.4.5. Project emissions due to physical leaks of hydrogen

60. In the case of project vehicles powered by hydrogen, the project participant shall document in the project design document a plan to minimize physical leaks of hydrogen in its use. The monitoring report shall demonstrate the implementation of this plan, which should be verified by the designated operating entity through site visits and/or documentation review.
61. If the project participant failed to demonstrate full implementation of the plan to minimize physical leaks of hydrogen, then the project participant shall calculate the project emissions due to physical leaks of hydrogen as follows:

$$PE_{H2-leaks,y} = FC_{PJ,H2,y} \times PL_{H2} \times GWP_{H2} \quad \text{Equation (10)}$$

Where:

- $FC_{PJ,H2,y}$ = Green hydrogen consumption by project vehicles in the year y (tH₂)
- PL_{H2} = Physical leaks of hydrogen in hydrogen value chain as a percentage of the total consumption
- GWP_{H2} = Global warming potential of hydrogen (t CO₂/t H₂).

5.5. Leakage

62. Potential sources of leakage emissions from a MRTS project are listed below and are calculated based on Equation 10 below:
- Changes in occupancy of the baseline transport system, that is, the project may potentially increase or decrease the occupancy rate of the baseline vehicles (i.e. buses and taxis); and
 - Reduced congestion in remaining roads (because passengers shifted from cars and motorcycles to the BRT project, resulting in higher average speed of baseline vehicles), plus a rebound effect.
 - Upstream emissions of gaseous fuels, if the project vehicles consume more gaseous fuels than baseline vehicles.
 - Upstream emissions related to the production, handling and use of green hydrogen.

$$LE_y = LE_{LF,Z,y} + LE_{LFT,y} + LE_{CONG,y} + LE_{UP,y} + LE_{hyd,y} \quad \text{Equation (11)}$$

Where:

- LE_y = Leakage emissions in year y (tCO₂)
- $LE_{LF,Z,y}$ = Leakage emissions due to change of load factor of buses in year y (tCO₂)

$LE_{LFT,y}$	=	Leakage emissions due to change of load factor of taxis in year y (tCO ₂)
$LE_{CONG,y}$	=	Leakage emissions due to change in congestion in year y (tCO ₂)
$LE_{UP,y}$	=	Leakage emissions due to upstream emissions of gaseous fuels in year y (tCO ₂)
$LE_{hyd,y}$	=	Leakage emissions due to upstream emissions related to the handling and use of green hydrogen in year y (tCO ₂)

63. As a conservative approach, leakage is only considered if the total annual effect is to reduce estimated emission reductions and where total net leakage effects are negative ($LE_y < 0$), project participants should assume $LE_y = 0$.
64. The impact of induced traffic (additional trips) provoked through the new transport system is addressed directly in the project emissions and is not part of the leakage. This is addressed by including as project emissions the trips of passengers, who, in absence of the MRTS project, would not have realized the trip.

5.5.1. Leakage due to the change in load factor of buses ($LE_{LF,Z,y}$)

65. The decrease in the occupancy of baseline conventional bus fleet results in a higher CO₂ emission factor per passenger-kilometer. Load factor changes are monitored in years 1 and 4 of the crediting period for the entire larger urban zone of the city as the potential impact is not necessarily in the proximity of the project MRTS (buses can be used in other parts of the larger urban zone of the city).
66. This leakage source is only included if the load factor of buses has decreased by more than 10 per cent as certain variations in the load factor caused by external circumstances are normal and normal and are calculated as:

$$LE_{LF,Z,y} = \max \left[\frac{N_{Z,1-4} \times AD_Z \times EF_{km,Z,y} \times \left(1 - \frac{ROC_{Z,1-4}}{ROC_{Z,x}} \right)}{10^6}; 0 \right] \quad \text{Equation (12)}$$

Where:

$N_{Z,1-4}$	=	Number of buses in years 1 and 4 of the crediting period (buses)
AD_Z	=	Average annual distance driven by baseline buses (km/bus)
$EF_{km,Z,y}$	=	Emission factor per kilometer for baseline buses in year y (gCO ₂ /km)
$ROC_{Z,1-4}$	=	Average occupancy rate relative to the capacity of baseline buses in years 1 and 4 of the crediting period (%)
$ROC_{Z,x}$	=	Average occupancy rate relative to the capacity of baseline buses in year x (%)
x	=	Most recent calendar year prior to the start of commercial operation of the project system or prior to the submission of the CDM-PDD for validation, whichever is earlier

67. The average annual distance driven by baseline buses (AD_Z) is determined based on the distance driven by the different bus sizes (small, medium, large) and the number of the different bus sizes.

$$AD_Z = \frac{\sum_i DD_{Z,s,x}}{\sum_s N_{Z,s,x}} \quad \text{Equation (13)}$$

Where:

$DD_{Z,s,x}$	=	Total distance driven by bus size s in year x (km)
$DD_{i,L}$	=	Total distance driven by large (L) buses i in year x (km)
N_k	=	Number of buses of size k in year x
s	=	Bus sizes: small (S), medium (M) and large (L)
x	=	Most recent calendar year prior to the start of commercial operation of the project system or prior to the submission of the CDM-PDD for validation, whichever is earlier

68. The average occupancy rate relative to the capacity of buses is determined through the equation below, based on boarding-alighting or through visual occupancy studies or by other means to be described in the CDM-PDD. The same monitoring method should be used for monitoring the baseline load factor before the project start and the load factor during the project execution. The detailed procedures concerning visual occupancy studies and boarding-alighting studies are presented in Appendices 1, 2 and 3.

$$ROC_Z = \frac{OC_{Z,t}}{CV_{Z,t}} \quad \text{Equation (14)}$$

Where:

$OC_{Z,t}$	=	Average occupancy of buses in the period t (passengers)
$CV_{Z,t}$	=	Average capacity of buses in the period t (passengers)
t	=	Period of time when the parameters are measured: most recent calendar year prior to the start of commercial operation of the project system or prior to the submission of the CDM-PDD for validation, whatever is earlier (x) or years 1 and 4 of the crediting period (1-4)

5.5.2. Determination of emissions due to a change in load factor of taxis ($LE_{LFT,y}$)

69. The project could have a negative impact on the load factor of taxis. Taxis can include cars as well as motorized rickshaws providing taxi services. If both types of services exist, the load factor change is monitored separately for these two taxi categories. Load factor changes are monitored for the entire larger urban zone of the city as taxis operate all over the larger urban zone of the city and are not confined to deliver their services in certain

areas. The load factor of taxis is monitored in the years 1 and 4 of the crediting period. This leakage is calculated as follows:

$$LE_{LFT,y} = \max \left[\frac{N_{T,1-4} \times AD_T \times EF_{km,T,y} \times \left(1 - \frac{ROC_{T,1-4}}{ROC_{T,x}} \right)}{10^6} ; 0 \right] \quad \text{Equation (15)}$$

Where:

- $LE_{LFT,y}$ = Leakage emissions due to a change in load factor of taxis in year y (tCO₂)
- $N_{T,1-4}$ = Number of taxis in years 1 and 4 of the crediting period (taxis)
- AD_T = Average annual distance driven by baseline taxis (km/taxi)
- $EF_{km,T,y}$ = Emission factor per kilometer for baseline taxis in year y (gCO₂/km)
- $ROC_{T,1-4}$ = Average occupancy rate relative to the capacity of baseline taxis in years 1 and 4 of the crediting period (%)
- $ROC_{T,x}$ = Average occupancy rate relative to the capacity of baseline taxis in year x (%)
- x = Most recent calendar year prior to the start of commercial operation of the project system or prior to the submission of the CDM-PDD for validation, whichever is earlier

70. The maximum change in load factor attributed to taxis is the emission reductions due to passengers switching from taxis to the project (calculated by the emission factor per passenger-kilometer for taxis, trip distance and number of passengers transported by the project, which would have used taxis in absence of the project). This maximum condition is established because load factors might also worsen city-wide due to factors external to the project, and the maximum leakage from a change in load factor of taxis due to the project can be determined according to the number of passengers transported by the project who in absence of the project would have taken a taxi.
71. The average occupancy rate relative to the capacity of taxis is determined through the equation below, based on visual occupancy studies counting the number of passengers. The detailed procedures concerning visual occupancy studies for taxis are presented in Appendix 3.

$$ROC_T = \frac{OC_{T,t}}{CV_{T,t}} \quad \text{Equation (16)}$$

Where:

- $OC_{T,t}$ = Average occupancy of taxis in the period t (passengers)
- $CV_{T,t}$ = Average capacity of taxis in the period t (passengers)

t = Period of time when the parameters are measured: most recent calendar year prior to the start of commercial operation of the project system or prior to the submission of the CDM-PDD for validation, whatever is earlier (x) or years 1 and 4 of the crediting period (1-4)

72. The parameter emission factor per kilometer for baseline taxis in year y ($EF_{km,T,y}$) is calculated using the equation (1) for $EF_{km,i,y}$ presented in the “TOOL18: Baseline emissions for modal shift measures in urban passenger transport”, substituting i for T (taxis).

5.5.3. Leakage due to reduced congestion ($LE_{CONg,y}$)

73. The project activity may reduce the number of remaining buses and potentially other vehicles on roads used by mixed traffic and, thus, also reduce congestion. On the other hand, MRTS project activities may also reduce the road space available for conventional buses and individual transport modes. Therefore, two effects resulting from reduced congestion are considered:

74. The implementation of the project activity may have the following overall impacts on congestion:

(a) On the one hand, the project system may reduce the road space available for conventional buses and individual transport modes. This may result in a reduced road capacity available to the vehicles operating on that road prior to the project activity, which, in turn, may increase the congestion on that reduced road capacity and, therefore, lead to higher emissions;

(b) On the other hand, an implementation of the project system may provide a new road infrastructure. In this case, the project system will likely attract passengers from conventional modes of transport; as a consequence, the number of vehicles that will travel on the affected roads will reduce, resulting in reduced congestion. In this case, reduced congestion may have the following impacts relevant for GHG emissions:

(i) Induced traffic effect (or rebound effect), i.e. more trips of passenger cars on the “affected roads”;

(ii) Changes in vehicle speed effect, i.e. change of emissions due to a reduced or increased speed of cars on “affected roads”.

75. In cases where the implementation of the project activity leads to a reduction of road capacity available for individual motorised transport modes, the impact of changes in congestion shall be monitored in the end of years 1 and 4 of the crediting period. In other cases (e.g. the project provides a new road infrastructure not taken from the existing road space in the city), monitoring of these changes is not required.⁹ This change in road capacity available for individual motorised transport modes may result from the reduction of road space due to the implementation of MRTS and/or a potential reduction of traffic flow due to the withdrawal of conventional public transport units as a result of the project activity.

⁹ Emission reductions due to the speed increase of the traffic flow generally overweighs the increase in emissions resulting from the traffic induction of passenger cars as a result of reduced congestion.

76. The equation below shall be applied to determine the additional road capacity, available to the transport modes remaining in operation, as a result of the implementation of project activity in the year when the project MRTS is intended to reach its planned capacity:

$$ARS_y = \sum_y \frac{BSCR_y}{N_{Z,x}} \times SRS_x - \frac{RS_x - RS_y}{RS_x} \quad \text{Equation (17)}$$

Where:

- ARS_y = Additional road capacity available to individual motorised transport modes in year y when the project MRTS is intended to reach its planned capacity (in percentage)
- $BSCR_y$ = Cumulative bus units displaced by the project on the trunk lanes as a result of the project in year y (number of vehicles)
- $N_{Z,x}$ = Total number of buses in the public transportation system in use in year x (units)
- SRS_x = Share of road space used by public transport in year x (in percentage). Calculated based on paragraph 404 77 below
- RS_x = Total road space available in year x (lane-kilometers)
- RS_y = Total available road space in the project in year y (lane-kilometers)
- x = Most recent calendar year prior to the start of commercial operation of the project system or prior to the submission of the CDM-PDD for validation, whichever is earlier. Data not older than three years

77. The following equation shall be used to determine SRS if no recent and good quality study is available which has calculated this parameter:

$$SRS_x = \frac{TD_{B,x} \times 2.5}{TD_{B,x} \times 2.5 + TD_{T,x} + TD_{C,x}} \quad \text{Equation (18)}$$

Where:

- SRS_x = Share of road space used by public transport in year x (in percentage)
- $TD_{B,x}$ = Total distance driven by public transport buses in year x (km)
- $TD_{T,x}$ = Total distance driven in kilometers by taxis in year x (km)
- $TD_{C,x}$ = Total distance driven in by passenger cars in year x (km)
- x = Most recent calendar year for which data is available. Data not older than three years

78. It is assumed that one bus occupies 2.5 times more road space than a personal car or a taxi.

79. For all distance variables the same vintage of data, the same spatial scope and the same time-span (e.g. one month or one year) is required.

80. If ARS_y is negative, then the road capacity in that year was reduced and leakage emissions due to increased congestion as a result of the reduced road capacity due to the project activity ($LE_{CONG,y}$) shall be quantified based on the equation below. If ARS_y is positive, $LE_{CONG,y}$ is assumed to be zero and no monitoring is required.
81. The corresponding emissions $LE_{CONG,y}$ are calculated as follows:

$$LE_{CONG,y} = \max[(LE_{REB,y} + LE_{SP,y}); 0] \quad \text{Equation (19)}$$

Where:

- $LE_{REB,y}$ = Leakage emissions due to induced traffic / rebound effect in year y (tCO₂)
- $LE_{SP,y}$ = Leakage emissions due to change in vehicle speed in year y (tCO₂)

5.5.3.1. Determination of emissions due to induced traffic/rebound effect ($LE_{REB,y}$)

82. The concept to capture emissions from induced traffic (or rebound effect, measured for passenger cars and taxis) includes the following conservative assumptions:
- The distance driven on the affected roads by all additional cars/taxis is considered as additional trip distance, i.e. it is assumed that formerly used alternative routes are shorter;
 - All additional cars/taxis on the affected roads are considered to be induced by the project and not by external effects such as general traffic growth.
83. The monitoring is conducted through measurements of traffic flows and distance driven by passenger cars and taxis on the affected roads in end of years 1 and 4 of the crediting period.
84. Ex-ante, the “affected roads” are identified and clearly listed in the CDM-PDD including a map. The procedure to identify the “affected roads” is described in the definition section of the methodology under the term “affected roads”.
85. A negative rebound effect based on additional congestion is expected in this situation. For each affected road the average speed of cars/taxis is monitored and compared with the baseline one.
86. Vehicle speed refers to the average speed, i.e. total distance divided by total time, on the affected road.
87. The rebound effect for the affected roads is calculated as follows:

$$LE_{REB,y} = \sum_i \frac{[TD_{i,1-4} \times EF_{KM,i,1-4} \times (N_{i,1-4} - N_{i,x} + N_{i,MS,y})]}{10^6} \quad \text{Equation (20)}$$

Where:

- $LE_{REB,y}$ = Leakage emissions due to rebound effect in year y (tCO₂)

- $TD_{i,1-4}$ = Average trip distance driven by vehicle category i on the affected roads in years 1 and 4 of the crediting period (km)
- $EF_{KM,i,y}$ = Emission factor per kilometer for vehicle category i in years 1 and 4 of the crediting period (gCO₂/km)
- $N_{i,1-4}$ = Number of vehicle category i using the affected roads in years 1 and 4 of the crediting period (cars, taxis)
- $N_{i,x}$ = Number of vehicle category i per annum using the affected roads in year x (cars, taxis)
- $N_{i,MS,y}$ = Number of vehicle category i per annum not used anymore due to mode shift to the MRTS in year y (cars, taxis)
- i = Vehicle category: passenger cars (C) and taxis (T)
- x = Most recent calendar year prior to the start of commercial operation of the project system or prior to the submission of the CDM-PDD for validation, whichever is earlier. Data not older than three years

88. The number of cars and taxis per annum not used anymore due to mode shift to the MRTS in years 1 and 4 of the crediting period is calculated as:

$$N_{i,MS,y} = \frac{MS_{i,1-4} \times P_y}{OC_{i,x}} \quad \text{Equation (21)}$$

Where:

- $MS_{i,1-4}$ = Net share of passengers using the MRTS which would have used mode i in years 1 and 4 of the crediting period y (%)
- P_y = Passengers transported by the project in year y (passengers)
- $OC_{i,x}$ = Average occupancy rate of vehicle category i year x (passengers)
- i = Vehicle category: passenger cars (C) and taxis (T)
- x = Most recent calendar year prior to the start of commercial operation of the project system or prior to the submission of the CDM-PDD for validation, whichever is earlier. Data not older than three years

89. The net share of passengers that shifted from car/taxi to the MRTS is based on the percentage of passengers which would have used in the baseline cars/taxis at least partially for their trip minus the share of passengers of the MRTS which use cars/taxis partially for their trip (to and/or from the MRTS).

5.5.3.2. Determination of emissions due to changes in vehicle speed ($LE_{SP,y}$)

90. Leakage emissions due to changes in vehicle speed are determined only for cars and taxis, as presented below.

$$LE_{SP,y} = \sum_i \frac{[N_{i,1-4} \times TD_{i,1-4} \times (EF_{KM,VP,i,1-4} - EF_{KM,VB,i})]}{10^6} \quad \text{Equation (22)}$$

Where:

- $LE_{SP,y}$ = Leakage emissions due to changes in vehicle speed of cars and taxis in year y (tCO₂)
- $N_{i,1-4}$ = Number of cars/taxis using the affected roads in years 1 and 4 of the crediting period (cars, taxis)
- $TD_{i,1-4}$ = Average trip distance made by cars/taxis on the affected roads in years 1 and 4 of the crediting period (km)
- $EF_{KM,VP,i,1-4}$ = Emission factor per kilometer for cars/taxis at the project speed in years 1 and 4 of the crediting period (gCO₂/km)
- $EF_{KM,VB,i}$ = Emission factor per kilometer for cars/taxis at the baseline speed (gCO₂/km)
- i = Vehicle category: passenger cars (C) and taxis (T)

91. The project speed on the affected roads is monitored in the end of years 1 and 4 of the crediting period. Vehicle speed is monitored under moving conditions. The same method should be used for determining the baseline and project speed.
92. The number of cars and taxis on the affected roads are monitored through visual or electronic counting.
93. To determine the emission factor per kilometer of cars/taxis at the project speed and baseline speed, project proponents can either use a speed dependency factor developed with an officially recognized methodology for the project region with the corresponding documentation to ensure good quality (this is the preferred option) or use as a default relationship between the speed dependency factor and emissions for passenger cars developed by CORINAIR. The same vehicle speed is used for passenger cars and taxis.

$$\frac{EF_{km,VP,i,1-4}}{EF_{km,VB,i}} = \left(\frac{V_{P,1-4}}{V_B} \right)^{-0.7} \quad \text{Equation (23)}$$

Where:

- $EF_{km,VB,i}$ = Emission factor per kilometer for cars/taxis at the baseline speed (gCO₂/km)
- $EF_{km,VP,i,1-4}$ = Emission factor per kilometer for cars/taxis at the project speed in years 1 and 4 of the crediting period (gCO₂/km)
- V_B = Average speed of cars/taxis prior to the project start (km/h)
- $V_{P,1-4}$ = Average speed of cars/taxis on affected roads in years 1 and 4 of the crediting period (km/h)

94. V_B and $V_{P,1-4}$ in this case refer to moving speed, i.e. the speed of the vehicle under moving conditions.

5.5.4. Upstream emissions from gaseous fuels ($LE_{UP,y}$)

95. Upstream leakage of gaseous fuels shall be only included if the project vehicles consume more gaseous fuels than baseline vehicles. In this case, and in order to simplify the calculations, the calculation of upstream leakage emissions is based only on the gaseous fuels used under the project activity. The methodological tool "Upstream leakage

emissions associated with fossil fuel use” shall be used to calculate leakage. The following leakage sources shall be considered:

- (a) Fugitive CH₄ emissions associated with fuel extraction, processing, liquefaction, transportation, re-gasification and distribution of natural gas used in the project plant and fossil fuels used in the grid in the absence of the project activity;
- (b) In the case more LNG is used under the project activity: CO₂ emissions from fuel combustion/electricity consumption associated with the liquefaction, transportation, re-gasification and compression into a natural gas transmission or distribution system.

5.5.5. Upstream emissions related to the handling and use of green hydrogen ($LE_{hyd,y}$)

96. In the case of vehicles powered by hydrogen included in the CDM project activity, leakage shall also account for upstream emissions related to the production, handling and use of green hydrogen. These emissions occur due to electricity consumption and fossil fuel combustion for the production, handling and use of green hydrogen, which includes:

- (a) Hydrogen compression and storage at the hydrogen production facility and charging/fuel stations;
- (b) Transportation of hydrogen (by road or via pipelines) to the hydrogen charging/fuel stations; and
- (c) Emission from water reservoirs of dedicated hydro power plants supplying electricity for the hydrogen production facility.

97. Emissions due to electricity consumption for the handling and use of green hydrogen shall be estimated using the latest approved version of the TOOL05, where the parameter $EC_{LE,I,Y}$ in Equation (3) of the tool corresponds to the electricity consumed by leakage electricity consumption source I due to the handling and use of green hydrogen in year y .

98. Emissions due to transportation of hydrogen (by road or via pipelines) to the hydrogen charging/fuel stations shall be estimated using the latest approved version of the TOOL12.

99. In case the green hydrogen facility utilizes electricity from a dedicated hydro power plant, leakage emissions shall include the emission from water reservoirs of the hydro power plant calculated according to the procedure outlined in paragraph 5.4.3 of the latest version of ACM0002 “Grid-connected electricity generation from renewable sources”:

- (i) calculation of the power density of the dedicated hydro power plant
- (ii) identification of the relevant default emission factor (kgCO₂e/kWh) for the electricity produced by the dedicated hydro power plant
- (iii) calculation of the emission from water reservoirs as the product of the emission factor specified under (ii) and the amount of electricity produced by the dedicated hydro power plant and used by the green hydrogen facility

100. The green hydrogen facility shall not use electricity from a dedicated hydro power plant with a power density lower than the value specified in paragraph 7 (b) of the latest version of ACM0002 “Grid-connected electricity generation from renewable sources”.

5.6. Emission reductions

101. Emissions reductions are calculated as:

$$ER_y = BE_y - PE_y - LE_y \quad \text{Equation (24)}$$

Where:

ER_y = Emissions reductions in year y (tCO₂)

BE_y = Baseline emissions in year y (tCO₂)

PE_y = Project emissions in year y (tCO₂)

LE_y = Leakage emissions in year y (tCO₂)

5.7. Changes required for methodology implementation in 2nd and 3rd crediting periods

102. When a renewable crediting period is chosen, project participants shall use a four-step model, or equivalent, of the transportation system of the project city for the purpose of modelling relevant parameters from the TOOL18, such as the modal split, share of passengers who shifted from electricity-based or road-based vehicle category i , S_i or share of passenger-kilometers who shifted from electricity-based or road-based vehicle category i , SD_i , and an average trip distances travelled by passengers who shifted from electricity-based or road-based vehicle category D_i for the second and third crediting periods. The model should be tested and calibrated with the results of origin-destination surveys. For the determination of the baseline emissions, the most conservative value shall be used between estimates of baseline emissions based on the modelled parameters and the parameters determined via passenger surveys in the 4th year of the previous crediting period.

103. The parameters below can be based on data from municipal transit authorities on vehicle registration statistics from the respective city or data from vehicle control stations (technical and emission control stations):

- (a) Percentage or share of vehicle-kilometers or vehicles in vehicle category i using fuel type n in year y , and
- (b) $N_{i,n,y}/N_{i,y}$, or parameters used to estimate this share $N_{i,y}$ and $N_{i,n,y}$, which are the number of vehicle-kilometers or vehicles in vehicle category i , and the number of vehicle-kilometers or vehicles in vehicle category i using fuel type n in year y .

104. Furthermore, project participants shall apply the latest approved version of the TOOL11.

5.8. Data and parameters not monitored

105. In addition to the parameters listed in the tables below, the procedures contained in the tools referred to in this methodology also apply.

Data / Parameter table 1.

Data / Parameter:	$PBL_{B,x}$
Data unit:	Passengers
Description:	Passengers transported by baseline buses prior to the project starting year x (per day or year)
Source of data:	Municipal transit authorities or bus operators. Data from the most recent calendar year prior to the start of commercial operation of the project system or prior to the submission of the CDM-PDD for validation, whatever is earlier. Vintage maximum three years. Use the same vintage as for the parameter $TDBL_{P,B}$
Measurement procedures (if any):	-
Any comment:	-

Data / Parameter table 2.

Data / Parameter:	$DD_{Z,s,x}$
Data unit:	km
Description:	Total distance driven by bus size s in year x
Source of data:	Data from bus companies (company records), municipal transit authorities or specific studies done by the project proponent or a third party. Vintage maximum three years
Measurement procedures (if any):	Distance driven by buses is often recorded by bus companies based on odometer reading. Preferable is GPS or other electronic means, however this is not yet common in bus companies. Data can also be based on sample measurements based, in general, on daily distance driven (measured by odometer or GPS) plus the average number of operation days of a bus (based on bus operator information). The total distance driven by all buses is the multiplication of the average annual distance driven per bus and the number of registered buses operating in the larger urban zone of the city. The data source used to monitor this parameter shall also be used to monitor parameter $N_{k,x}$, as well as $SFC_{i,n,x}$ and $P_{i,x}$ in the tool TOOL18.
Any comment:	Bus sizes: small (S), medium (M) and large (L).

Data / Parameter table 3.

Data / Parameter:	$N_{Z,s,x}$
Data unit:	Number of buses bus size s in year x
Description:	Number of buses in use in the baseline

Source of data:	Municipal transit authorities based on vehicle registration statistics from the respective city or data from vehicle control stations (technical and emission control stations). If no city/municipal data is available, regional data (canton, state) or, as a last option, national data can be used. Vintage maximum three years
Measurement procedures (if any):	The data source used to monitor this parameter shall also be used to monitor parameter $DD_{i,S,x}$, $DD_{i,M,x}$, $DD_{i,L,x}$ as well as $SFC_{i,n,x}$ and $SEC_{i,x}$ in the TOOL18.
Any comment:	Bus sizes: small (S), medium (M) and large (L).

Data / Parameter table 4.

Data / Parameter:	RS_x
Data unit:	km
Description:	Total road space available in year x
Source of data:	Official statistics or studies conducted by the project proponent or a third party
Measurement procedures (if any):	Based on infra-structure statistics
Any comment:	Road space baseline based on official information. Reduced road space based on construction plans (reduced road space is lanes which were eliminated due to dedicating bus lanes to the project system).

Data / Parameter table 5.

Data / Parameter:	RS_y
Data unit:	km
Description:	Total road space available due to the project activity
Source of data:	Official statistics or studies conducted by the project proponent or a third party
Measurement procedures (if any):	Based on infra-structure statistics
Any comment:	Road space based on official information and on construction plans. During the crediting period the actual RS_y implemented should be checked against the ex ante expectation. If there are differences, the Project Proponent should demonstrate why it does not affect the project design (i.e. by applying equation 9 again), or request a Post Registration Change to incorporate or eliminate the leakage calculation

Data / Parameter table 6.

Data / Parameter:	AD_T
Data unit:	km /taxi
Description:	Average annual distance driven by taxis
Source of data:	Municipal transit authorities or taxi operators. Vintage maximum three years

Measurement procedures (if any):	Based on records of taxi companies or on surveys. A simple method can be odometer reading of a sample of taxis and dividing total distance driven by the vehicle age
Any comment:	-

Data / Parameter table 7.

Data / Parameter:	$N_{i,x}$
Data unit:	Number of vehicles
Description:	Number of vehicles of vehicle category i per annum using the affected roads in year x
Source of data:	Municipal transit authorities or studies ordered by project proponent. Vintage maximum three years
Measurement procedures (if any):	Visual counting on the identified roads. Counting should be based on various parts of the road, if major roads depart from the observed road to ensure average numbers
Any comment:	The same method should be applied to determine number of cars and taxis in the project situation to ensure a consistent approach. Vehicle categories: passenger cars (C) and taxis (T)

Data / Parameter table 8.

Data / Parameter:	V_B
Data unit:	km/h
Description:	Average total speed and average speed under circulation is measured
Source of data:	Municipal transit authorities or studies ordered by project proponent. Vintage maximum three years, if no major infrastructure or policy (e.g. licence plate scheme or new traffic signalling) changes have occurred since the last major change
Measurement procedures (if any):	On-board measurements determining the average speed when circulating and average total speed on the road based e.g. on GPS
Any comment:	Average speed required for calculation of the rebound effect refers to total distance divided by total time on the affected road. Average moving speed required for the calculation of the speed effect refers to the speed under moving conditions i.e. total distance divided by time under movement (total time minus standstill time of vehicle), on the affected road. Only passenger cars and 4-wheel taxis are monitored. The same speed data is taken for both vehicle types. The same method should be applied to determine vehicle project speed thereafter to ensure a consistent approach. Required for monitoring of the rebound effect and the speed effect on affected roads

Data / Parameter table 9.

Data / Parameter:	$TD_{Z,x}$, $TD_{T,x}$, $TD_{C,x}$
Data unit:	km
Description:	$TD_{Z,x}$: Total distance driven by public transport buses in year x $TD_{T,x}$: Total distance driven by public transport taxis in year x $TD_{C,x}$: Total distance driven by passenger cars in year x
Source of data:	Official statistics (vehicle registration data; transportation statistics)
Measurement procedures (if any):	-
Any comment:	Data can be either with or without informal transport as long as the above mentioned parameters are from the same data source. In general, data including only formal transport is of a better data quality and should thus be taken

Data / Parameter table 10.

Data / Parameter:	GWP_{H2}
Data unit:	t CO ₂ /t H ₂
Description:	Global Warming Potential (GWP) of hydrogen
Source of data:	IPCC AR4 WG1 as under chapter 2.10.3.6
Value to be applied	5.8
Any comment:	The GWP value is calculated as an indirect 100-year GWP.

Data / Parameter table 11.

Data / Parameter:	PL_{H2}
Data unit:	Percentage
Description:	Physical leaks of hydrogen from the hydrogen value chain as percentage of the total consumption
Source of data:	A study "Hydrogen emissions from the hydrogen value chain-emissions profile and impact to global warming" by Jasmin Cooper, Luke Dubey, Semra Bakkaloglu, Adam Hawkes, published at "Science of The Total Environment", by Elsevier B.V. on 15 July 2022.
Value to be applied	5
Any comment:	The project participants may propose another value through a request for revision of this methodology.

6. Monitoring methodology

6.1. Data and parameters monitored

106. All data collected as part of monitoring should be archived electronically and be kept at least for two years after the end of the last crediting period. One hundred per cent of the data should be monitored if not indicated otherwise in the tables below. All measurements should be conducted with calibrated measurement equipment according to relevant industry standards.

107. In addition to the parameters listed in the tables below, the procedures contained in the tools referred to in this methodology also apply.

Data / Parameter table 12.

Data / Parameter:	P_y
Data unit:	Passengers
Description:	Total number of passengers in year y
Source of data:	As per the "TOOL18: Baseline emissions for modal shift measures in urban passenger transport"
Measurement procedures (if any):	As per the "TOOL18: Baseline emissions for modal shift measures in urban passenger transport"
Monitoring frequency:	As per the "TOOL18: Baseline emissions for modal shift measures in urban passenger transport"
QA/QC procedures:	As per the "TOOL18: Baseline emissions for modal shift measures in urban passenger transport"
Any comment:	-

Data / Parameter table 13.

Data / Parameter:	$EF_{pkm,i,1-4}$
Data unit:	tCO ₂ /pkm
Description:	Emission factor per passenger-kilometer of mode i in years 1 and 4 of the crediting period y (gCO ₂ /pkm)
Source of data:	Calculated based on equations 2 and 3 from the "TOOL18: Baseline emissions for modal shift measures in urban passenger transport".
Measurement procedures (if any):	As per the "TOOL18: Baseline emissions for modal shift measures in urban passenger transport".
Monitoring frequency:	Calculated based on the "TOOL18: Baseline emissions for modal shift measures in urban passenger transport", through surveys conducted in the end of years 1 and 4 of the crediting period,.
QA/QC procedures:	As per the "TOOL18: Baseline emissions for modal shift measures in urban passenger transport".
Any comment:	The parameter $EF_{pkm,i,x}$ in the tool corresponds to the emission factor per passenger-kilometer of mode i in years 1 and 4 of the crediting period y ($EF_{pkm,i,1-4}$). It has to be determined separately for electricity based transport system (equation 2 of the tool) and fuel based transport system (equation 3 of the tool).

Data / Parameter table 14.

Data / Parameter:	$DPE_{FC,y}$
Data unit:	tCO ₂
Description:	Direct project emissions from fuel consumption in year y
Source of data:	Calculated based on the TOOL03

Measurement procedures (if any):	As per the TOOL03
Monitoring frequency:	As per the TOOL03
QA/QC procedures:	As per the TOOL03
Any comment:	<p>The parameter $PE_{FC,j,y}$ in the tool corresponds to the direct project emissions from the project transport system that uses fossil fuels in year y (DPE_y), and the element process j corresponds to the combustion of fuel type n in the project vehicles.</p> <p>If the project does not have reliable records on total fuel consumed, the specific fuel consumption of a representative sample of comparable transport units (comparable technology, vintage and size) and the total distance driven are used to determine the parameter $FC_{i,j,y}$, as per equation (5).</p>

Data / Parameter table 15.

Data / Parameter:	$DPE_{EC,y}$
Data unit:	tCO ₂
Description:	Direct project emissions from electricity consumption in year y
Source of data:	Calculated based on the TOOL05
Measurement procedures (if any):	As per the TOOL05
Monitoring frequency:	As per the TOOL05
QA/QC procedures:	As per the TOOL05
Any comment:	The parameter $PE_{EC,j,y}$ in the tool corresponds to the direct project emissions from the project transport system that uses fossil fuels in year y ($DPE_{FC,y}$). Only electricity consumed for train propulsion should be included in rail-based MRTS.

Data / Parameter table 16.

Data / Parameter:	$SFC_{i,n,y}$
Data unit:	Mass or volume units of fuel/km
Description:	Specific fuel consumption of vehicle category i using fuel type n in year y included in the sample
Source of data:	MRTS operator(s) or project owner

Measurement procedures (if any):	<p>Calculated based on total fuel consumed and total distance driven per bus size sub-category of the buses included in the sample.</p> <p>The specific fuel consumption is taken from a representative sample of comparable project units in terms of technology, vintage and size. Buses of the sample shall be project units running on project bus lanes. The sample criteria are based on technology (Euro standard), age, and bus size. The sample shall be representative of the route(s) serviced by the project as well as the operation frequencies during the day to account for differences of fuel consumption related to time.</p> <p>Measurement procedures shall include distance driven (preferably recorded by GPS or other electronic means with a maximum error level of 5 per cent) and the fuel consumed monitored either through appropriate equipment installed in the units or through standard measurement procedures at a calibrated fuel station</p>
Monitoring frequency:	Annually
QA/QC procedures:	To be conservative project fuel consumptions based on specific fuel consumption values of samples shall be based on the upper limit of the uncertainty band at a 95 per cent confidence level i.e. with 95 per cent confidence the actual average fuel consumption is equal to or lower than the value used by the project
Any comment:	<p>This data is only required if total fuel consumption (TC) is not available.</p> <p>This data is only collected if the MRTS operates with buses</p>

Data / Parameter table 17.

Data / Parameter:	$DD_{P,J,n,y}$
Data unit:	km
Description:	Distance driven by project units using fuel type n in year y
Source of data:	MRTS operator(s) or system manager
Measurement procedures (if any):	Based on GPS (preferred), other electronic means, odometer or number of units per route and turnover per route
Monitoring frequency:	Continuously, aggregated at least annually
QA/QC procedures:	In many systems operators are paid according to distance driven. Payment of operators can thus be used to check the distance driven
Any comment:	Used only for QA/QC in case of bus operated MRTS to control the specific fuel consumption (fuel per distance)

Data / Parameter table 18.

Data / Parameter:	$N_{i,1-4}$
Data unit:	Number of vehicles
Description:	Number of vehicles category i in years 1 and 4 of the crediting period
Source of data:	Municipal transit authorities based on vehicle registration statistics from the respective city or data from vehicle control stations (technical and emission control stations)

Measurement procedures (if any):	For buses as well as for taxis informal or illegal units may operate. While estimates on the number of informal units may be available these are due to their nature not trustworthy. For both categories it is thus recommended to only include formally registered units
Monitoring frequency:	Studies conducted at the end of years 1 and 4 of the crediting period
QA/QC procedures:	-
Any comment:	Vehicle categories: buses (B), passenger cars (C), taxis (T)-

Data / Parameter table 19.

Data / Parameter:	$EF_{km,i,1-4}$
Data unit:	gCO ₂ /km
Description:	Emission factor per kilometer for vehicle category <i>i</i> in years 1 and 4 of the crediting period (gCO ₂ /km)
Source of data:	Calculated based on equation 1 from the TOOL18
Measurement procedures (if any):	As per the TOOL18
Monitoring frequency:	Calculated based on surveys conducted at the end of years 1 and 4 of the crediting period, based on the TOOL18.
QA/QC procedures:	As per the TOOL18
Any comment:	The parameter $EF_{km,i,x}$ in the tool corresponds to the emission factor per kilometer of vehicle category <i>i</i> in years 1 and 4 of the crediting period <i>y</i> ($EF_{km,i,1-4}$). Vehicle categories: buses (Z) and taxis (T). For taxis, a default emission factor for new vehicles can be obtained from the source provided in the table in section "Data and Parameters not monitored" of the tool.

Data / Parameter table 20.

Data / Parameter:	$OC_{i,t}$
Data unit:	Passengers
Description:	Average occupancy of vehicle category <i>i</i> in the period of time <i>t</i>
Source of data:	Municipal transit authorities or surveys conducted by the project proponent or a third party
Measurement procedures (if any):	Based on visual occupancy studies for all vehicle categories. For buses the occupancy rate is based on boarding-alighting studies, electronic smart tickets or on visual occupancy studies with expansion factors for routes served to determine the average occupancy rate along the entire route. As an alternative for buses, the occupancy rate can be based on average trip distance of bus passengers, total passengers and total distance driven of buses. For taxis, the driver should not be counted. The detailed procedures concerning visual occupancy and boarding alighting studies are presented in appendices 1, 2 and 3

Monitoring frequency:	Studies/surveys conducted at the end of years 1 and 4 of the crediting period
QA/QC procedures:	-
Any comment:	<p>Period of time when the parameters are measured: most recent calendar year prior to the start of commercial operation of the project system or prior to the submission of the CDM-PDD for validation, whatever is earlier (x) or years 1 and 4 of the crediting period (1-4)</p> <p>Vehicle categories: buses (B), passenger cars (C), taxis (T)</p>

Data / Parameter table 21.

Data / Parameter:	$CV_{i,t}$
Data unit:	Passengers
Description:	Average capacity of vehicle category <i>i</i> in the period <i>t</i> (passengers)
Source of data:	Official statistics
Measurement procedures (if any):	-
Monitoring frequency:	Surveys conducted at the end of years 1 and 4 of the crediting period
QA/QC procedures:	-
Any comment:	<p>Period of time when the parameters are measured: most recent calendar year prior to the start of commercial operation of the project system or prior to the submission of the CDM-PDD for validation, whatever is earlier (x) or years 1 and 4 of the crediting period (1-4)</p> <p>Vehicle categories: buses (B), passenger cars (C), taxis (T)</p> <p>For taxis, the average capacity shall not include the driver.</p>

Data / Parameter table 22.

Data / Parameter:	$BSCR_y$
Data unit:	Number of vehicles
Description:	Cumulative bus units displaced by the project on the trunk lanes as a result of the project in year <i>y</i>
Source of data:	Municipal transit authorities, official statistics or studies ordered by project proponent
Measurement procedures (if any):	-
Monitoring frequency:	Yearly
QA/QC procedures:	-
Any comment:	<p>Used to calculate ARS_y.</p> <p>The number of buses circulated in trunk lanes prior to the construction of the project activity that have ceased to circulate in trunk lanes due to the project activity are to be considered. These buses can be retired or used in another part of the network</p>

Data / Parameter table 23.

Data / Parameter:	$TD_{i,1-4}$
Data unit:	km
Description:	Average trip distance driven by vehicle category i on the affected roads in years 1 and 4 of the crediting period
Source of data:	Municipal transit authorities or project owner
Measurement procedures (if any):	Electronic or visual tracking of samples of vehicles entering/exiting the affected roads registering the entry and the exit point and measuring the distance by GPS or other means
Monitoring frequency:	Surveys conducted at the end of years 1 and 4 of the crediting period
QA/QC procedures:	-
Any comment:	-

Data / Parameter table 24.

Data / Parameter:	$MS_{i,1-4}$
Data unit:	Percentage
Description:	Net share of passengers using the MRTS which would have used mode i in the years 1 and 4 of the crediting period
Source of data:	Survey conducted by an external survey company
Measurement procedures (if any):	Survey. The relevant question numbers are 2 and 3
Monitoring frequency:	The survey is conducted at the end of years 1 and 4 of the crediting period
QA/QC procedures:	See Appendix 4 for the survey design
Any comment:	Only used for leakage calculation of rebound effect (reduced amount of cars and taxis) if required (see condition for rebound effect calculation)

Data / Parameter table 25.

Data / Parameter:	$VP_{,1-4}$
Data unit:	km/h
Description:	Average speed of cars/taxis on affected roads in years 1 and 4 of the crediting period
Source of data:	Municipal transit authorities or studies ordered by project proponent

Measurement procedures (if any):	<p>On-board measurements determining the total average speed and the average moving speed (when circulating) on the affected road based, e.g. on GPS measuring. The same methodology as for determination of V_B should be used.</p> <p>Average speed required for calculation of the rebound effect refers to total distance divided by total time, on the affected road.</p> <p>Average moving speed required for calculation of the speed effect refers to speed under moving conditions i.e. total distance divided by time under movement (total time minus standstill time of vehicle), on the affected road.</p> <p>Taxis and passenger cars are treated identical. This condition should be monitored for each affected road</p>
Monitoring frequency:	Once at the end of years 1 and 4 of the crediting period
QA/QC procedures:	-
Any comment:	Only passenger cars and 4-wheel taxis. See also table for V_B

Data / Parameter table 26.

Data / Parameter:	$LE_{UP,y}$
Data unit:	tCO ₂
Description:	Leakage upstream emissions of gaseous fuels during the year y
Source of data:	As per "Upstream leakage emissions associated with fossil fuel use"
Measurement procedures (if any):	As per "Upstream leakage emissions associated with fossil fuel use"
Monitoring frequency:	As per "Upstream leakage emissions associated with fossil fuel use"
QA/QC procedures:	As per "Upstream leakage emissions associated with fossil fuel use"
Any comment:	As per "Upstream leakage emissions associated with fossil fuel use"

Data / Parameter table 25.

Data / Parameter:	$LE_{hyd,y}$
Data unit:	tCO ₂
Description:	Leakage upstream emissions related to the handling and use of green hydrogen in year y
Source of data:	As per the TOOL05 and TOOL12
Measurement procedures (if any):	As per the TOOL05 and TOOL12
Monitoring frequency:	As per the TOOL05 and TOOL12
QA/QC procedures:	As per the TOOL05 and TOOL12
Any comment:	As per the TOOL05 and TOOL12

Data / Parameter table 26.

Data / Parameter:	Green attribute of hydrogen
Data unit:	N/A
Description:	Demonstration that the hydrogen is produced by dedicated greenfield renewable energy generation plant.

Source of data:	Green hydrogen certificate from credible source to be acquired by project participant.
Measurement procedures (if any):	Green hydrogen certification in accordance with international standards and this methodology.
Monitoring frequency:	For every consignment of hydrogen
QA/QC procedures:	
Any comment:	

DRAFT

Appendix 1. Guideline for the establishment of load factor studies for buses based on visual occupancy

1. Load factor surveys based on visual occupancy studies use the following procedures:
 - (a) Vehicle categories are defined according to the characteristics of the fleet and types of services (e.g. with or without standing passengers);
 - (b) Occupancy categories are defined (usually five or six), for instance <50 per cent occupied, 50-100 per cent seats occupied, 100 per cent seats occupied, <50 per cent space for standing passengers occupied, 50-100 per cent of standing space occupied, overload (>100 per cent of legally permitted space occupied);
 - (c) The number of passengers corresponding to each vehicle category and type of service is defined. A pilot study could be completed to calibrate the levels of occupancy with actual in vehicle counts;
 - (d) Formats for field study are prepared;
 - (e) Field data collectors are trained;
 - (f) Locations, days and times for field study are defined. Points are strategically located to cover all the routes with the minimum of points. Suggested days are Tuesday to Thursday, avoiding days immediately after or before a holiday. A typical season (school or university vacations) should be avoided. The recommended time period for the study is 6AM-9PM. Measurements should be realized for all weekdays proportional to the number of buses displaced on these days. The same days and time periods need to be chosen for the baseline as well as for the monitoring studies to ensure data comparability;
 - (g) Field data is collected. Coverage of the occupancy counts should be higher than 95 per cent of the number of buses that cross the checkpoint. 100 per cent coverage is desired. To control this outcome, a separate vehicle count is advised. Data can be adjusted with the actual count;
 - (h) Data is digitized and its quality is controlled. In case of mistakes in data collection, counts should be repeated;
 - (i) The total number of vehicles, number of available spaces (vehicle capacity) and the total number of passengers is reported. Occupancy is the number of passengers divided by the vehicle capacity.
2. The average load factor is equal to the average load factor of each route multiplied by the total number of passengers in the route, divided by the total passengers in the network.

Appendix 2. Guideline for the establishment of load factor studies for buses based on boarding-alighting surveys

3. Load factor surveys based on boarding-alighting studies for buses use the following procedure:
 - (a) Routes for the survey shall be selected, weighted upon the expected number of passengers per route. Only active routes are included;
 - (b) The load factor (occupancy rate) is defined as the average percentage of capacity of the vehicle used by passengers. The average load factor of a route is based on the average of each load factor between each station of the specified route;
 - (c) The common operational procedure used is to ride on the unit and count at each station the number of passengers boarding and alighting. Instead of manual controls electronic or mechanical controls can be used;
 - (d) Locations, days and times for the survey are defined. Atypical seasons (school or university vacations) should be avoided. The recommended time period for the study is the entire period of operation of the selected buses. Measurements should be realized for all weekdays proportional to the number of buses displaced on these days. The same days and time periods need to be chosen for the baseline as well as for the monitoring studies to ensure data comparability;
 - (e) The survey shall be conducted during the entire operation period of buses (not only peak or off-peak hours);
 - (f) The units selected are clearly identified including licence plate, day monitored, number of turn-arounds, route and route distance;
 - (g) Data are digitized and its quality is controlled. In case of mistakes in data collection, counts should be repeated.
4. Boarding and alighting information can also be obtained in some cases from electronic means such as electronic ticketing, digital camera passenger identification per bus, monitoring of average bus weight per station, etc.

Appendix 3. Guideline for the establishment of load factor studies for taxis/motorcycles or passenger cars

1. The actual number of passengers excluding the driver of taxis is counted in a given point within a given time period. The counting is based on visual occupancy counting the number of passengers occupying the vehicle excluding the driver for taxis. The procedures to establish visual occupancy are:
 - (a) Locations, days and times for field study are defined, avoiding days immediately after or before a holiday. Atypical seasons (school or university vacations) should be avoided. The same days and time periods need to be chosen for the baseline as well as for the monitoring studies to ensure data comparability;
 - (b) Field data is collected. Coverage of the occupancy counts should be higher than 95% of the number of taxis that cross the checkpoint. One hundred per cent coverage is desired. To control this outcome a separate vehicle count is advised. Data can be adjusted with the actual count;
 - (c) Occupancy is the number of passengers using the vehicle. The driver is not counted for taxis. Taxis without passengers are counted as no (zero) occupancy;
 - (d) The total number of vehicles and the total number of passengers is reported. The average occupancy rate of vehicles is the total number of passengers divided by the total number of vehicles in which counts were performed;
 - (e) The study is realized in different locations of the larger urban zone of the city;
 - (f) The same methodology is used for the load study performed prior to the project start and during its monitoring. Locations of monitoring can, however, change as traffic flows in the larger urban zone of the cities change over time. Other parameters of the study (duration, sample size, counting method, etc.) however should remain constant to ensure consistency and comparability of studies.

Appendix 4. Methodological design of survey MRTS

1. Methodological design of survey

1. The methodological design of the survey is presented in detail. The following points are discussed:
 - (a) Survey objective;
 - (b) Target population;
 - (c) Sample frame;
 - (d) Sample design;
 - (e) Geographical coverage;
 - (f) Sample frequency;
 - (g) Sample size;
 - (h) Use of a pilot test survey;
 - (i) Selecting the sample;
 - (j) Methodology for information collection and estimation of the parameters;
 - (k) Survey realization;
 - (l) Calculation of a trip distance in the survey;
2. Whenever the MRTS is extended, a new survey distribution is realized and data of the new survey is used for calculating emissions reductions achieved from the moment of the MRTS extension.

1.1. Technical summary data sheet of the survey -

Table 1. Strategy and sample design in the MRTS passenger survey

Parameter	<p>The main parameters that must be determined from the survey are:</p> <ul style="list-style-type: none"> • For Baseline Emissions: <ul style="list-style-type: none"> ○ Share of passengers who shifted from electricity-based or road-based vehicle category i (parameter S_i from the TOOL18); ○ Average trip distance travelled by passengers who shifted from electricity-based or road-based vehicle category i (parameter D_i from the TOOL18). • For Indirect Project Emissions: <ul style="list-style-type: none"> ○ Average indirect project trip distance of surveyed passengers using mode i in years 1 and 4 of the crediting period (parameter $D_{ind,i,1-4}$ from Equation 4).
Target population	Passengers over 12 years using the MRTS

Sample frame	Passenger flow in selected stations of the MRTS
Sample design	Two stage probabilistic design: <ul style="list-style-type: none"> • First stage: Stratified – Simple Random Sampling (SRS); <ul style="list-style-type: none"> ○ <u>Main strata:</u> Group of Stations based on passenger flow; stations sampled from within such strata; ○ <u>Sub-strata:</u> Ranges of hours; an hour interval sampled from within such sub-strata; • Second stage: Systematic Sampling of passengers in selected hour intervals.
Coverage	Larger urban zone of the city where the MRTS operates
Size of Universe	Generally, in one day an MRTS mobilizes between 100,000 and 3,000,000 passengers, depending on the type of transport system
Sample size	The sample size determination depends on the transport system characteristics regarding daily passenger flow and number of stations. The sample size indicated is an estimate and needs to be determined per project type (see corresponding chapter)
Sample frequency	At the end of years 1 and 4 of the crediting period, through an entire week.
Method of information collection	The information will be obtained through the face-to-face application of the established questionnaire on a random base
Consistency of the survey results	The internal consistency of the results of the survey shall be carefully checked. The reliability will be measured using the Cronbach's alpha. A coefficient of over 0.7 has to be reached, values over 0.9 shall be re-checked to avoid redundancy of data. In case the survey does not demonstrate internal consistency in their results, it will be rejected and another survey could be arranged

2. Survey objective

3. The survey objective is to determine the input parameters needed to calculate:
 - (a) The baseline emissions caused by passengers which use the MRTS and in absence of the latter would have used other modes of transport to realize their trip;
 - (b) The indirect project emissions caused by passengers using the MRTS, which correspond to the emissions caused from the point of origin (O) to the MRTS entry station, and from the MRTS exit station to the final destination (D).

3. Target population

4. The target population are all passengers over 12 years of age. Smaller children are excluded due to problems in answering the questions. Also, smaller children, in general, are accompanied by their parents or an adult and thus have the same trip sequence as the adult person.

4. **Sample frame**

5. The sample frame is the passenger flow in selected stations of the MRTS. Data for the passenger frame is obtained from the system manager.


5. **Sample design**

6. A two staged probabilistic design is applied:
 - (a) **First stage:** Stratified – Simple Random Sampling (SRS) to identify the MRTS stations and the hours interval when the survey will be conducted, where:
 - (i) Main strata: Group of Stations. Stations are grouped depending on the passenger flow per station to provide information for busier stations and less frequented stations. In practical terms, three groups of stations could be created: stations with a high, medium and low passenger volume. In the case of large heterogeneity of passenger flows an additional group is included to control this variability.

The stations where the survey will be conducted are selected from main strata. The selected stations shall remain fixed through the survey week;
 - (ii) Sub-strata: Ranges of hours. In MRTSs, there are generally periods of heterogeneous passenger flow (e.g. morning peak, evening peak, /off-peak hours). Such ranges of hours are to be determined for the 7 days of the survey week, and an hour selected from each range.

DRAFT

Figure 1. Stratification model used



(b) **Second stage:** Systematic sampling of passengers in selected stations within the selected hours.

6. Geographical coverage

7. The geographical coverage is the area where the MRTS operates (project boundary).

7. Sample frequency

8. Two surveys shall be conducted during the crediting period: at the end of the 1st and 4th years of the crediting period.

9. The survey shall take place during an entire week that does not correspond to a public holiday or a holiday season and shall be representative for the average demand for transport services in the considered year.

8. Sample size

10. To ensure that the input parameter estimates are sufficiently precise (where precision is quantified via a 95% confidence interval for a parameter), the sample size for estimating the input parameters below is to be considered at the planning stage:

(a) S_i ("Share of passengers who shifted from electricity-based or road-based vehicle category i ");

- (b) D_i ("Average trip distance travelled by passengers who shifted from electricity-based or road-based vehicle category i ");
- (c) $D_{ind,i,1-4}$ (Average indirect project trip distance of surveyed passengers using mode i in years 1 and 4 of the crediting period).

11. Following the "Standard: Sampling and surveys for CDM project activities and programmes of activities", sample size determination should be based on 95/10 confidence/precision for large-scale CDM project activities. The sample size selected shall be the highest among the values determined for each input parameter.

9. Use of a pilot survey

12. Data obtained from a similar transport system may be used as a reference and pilot result. In case the MRTS is already operating, it is recommended to realize a pilot sample which can be of a smaller sample size and simplified concerning stratification etc. In cases where the MRTS is not operating, results from comparable surveys from comparable MRTS from other cities may be used as a reference.

10. Selecting the sample

13. The method to select stations, hours and passengers for applying the survey has to guarantee a random and non-biased selection process, which is especially important in face-to-face interviews.

10.1. Selection of stations and evaluation hours.

14. Given that there is a complete list of stations, the selection of stations within the main strata is conducted according to a Simple Random Sampling design.

15. Similarly, a specific hour interval is selected from within each sub-stratum, that is, the range of hours (e.g. morning peak, evening peak, off peak) by simple random sampling.

10.2. Selection of passengers

16. Given that there is no reference frame or list frame for the identification of MRTS users, the selection of the sample in the last stage will be performed according to a systematic sampling design within each selected hour and considering the following steps:

- (a) A random starting point is generated between 1 and n ;
- (b) Systematic selection of passengers: every n^{th} passenger entering the station, starting with the random number. In this way, if the random number is 20, the first passenger selected is the 20th that enters the station, the 2nd $n+20$ and thus successively every n^{th} passenger.

11. Methodology for information collection and estimation of the parameter

11.1. General considerations on information collection

17. The information will be obtained through the face-to-face application of the questionnaire provided in Appendix 5.

18. According to the selected stations and hour intervals, each survey interviewer will carry out the number of established surveys. Given that the selection of people is done randomly in a time range, the start point, that is the person number from which the contact begins, is random and is defined by the appointed pollster supervisor.
19. The random selection of individuals, as well as the sufficiency in the sample size, enables obtaining dispersion and representation of the study population through the sample. Further, it allows controlling factors that may affect the user type, in terms of use of modes of transport and distance in these travels.

12. Survey realization

20. The survey shall be realized through a company with minimum 3 years of experience in comparable surveys in the respective country to ensure a professional survey execution. The following principles are to be followed in the survey realization:
 - (a) Non-responses should be recorded;
 - (b) Record and store all original surveys;
 - (c) Surveys are conducted at MRTS stations when people wait for MRTS-boarding. It should be avoided to realize the survey with people de-boarding the MRTS as latter will not want to invest time in a survey thus potentially giving wrong answers.

12.1. Preparation phase

21. This phase is characterized by the development of all the activities previous to the execution of the field operation and it is divided in:
 - (a) Drafting of the manual on information collection and basic concepts. The manual on information collection and basic concepts covers in general terms the profile of the field personnel, the questionnaire structure, the instructions and specifications for filling in the questionnaire, the definitions and basic concepts of the study and the instructions and formats used;
 - (b) Selection and training of field personnel. The selection and training of the field personnel is performed on concepts of filling in of questionnaires, in order to select the most adequate survey interviewers for the development of the field work:
 - (i) A pre-test is performed with the aim of familiarizing the supervisors with the instrument of information collection and establishing in general terms the acceptance degree of the population facing the instrument's application. The pre-test is also to assure that respondents understand what the MRTS is as they might not have taken a similar system before, to ensure that all the concepts are clearly defined and the questions are not ambiguously phrased and avoid interviewer errors. Interviewers may misread the question or twist the answers in their own words and thereby introduce bias. The pre-test has to detect and minimize this potential error;
 - (ii) The results of the pre-test will be documented and will be taken into consideration for the modification of the final instrument and for the preparation of the model of information collection.

12.2. Validation process of the information

22. A supervisor should be used in the field to carry out the field verifications, guaranteeing the validity of the gathered information as well as the attained coverage.

13. Calculation of trip distance in the survey

23. Trip distances need to be determined for each surveyed passenger. The following procedures are applied:
- (a) For NMT, others and induced traffic this is not required as the applied EF is "0";
 - (b) For users of buses either:
 - (i) The shortest possible geographical distance based on electronic maps or measuring the distance between the two points with GPS or a comparable mean or through distance measurement on maps; or
 - (ii) Measuring the actual distance from the bus entry station to the bus exit station based on (electronic) route maps of the bus operators with official distances or measuring e.g. with GPS the distances between the involved stations;
 - (c) For users of passenger cars, taxis, motorcycles, motorized rickshaws and other modes of motorized transport except buses based on the shortest possible geographical distance based on electronic maps or measuring the distance between the two points with GPS or a comparable mean or through distance measurement on maps;
 - (d) For non-project rail systems based on official or GPS distances between the entry and exit station of the rail-systems.
24. A default questionnaire to be used is included in Appendix 5 below. This questionnaire should be used by all projects except if valid arguments exist to change the questionnaire and to adapt it to local circumstances. The questionnaire shall be realized in the local language. The questionnaire needs to be adapted to national or local circumstances, the wording needs to be checked locally and local test-runs should be performed to ensure that the questions are simple, easily understood, cannot be misinterpreted and lead to reliable results. The survey is reviewed in the language of users of the project, not translated directly from the CDM methodology.

Appendix 5. Default Questionnaire

1. The questionnaire has to be adapted to local circumstances using local wording and language. The default questionnaire is basically the framework to follow.

SECTION A: Data concerning surveyor

Survey ID (correlative number):

Interviewer:

Date:.....

Time:

Place (station) where interview was performed:.....

Survey response/completeness:

Survey was fully completed

Survey was fully or partially not responded

Comments/Observations of surveyor:.....

SECTION B: General Data of Interviewed Person

This section can also be filled out at the end of the interview!

Age of surveyed person:

12-17 years 18-25 years 26-35 years 36-45 years 46-55 years
 56-65 years over 65 years

Gender of the surveyed person

female male

Socio-economic level of the surveyed person

< 1 minimum wage 1-2 minimum wages 2-4 minimum wages 4-6 minimum wages
 > 6 minimum wages

SECTION C: Trip Data of Interviewed Person

Question 1

“Describe the trip you are currently realizing”

Your trip origin (starting trip point, e.g. my home):.....

- 1.1. Your entry (boarding) station MRTS lane (name or code of MRTS station):.....
- 1.2. Your exit (deboarding) station MRTS lane (name or code of MRTS station):.....
- 1.3. Your final trip destination (final trip point, e.g. office):.....

Explanations for the interviewer:

- *The question refers to the current trip the passenger is making;*
- *The trip origin and the trip destination shall be identified with a clear address. Use a map if it is unclear. If the person does not know or does not want to disclose this information then stop at this point. The questionnaire is deemed thereafter as non valid;*
- *The MRTS stations identified in 1.2 and 1.3 shall be listed with their official names or codes;*
- *Only urban trips are considered. If the passenger has as trip origin or trip destination a point outside the boundaries of larger urban zone of the city then discontinue the interview. The questionnaire is deemed thereafter as non-valid.*

Question 2

“What mode of transport did you use from your trip start to the MRTS? Please refer to the mode on which you performed the longest stretch if you used various modes”

Bus (conventional not bus lane) Existing bus lane/BRT (NOT the project) Rail (NOT the project) Taxi Passenger car Motorcycle Motorized taxi tri-cycle Bike or per foot Other

Explanations for the interviewer:

- *See graph 1 for explanation;*
- *Rail refers to non-project metro, urban rail, tram etc.;*
- *Only tick 1 answer (the mode used for the longest stretch of this trip segment).*

Question 3

“What mode of transport will you use from the point where you leave the MRTS lane until your final destination? Please refer to the mode on which you will perform the longest stretch if you intend to use various modes”

Bus (conventional not bus lane) Existing bus lane/BRT (NOT the project) Rail (NOT the project) Taxi Passenger car Motorcycle Motorized taxi tri-cycle Bike or per foot Other

Explanations for the interviewer:

- *See graph for explanation;*

- Rail refers to non-project metro, urban rail, tram etc.;
- Only tick 1 answer (the mode used for the longest stretch of this trip segment).

Question 4

“Assuming that the MRTS you are currently using would not exist: Would you have made the trip you are currently doing anyway or would you have stayed at home/office/origin?”

- I would have made the trip” → Continue with question 5
- I would have stayed at home/office/origin → The questionnaire is terminated

For the interviewer:

The purpose of this question is to know if the passenger made this trip only because the MRTS exists. In absence of the MRTS he would not have made any trip and would have stayed at his point of origin.

Question 5

“Have you moved your home or workplace since the start of operations of the MRTS?”

- No → continue with question 6
- Yes: “Has the availability of the new MRTS been an important factor when choosing the location of your new home or new workplace?”
- No → continue with question 6
- Yes → “What was your original/former trip origin and trip destination?” (at the time before you moved your home or workplace)

Origin point:.....

Destination point:

Continue with question 6 (based on the origin and destination as identified)

Question 6

“Assuming that the MRTS you are currently using would not exist: How would you have made the same trip you are doing now?”

From Home/Office/Others¹ (.....) to point..... by *

From point.....to pointby *

From point.....to pointby *

From point.....to home/office/others² (.....) by *

*can be

¹ Origin of trip.

² Final destination.

- Bus (conventional not bus lane)
- Existing bus lane/BRT (NOT the project)
- Rail (NOT the project)
- Taxi → *continue with question 6A*
- Passenger car → *continue with question 6B*
- Motorcycle → *continue with question 6C*
- Motorized taxi tri-cycle → *continue with question 6D*
- Bike or per foot
- Other

Explanations for the interviewer:

- *Rail refers to non-project metro, urban rail, tram etc.;*
- *For each segment of the trip make a separate answer.*

Question 6A

“Have you used a taxi in the last 6 months?”

- Yes No

Question 6B

“Do you or your family own a car or do you have access to a car (e.g. car-sharing) or have you used a passenger car in the last 6 months?”

- Yes No

Question 6C

“Do you or your family own a motorcycle or do you have access to a motorcycle or have you used a motorcycle in the last 6 months?”

- Yes No

Question 6D

“Have you used a motorized taxi tri-cycle in the last 6 months?”

- Yes No

If interviewed persons respond in the questions 6A to 6D with NO they are not included in the final calculation i.e. this specific survey is not included as the response is deemed as non-consistent with the one given in question 6.

The project proponent shall include the questionnaire as annex to the CDM-PDD. The questionnaire is to be reviewed by the DOE. The DOE assesses if the questionnaire is in accordance with the principles (core elements of survey) specified above.

- - - - -

Document information

<i>Version</i>	<i>Date</i>	<i>Description</i>
06.0	15 May 2024	Revision to: <ul style="list-style-type: none"> • Include autonomous-rail rapid transit (ART) as one of the rail-based MRTS and the utilization of green hydrogen as a fuel for MRTS.
05.0	27 May 2021	EB 110, Annex 2 Revision to: <ul style="list-style-type: none"> • Align the requirements of sampling and survey of passengers with the “Standard: Sampling and surveys for CDM project activities and programmes of activities” and the “Guideline: Sampling and surveys for CDM project activities and programmes of activities”; • Expand the baseline scenario by adding an option for possible expansion of the existing transport system using additional vehicles; Remove the expansion factor to calculate baseline and project emissions, improving the methodology’s consistency with AM0031.
04.0	24 July 2015	EB 85, Annex 10. Revision to: <ul style="list-style-type: none"> • Introduce a reference to the tool “Baseline emissions for modal shift measures in urban passenger transport”; • Improve the approaches for additionality demonstration; • Improve guidance on the renewal of the crediting period; • Improve the language, readability, clarity and consistency.
03.0	25 November 2011	EB 65, Annex 18. Revision to: <ul style="list-style-type: none"> • Introduce a new approach to additionality demonstration; • Reduce monitoring requirements set in the MRTS passenger survey from annual monitoring to monitoring in the years 1 and 4 of the crediting period; • Remove an applicability condition requiring demonstration that the project system partially replaces a traditional public transport system in the city hosting the proposed project activity; • Remove an applicability condition restricting the use of the methodology in case more gaseous fossil fuels are used in the project activity compared to the baseline scenario;

<i>Version</i>	<i>Date</i>	<i>Description</i>
		<ul style="list-style-type: none"> • Reduce monitoring requirements (from annual monitoring to monitoring in the years 1 and 4 of the crediting period) for leakage emissions from reduced congestion as a result of the project activity in case road capacity is reduced as a result of the project activity and requires no monitoring in case road capacity is not reduced as a result of the project activity. Provides additional guidance on assessing changes in road capacity due to the project activity; • Remove the requirement to conduct a sensitivity analysis of data and parameters used to determine baseline, project and leakage emissions; • Introduce a reference to the “Tool to calculate project or leakage CO₂ emissions from fossil fuel combustion” to determine direct project emissions; • Introduce the requirement to account for leakage due to upstream emissions in case project vehicles consume more gaseous fuels than baseline vehicles; • Improve language, readability and consistency; • Title modified from “Baseline and Monitoring Methodology for Mass Rapid Transit Projects” to “Mass Rapid Transit Projects”.
02.0	30 July 2010	EB 55, Annex 14. Revision to: <ul style="list-style-type: none"> • Introduce the definition of larger urban zone (LUZ) of a city; • Accommodate situations, for the common practice analysis, where the city has less than 1 million inhabitants in its LUZ.
01.0	16 October 2009	EB 50, Annex 2. Initial adoption.

Decision Class: Regulatory
 Document Type: Standard
 Business Function: Methodology
 Keywords: transport, energy efficiency
